

barduva 

B&C



RB 150

OPEN PLATFORM LIFT


MADE IN EU



barduva

RB 150

Open Platform Lift



Barduva RB 150 is a Open Platform Lift, also known as Wheelchair Lift, which provides internal or external vertical travel up to 3 meters. Our Open Platform Lift can accommodate changes in level from 600 mm up to 3000 mm in commercial and domestic environments and is appropriate alternative solution to a fully enclosed platform lift.

RB 150 is specifically designed for applications with little or no alterations to existing buildings. The open type

design offers an aesthetically pleasing solution with brushed stainless steel finish as option. The lift provides a safe and easy way to gain access to a property where stairs would otherwise prevent wheelchair access.

It is designed to give customers choice and flexibility.

RB 150 Wheelchair Lift is a space saving and cost effective way to provide access for everyone to your home or workplace.

All our lifts are supplied with a 24-month warranty, as standard, and we offer a range of maintenance and service options, which can be tailored to suit your specific requirements.

FEATURES

- MODERN LIGHTWEIGHT DESIGN
- STAINLESS STEEL CONSTRUCTION AS OPTION
- LOW SPACE REQUIREMENTS
- HIGH LEVEL OF SECURITY
- SILENT OPERATION
- SIMPLE TO USE
- NO PIT REQUIRED
- SIMPLE TO INSTALL AND EASY TO SERVICE
- OVERALL LOW MAINTENANCE AND RUNNING COSTS



Our **Mechanical emergency fall brake for elevator** technology is under patent protection process at International level, i.e.: it has patent pending status in Lithuania Patent State Bureau and in World Intellectual Property Organization (WIPO).

SPECIFICATIONS

User group	Ambulant and wheelchair users
Suitability	For internal or external use
Travel	From 600 mm up to 3000 mm
Number of stops	2
Maximum capacity	400 kg
Platform size	1100 x 1400 mm (standard)
External dimensions	1300 x 1770 mm (standard)
Gate	950 x 1100 mm (standard) with auto closers
Cabin height	1100 mm
Drive type	Belt
Power	220-240 V, 1 phase, 16A 380-400 V, 3 phase, 10A, 50 Hz
Lighting	Controls illuminated
Safety edge	Safety edge-under platform proximity sensors
Handrail	Integrated to lift cabin (on both sides)
Machine room	Integral to guide rails
Floor	Anti slip rubber (Anti slip diamond plate for outdoor version)
Finish	RAL 9006 (White aluminium)

OPTIONS

PLATFORM
900 x 1400 mm 1000 x 1400 mm
GATE
Automatic upper gate Automatic lower gate
CONTROL
Configurable control side Dual control on the platform Auto dialer on the platform Remote control Braille on the control
SAFETY
Automatic emergency lowering device
FINISH
Painted in any RAL color Brushed Stainless Steel