

Streamvault SV-2000E

Turnkey security appliance

The Streamvault™ SV-2000E security appliance is a turnkey solution that lets you easily deploy a unified system combining video surveillance, access control, automatic license plate recognition and communications. It accelerates your project by delivering a secure appliance with Security Center pre-loaded.

Guaranteed performance

up to
> **670 Mbps**
total throughput

up to
> **2000**
readers

up to
> **75**
ALPR cameras

up to
> **560 TB**
NLSAS storage



Key features

Turnkey appliance with Genetec™ Security Center pre-installed

Video surveillance-grade NLSAS storage with RAID 5, 6 or 10 configuration

iDRAC9 Enterprise for local and remote server management

Machine learning endpoint protection

5-year hardware warranty with Keep Your Drive and Genetec Assurance with next-business day on-site service

Benefits



Design with confidence – The SV-2000E appliance delivers certified performance for a wide range of scenarios, so you know your system will meet your needs today and tomorrow.



Protect your security system – Streamvault appliances help you build a resilient security system that protects your data and operations. Our cyber security experts stay vigilant on evolving threats and help identify and address new vulnerabilities promptly.



Get up and running faster – The SV-2000E appliance is ready to install the moment you receive it. It shortens deployment time and standardizes processes across locations.

Applications

Education

Provide a safer environment for students and staff across your campus, or deploy the SV-2000E appliance as a centralized monitoring solution for multiple remote schools.

Transportation

Take advantage of advanced security capabilities, such as dynamic mapping and video analytics, and help your team efficiently monitor and respond to events across your terminal.

Retail

The SV-2000E appliance lets you standardize security processes across your entire chain. Augment video surveillance with ALPR and point-of-sale integration to make the most of your system.

Technical specifications

OS

Windows Server Standard 2019 LTSC

Processor

SV-2030E-R4/R6S:

Intel® Xeon® E-2336

Passmark: 17,162

SV-2040E-R12:

1x Intel® Xeon® Silver 4410Y 2.0GHz

Passmark: 29,585

SV-2040E-R28:

1x Intel® Xeon® Gold 5416S 2.0GHz

Passmark: 36,391

Memory

SV-2030E-R4/R6S: 16GB DDR4

SV-2040E-R12/R28: 32GB DDR5

Ethernet

SV-2030E-R4/R6S: 2x 1GbE RJ45

SV-2040E-R12/R28: 2x 1GbE RJ45

Peripherals

1x USB 2.0 + 1x USB 3.0

Video output

SV-2030E-R4/R6S/R12:

1x VGA front, 1 VGA rear

SV-2040E-R28: 1 VGA rear

Integrated Dell Remote Access Controller

iDRAC9 Enterprise

Performance

SV-2030E-R4/R6S: 465 Mbps / 300 cameras

SV-2040E-R12: 670 Mbps / 300 cameras

SV-2040E-R28: 670 Mbps / 500 cameras

Mechanical and environmental

Operating temperature

50°F to 95°F (10°C to 35°C)

Operating humidity

8 - 80% (non-condensing)

Compliance standards

IEC 60950-1, European Norm EN 60950-1,

CISPR 22/CISPR 24, EN55022/55024

Expansion

SV-2030E-R4/R6S:

1x PCIe x8 (LP) and 1x PCIe x16 (FH)

SV-2020E-/R12/R28: Up to 2x LP

Cybersecurity

Endpoint protection

BlackBerry Protect machine learning antivirus

Hardened image

200+ security setting changed by default

Maintenance

Verified Windows updates

Connected services for Genetec software and device firmware updates

Storage

Drive type

SV-2030E-R4/R6S: Hot-swap 3.5"

SV-2040E-R12/R28:

Enterprise HDD

OS drive

SV-2030E-R4:

2x 240GB SSD (RAID 1)

SV-2030E-R6S:

2x 480GB SSD (RAID 1)

SV-2040E-R12/R28:

2x 480GB M.2 NVMe (Hot Swappable)

Available drive sizes

4TB, 8TB, 12TB, 16TB, 20TB

RAID controller

SV-2030E-R4: H755 8GB NV cache

SV-2030E-R6S: H355

SV-2040E-R12: H755 8GB NV cache

SV-2040E-R28: H965i 8GB NV cache

Data RAID level

SV-2030E-R4/R6S: RAID 5; RAID 6 or RAID

10 available as options

SV-2040E-R12: RAID 5/6 or

RAID 10 available as an option

SV-2040E-R28: RAID 6 or RAID 6 + 1 hot

spare, RAID 10 available as an option

Maximum data storage

SV-2040E-R12: 240TB (raw); 218,3 TB (usable)

SV-2040E-R28: 560TB (raw); 509,3TB (usable)

Warranty and support

Hardware warranty

5-year hardware warranty with Keep Your Drive and Genetec Assurance with next business day on-site service

Security Center support

Current and two previous versions (N-2)

Models

Model	Form factor	Bays	Dimensions (W x D x H)	Max weight	Power (100-240V)
SV-2030E-R4/R6S	1U	Up to 8x 2.5" Up to 4x 3.5"	17.1" x 23.5" (3.5" HDD)/21.5" (2.5" HDD) x 1.7" (434mm x 595.6mm/545mm x 43mm)	30 lbs (13.6 kg)	2x 350W
SV-2040E-R12	2U	12	17.1" x 28.2" x 3.4" (434mm x 716mm x 87mm)	73 lbs (33.1 kg)	2x 1100W
SV-2040E-R28	2U	28	19" x 34.126" x 3.41" (482mm x 855.83mm x 86.8mm)	88.2 lbs (40 kg)	2x 1100W

Genetec Inc.

genetec.com/locations

info@genetec.com

@genetec

*Hardware specifications are subject to change. Units provided will be equivalent or superior to what is shown in this document.

© Genetec Inc., 2023. Genetec, Streamvault and the Genetec Logo are trademarks of Genetec Inc., and may be registered or pending registration in several jurisdictions. Other trademarks used in this document may be trademarks of the manufacturers or vendors of the respective products.