

Streamvault SVW-300E

Security workstation

The Genetec Streamvault[™] SVW-300E workstation is a turnkey solution designed for small and medium-sized security system monitoring. With support for multiple displays and Security Center pre-installed, it helps operators keep a watchful eye on your installations.



Key features

Turnkey workstation with Genetec[™] Security Center pre-installed

Connect up to 4 monitors

Display up to 45 full high-resolution video streams

Machine learning endpoint protection

5-year hardware warranty with next business-day on-site support and hard drive retention

Benefits



Compact design – With its small formfactor, the SVW-300E workstation fits seamlessly into your environment.



Smooth performance – The SVW-300E workstation takes advantage of the Security Center GPU-accelerated decoding feature to deliver fluid playback of live and recorded high definition video.



Turnkey deployment – All Streamvault solutions come with Security Center preloaded and ready to go, so you can get your system up and running faster.

Applications

Corporate offices

Whether you are looking to add a security workstation to your office or provide live viewing capabilities to reception staff, the SVW-300E workstation is a cost-effective solution for corporate environments.

Retail

Display live camera feeds in public areas using a discreet workstation that can be easily be stored behind the counter, and enhance safety and security.

Technical specifications

OS

Windows 11 IoT

Processor

SVW-305E-SF1: Core i7-12700 Passmark: 31,115 T3: SVW-305E-T3: Core i7-12700k Passmark: 34,784

Graphics card

SF1-S1000: 1x NVIDIA Quadro T1000 SF1-S2000: 1x NVIDIA Quadro RTX A2000 T3-S2000: 1x NVIDIA Quadro RTX A2000 T3-S4000: 1x NVIDIA Quadro RTX A4000

Display

SF1-S1000/S2000: 4x Mini-DisplayPort T3-S2000: 4x Mini-DisplayPort T3-S4000: 4x DisplayPort 1.4

Memory

16 GB DDR5

Ethernet

1GbE RJ45 Ports

OS drive

1x 512GB SSD

Storage

SF1/T3: 1 TB SATA drive

Peripherals

SF1:

Front: 1x USB 3.2 Gen1 1x USB 3.2 Type-C 2x USB 2.0 Rear: 1x USB 3.2 Gen2 3x USB 3.2 Gen1 2x USB 2.0 T3: Front: 2x USB 3.2 Gen1 2x USB 3.2 Type-C Rear: 2x USB 3.2 Gen2 2x USB 3.2 Type-C

2x USB 2.0

Genetec Inc.

genetec.com/locations info@genetec.com @genetec

Mechanical and environmental

Power supply SF1: 260W (100-240 VAC) T3: 500W (100-240 VAC)

Operating temperature SF1: 41°F to 95°F (5°C to 35°C) T3: 50°F to 95°F (10°C to 35°C)

Operating humidity SF1: 20 - 80% (non-condensing) T3: 5 - 90% (non-condensing)

Dimensions (W x D x H) SF1: 3.7" x 11.5" x 11.4"

(97mm x 292mm x 290mm) T3: 6.81" x 16.53" x 14.52" (173mm x 420.2mm x 369.3mm)

Max Weight

SF1: 11.42 lbs (5.14 kg) T3: 34.83 lbs (15.8 kg)

Certifications

IEC 60950-1, European Norm EN 60950-1, CISPR 22/CISPR 24, EN55022/55024

Cybersecurity

Endpoint protection

BlackBerry Protect machine learning antivirus

Hardened image

200+ security settings changed by default

Maintenance

Verified Windows updates Connected services for Genetec software and device firmware updates

Warranty and support

Hardware warranty

5-year warranty with next business day on-site service and Keep your own Hard Drive

Security Center support

Current and two previous versions (N-2)

© 2023. Genetec Inc. All rights reserved. Genetec, Streamvault and their respective logos are trademarks of Genetec Inc., and may be registered or pending registration in several jurisdictions. Other trademarks used in this document may be trademarks of the manufacturers or vendors of the respective products.