

# Conduit Fitting: Drain Fitting, DDF Series

Flameproof and Dust protection by enclosure

Zone 1 & 2 – 21 & 22



## Application

- The DDF drain fitting is installed at bottom of enclosure or conduit fitting to drain water formed by condensation.
- The drain fitting can be used with enclosure up to 130 litres for group IIC gases.
- The drain fitting shall not be used with any form of adaptor or reducer.

## Specification


Body material : Stainless steel, SUS 304  
 Size : 1/2 inch NPT or M20x1.5

## Technical Data

|                                 |   |                   |
|---------------------------------|---|-------------------|
| <b>Hazardous Area</b>           | <b>Gas</b>  | <b>Dust</b>       |
| <b>Zones</b>                    | 1 & 2   | 21 & 22           |
| <b>Equipment Group/Category</b> | Ex II 2G  | Ex II 2D          |
| <b>Symbol of Protection</b>     | Ex db IIC Gb  | Ex tb IIC Db IP66 |
| <b>Certificate</b>              | TÜV CY 20 ATEX 0206299 U                                    |                   |
| <b>Conformity to Standards</b>  | EN 60079-0:2012+A11:2013, EN 60079-1:2014, EN 60079-31:2014 |                   |
| <b>Ambeint Temperature</b>      | -20°C to +75°C  |                   |
| <b>Index of Protection</b>      | IP66  |                   |



Approx. Weight ; 0.080 kgs.



## Catalogue Number Logic

