




# IP Camera

WIFI SURVEILLANCE SYSTEM



# IP Camera

WIFI SURVEILLANCE SYSTEM



## Feature

- 1/2.3" CMOS Sensor / 960P(1280x960)
- Main 1280x960, 1280x720, 960x576, 720x576
- Sub 640x360, 352x288
- Focal Length 4mm.
- IR Array 4 Pcs. / 20-30M.
- IR Smart / IR CUT Support
- RJ45 x1 (Speed 100Mbps)
- Ingress Protection IP66
- Power DC Jack 12V +-10%

## WiFi IP Camera Specification

Model	HW-33B13-H3
<b>Image Sensor</b>	1/2.3" CMOS progressive scan
<b>CPU</b>	Hisilicon Hi3516EV100
<b>Pixels</b>	1.3MP
<b>Min. Illumination</b>	Color 0.1 Lux B/W 0.01 Lux
<b>Day / Night</b>	Support (Day&Night) auto switch
<b>Wide Dynamic Range</b>	Digital WDR (Auto )
<b>White Balance</b>	Auto
<b>Gain Control</b>	Auto
<b>Backlight Compensation</b>	WDR / BLC
<b>Images Setup</b>	Contrast, brightness, saturation, hue, shapen
<b>OSD Setting</b>	Support
<b>Lens</b>	
<b>Mount Type</b>	M12
<b>Focal Length</b>	4mm.
<b>Infrared</b>	
<b>IR</b>	IR LED Array 4 pcs.
<b>IR IR LED Array Distance</b>	20-30M.
<b>IR Intensity</b>	Smart IR
<b>IR-CUT</b>	Support (IR led mode, light mode, smartmode, daylight, night)
<b>Video</b>	
<b>Compression</b>	H.265/H.264
<b>Video Format</b>	PAL(50Hz)/NTS(Hz)
<b>Dual-stream</b>	Supported
<b>Image Resolution</b>	Main stream: 1280x960/1280x720/960x576/720x576 Secondary stream: 640x360/352x288
<b>Frame Rate</b>	Main 1280x960@15fps/1024Kbps. Sub 640x360@15fps/256Kbps.
<b>Bitrate Control</b>	VBR / CBR
<b>Privacy Mask</b>	Supported
<b>Network</b>	
<b>Network Protocols</b>	TCP/IP, IPv4, UPNP, HTTP, DNS, DDNS, NTP, DHCP
<b>Cloud P2P</b>	Support (www.e-seenet.com)
<b>User Interface</b>	CMS EseeCloud, IPPro3, hiviewwifi, IE11
<b>Application Programming</b>	ONVIF
<b>Wi-Fi</b>	
<b>Wireless Mode</b>	Access point/station mode/repeater
<b>Wi-Fi Standard</b>	802.11b/g/n
<b>Wi-Fi Distance</b>	300M Open area (depend on installation environment)
<b>HW-E4</b>	Supported
<b>Alarm</b>	
<b>Motion Detection</b>	Supported
<b>Maintenance and Security</b>	
<b>Account Management</b>	Supported
<b>Upgrading</b>	Supported
<b>Interfaces</b>	
<b>Ethernet</b>	RJ45 x1 (10/100/Mbps) Water-proof
<b>Power Input</b>	DC Jack x1 (12VDC)
<b>Wi-Fi</b>	x1
<b>Environmental</b>	
<b>Operating Temperature</b>	-10C ~ +50C
<b>Operating Humidity</b>	Less than 80% (no condensation)
<b>Protection Level</b>	IP66
<b>Electrical</b>	
<b>Power</b>	12V DC +- 10% (1A)
<b>Power Consumption</b>	<6W.
<b>Mechanical</b>	
<b>Weight</b>	500g.
<b>Dimensions</b>	66x180mm.
<b>Mounting Bracket</b>	White metal bullet case

