

# Floodlight CAMERA

## 2Megapixel Network Camera



## Feature

- Pixels 1920x1080 / 2MP
- Resolution Main 1920x1080 / Sub 1280x720
- Frame Rate 1-30 fps
- Led 32 pcs.
- Field of view 111°
- Focal Length 3.6 mm.
- Auto Iris Auto Electric Iris
- Day&Night Auto, Day, B/W
- IR LED IR Array 2 Pcs.
- Network Protocol IPv4,DNS, HTTP,SMTP,Onvif
- SD Card Maximum 128 Gb
- Power AC 110-240V

## Specification

Model	HP-S20LA
Pixels	1920x1080
Security Siren	110 DB
Call	Two way talk
<b>Video</b>	
Power Frequency	50Hz, 60Hz
Stream Type	Dual stream (Main, Sub)
Resolution	Main 1920x1080 Sub 1280x720
Bit Rate	32-6144 kbps
Frame Rate	1-30 fps
Video format	50,60 Hz
Image Setup	Flip, Mirror
Scene Mode	Auto, indoor, outdoor
Scene Style	Brightness, saturation, contrast, sharpness, exposure
<b>LED</b>	
Led	32 pcs.
CCT	3000K
Beam angle	120°
Wattage	12W
<b>PIR</b>	
PIR detection angle	120°
PIR detection Distance	8 Meters
<b>Lens</b>	
Field of view	111°
Focal Length	3.6 mm.
Auto Iris	Auto Electric Iris
<b>Infrared</b>	
Day&Night	Auto, Day, B/W
IR LED	IR Array 2 Pcs.
IR Intensive	Support IR Smart
IR CUT	Support IR CUT
<b>Network</b>	
Network Protocol	IPv4,DNS, HTTP,SMTP,Onvif
Wi-Fi	2.4 ghz
<b>Electrical</b>	
Power	AC 110-240V
Wattage	Max 15w
<b>Environmental</b>	
Temperature	-28°C to 65°C
<b>Mechanical</b>	
Body materia	Aluminum
Package type	Color box
Camera dimensions	13.7*13*13cm
Package box size	20*16.5*14cm
<b>Memory</b>	
Cloud Storage	Yes
SD Card Maximum	128 Gb