

# 5MPiXEL

Network Video Recorder



- 5M Input Support**
- H.265 H.264 Compression**
- HDMI Interface**
- USB Port**
- ONVIF Support**
- CMS Support**
- Free DDNS Support**
- Cloud**



Xmeye



hiviewXview



Download Application

## NETWORK VIDEO RECORDER



H.265AI NVR 32CH.

5.0 MegaPixel



## Feature

- Support 5MP x 32ch., 3MP x16., 4K x 8ch.
- Support H.265 AI Intelligent analysis encode.
- Support Startup wizard.
- Support Quick set IP camera.
- Support Tour function
- Support HDMI resolution output Max.4K (3840x2160)
- Support Hiview cloud P2P ([www.hiviewxview.com](http://www.hiviewxview.com))
- Support App "hiviewxview"
- Support OTA upgrade (Online upgrade)
- Support Free Hiview DDNS
- Support Record bitrate information table
- Support Log search and export file
- Support HDD information
- Support Import/Export Log, File config function
- Support Auto-reboot maintain system
- Support Output image adjustment
- Support Account management
- Support PTZ control

## Specification

Model	HP-8932H4
System	Embedded Linux
GUI Languages	Thai, English Etc. (More than 20)
<b>Video</b>	
Decode	H.265, H.265x, H.265AI
Video Input	4Kx8Ch / 5MPx32Ch / 3MPx16Ch
Playback	4Kx2Ch / 5MPx4Ch / 3MPx4Ch
Video Standard	PAL/NTSC
<b>Audio</b>	
Audio Compression	G.711a
Audio Intetcom	Support
<b>Record</b>	
Record Mode	Manual, Regura, Alarm, Motion, Timing
Record Period	Support 4 period mode
Serach Mode	Common / Synce / Dayparting playback mode Intelligent fast / retrieval playback mode
Storage Mode	HDD storage, Network storage
Backup Mode	Network, USB, SATA
Overwrite Mode	Support
Snapshot Mode	Support cycle capture, timing capture
<b>Channel type</b>	
Mode 1	5MP x32 / Playback x4 / Preview x32
Mode 2	3MP x16 / Playback x8 / Preview x16
Mode 3	8MP x8 / Playback x2 / Preview x8
<b>Network</b>	
Network Protocol	IPv4, IPv6, DHCP, DNS, DDNS, UPNP, HTTP PPPoE, FTP, SMTP, NTP, RTSP, DST
ONVIF	Support V2.4
Wireless 3G/4G	Support
USB Wi-Fi	Support
Free Hiview DDNS	Support



Xmeye



hiviewXview



Download Application

# NETWORK VIDEO RECORDER



H.265AI NVR 32CH.

5.0 MegaPixel



## Feature

- Support 5MP x 32ch., 3MP x16., 4K x 8ch.
- Support H.265 AI Intelligent analysis encode.
- Support Startup wizard.
- Support Quick set IP camera.
- Support Tour function
- Support HDMI resolution output Max.4K (3840x2160)
- Support Hiview cloud P2P ([www.hiviewxview.com](http://www.hiviewxview.com))
- Support App "hiviewxview"
- Support OTA upgrade (Online upgrade)
- Support Free Hiview DDNS
- Support Record bitrate information table
- Support Log search and export file
- Support HDD information
- Support Import/Export Log, File config function
- Support Auto-reboot maintain system
- Support Output image adjustment
- Support Account management
- Support PTZ control

## Specification

Model	HP-8932H4
Cloud P2P	Support ( <a href="http://www.hiviewxview.com">www.hiviewxview.com</a> )
Mobile Application	iOS&Android (hiviewxview)
OTA Upgrade	Support
Browsers Access	Support IE, Chrome, Firefox, Etc.
VMS	Support
<b>Alarm</b>	
Alarm Mode	Motion detection, video blind, video loss Abnormal alarm
Alarm Tringering	Record, tour, show message, buzzer, Email alarm, Write log, mobile reported PTZ activation, Post record
Alarm Period	Support
FTP Alarm	Support
IP Filter	Support (White list and black list)
Buzzer Alarm	Support
<b>Hardware Interface</b>	
HDMI Output	x1 (1024x768, 1280x1024, 1440x900, 1920x1080, 3840x2160)
VGA Output	x1 (1024x768, 1280x1024, 1440x900, 1920x1080)
Audio Input/Output	Input x1 (RCA)/Output x1(RCA)
Ethernet Port	x1 RJ45 (Speed 10/100/1000 Mbps)
USB 2.0	x2
USB 3.0	x1
HDD	x4 (Max. 10TB)
Cooling Fan	x1 (build-in)
<b>General</b>	
Working Temperature	0°C~+55°C
Working Humidity	10%~90% RH
Power Supply	12V/5A
Power Consumption	58mA/5W (Without HDD)
Weight	Around 1.6KG
Dimension (mm.)	440(sL)x440.5(W)x60(H)



Xmeye



hiviewXview



Download Application

# NETWORK VIDEO RECORDER