

YP5-16N



H.265+
Compression Code



YP5-16N



Feature

- Support 16ch 5M-N unreal-time encoding
- Support XVI,AHD, TVI,CVI, CVBS, IP video input
- Support VGA maximum 1080P output, HDMI up to 4K output
- Mini 1U Case, 1 SATA(Up to 8TB)
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment
- Support the Onvif protocol
- Support GB28181 (Optional)
- Cloud services, P2P, alarm information push to phone
- Support remote access, support ARSP
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- Mobile phone remote monitoring (iOS, Android)
- Multi browser access (IE, Chrome, Firefox, Safari)
- Support for more than twenty languages
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform
- Support coaxial control

Specification

1/2

Model	YP5-16N
Codec	H.265/H.264
Preview	16ch5M-N@12fps(6 in 1)/16ch 4M-N@15fps(6 in 1)/16ch 1080N@15fps(6 in 1), default 5M-N
Encode	16ch5M-N@6fps(6 in 1)/16ch 4M-N@8fps(6 in 1)/16ch 1080N@15fps(6 in 1), default 5M-N
Decode	8ch5M-N@6fps(6 in 1)/16ch 4M-N@8fps(6 in 1)/16ch 1080N@15fps(6 in 1), default 5M-N
Multi-mode	Analog:16ch 5M-N/16ch 4M-M/16ch 1080N Digital to analog conversion: support Hybird:8ch 1080N(analog)+8ch 960P (network) IP: 8ch 1080P+8ch 960P / 4ch 3M/4ch 5M
Playback	16/8ch
Audio	
Compression	G.711a
Intercom	Support
Management	
Record mode	Manual > Alarm > Motion detection >Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA
Interface	
Video input	16*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)
VGA output	1*VGA (MAX:1080P)
Audio I/O	2/1
Alarm I/O	0/0
Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
PTZ control	1*RS485, Support for multiple PTZ protocol
USB Port	2*USB2.0 ports
HDD	1*SATA interface (Up to 8TB)
General	
Temperature	0°C - + 55°C
Humidity	10% -90% RH
Power supply	12V / 2A
Consumption	<10W (Without HDD)
Weight	Around 1KG
Dimension	255mm(L)* 236mm(W)* 44mm(H)



hiviewXview

