




DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT


H.265+

Compression Code



ดาวน์โหลด แอปพลิเคชัน





Feature

- 4Ch. XVI 5-in-1, H.264/H.265
- Resolution 5MP, 4MP, 3MP, 2MP, 720P, 960H, D1
- HDD x1 (Max. 10Tb.), BNCx4, HDMIx1, VGAX1
- Audio in x1, Audio out x1, RJ45x1, USBx3
- HDMI output max. 4K
- Backup Network (IE, App, VMS), USB hard Disk, USB Burner
- Backup Format H.26X, AVI(only for H.264), MP4
- DDNS hiview.org, CN99, DynDNS, Oray, NO-IP
- Onvif Support Onvif 2.4
- USB Wi-Fi Supported Wi-Fi (Extend via USB)
- 4G Supported / Cloud Support
- Power supply DC12V/2000mA.

H.265+

Compression Code




ดาวน์โหลด แอปพลิเคชัน



Specification

1/3

Model	HA-85504
Video system	5-in-1 (AHD,TVI,CVI,CVBS,IPC)
Video compression	H.264, H.265
Audio compression	G.711A
Video standard	PAL/NTSC
Intercom	Supported
View	
GUI Language	Thai, english, Chinese Etc. (28 Languages)
Resolution Output	1024x768,1280x720,1280x1024,1440x900, 1920x1080,3840x2160
Output Image Adjust	Supported
Local live view	1/4 (Depend on mode)
Local playback	4CH. (Depend on mode)
Network live view	Depend on channel type mode
Network playback	1CH. (IE)
E-Zoom	Support live view&playback mode
Dwell/Tour	Supported
Rigion cover	Support (Max. 4 areas adjustable)
Channel OSD Setting	Supported
Image Setting	Supported
Channel type	
Mode 1	Local 4M x4, Playback x4,Preview x4
Mode 2	Local 5M x4, Playback x1,Preview x4
Mode 3	Local 1080P x4, Playback x4,Preview x4
Mode 4	Local 4M x4 + IPC 4M x4, Playback x1,Preview x8
Mode 5	IPC 1080P x16, Playback x2,Preview x16
Mode 6	IPC 5M x8, Playback x1,Preview x8
Preview Custom Mode	Support
Video streaming	
Stream type	Support Dual stream (Main, Sub)
Bit rate control	CBR, VBR
Main stream resolution	5MP, 4MP, 3MP, 2MP, 720P, 960H, D1
Preview Ability	4x5M@12fps (6in1), 4x4M@15fps (6in1), 4x3M@18fps (6in1), 4x1080P@25fps (6in1)
Encode Ability	4x5M@6fps (6in1), 4x4M@8fps (6in1), 4x3M@10fps (6in1), 4x1080P@15fps (6in1)
Decode Ability	1x5M@6fps (6in1), 4x4M@8fps (6in1), 4x3M@10fps (6in1), 4x080P@15fps (6in1)
Main stream	5MP@6fps, 4MP@8fps, 3MP@9fps, 1080P@15fps, 720P/960H/D1@25fps
Substream	CIF/D1@25fps (Depend on mode)
Record Quality	Lowest, lower, low, high, higher, highest
SnapShot	Supported (Cycle capture, timing capture)
Recording	
Storage mode	HDD, Network
Record length	1-120s
Pre-Record	Supported 1-30s
Record mode	Regular, Detect, Alarm, Snapshot



Feature

- 4Ch. XVI 5-in-1, H.264/H.265
- Resolution 5MP, 4MP, 3MP, 2MP, 720P, 960H, D1
- HDD x1 (Max. 10Tb.), BNCx4, HDMIx1, VGAX3
- Audio in x1, Audio out x1, RJ45x1, USBx3
- HDMI output max. 4K
- Backup Network (IE, App, VMS), USB hard Disk, USB Burner
- Backup Format H.26X, AVI(only for H.264), MP4
- DDNS hiview.org, CN99, Dyndns, Oray, NO-IP
- Onvif Support Onvif 2.4
- USB Wi-Fi Supported Wi-Fi (Extend via USB)
- 4G Supported / Cloud Support
- Power supply DC12V/2000mA.

H.265+

Compression Code



ดาวน์โหลด แอปพลิเคชัน



Specification

2/3

Model	HA-85504
Time period/Expired	Support 4 period
Recording Status	Supported
HDD Over write	Supported (Overwrite / Stop record)
HDD	
HDD Management Mode	Read/Write, Read only, Redundant, Partition. Snapshot
HDD Info	Support view recording time, type&capacity, Record Time.
Search / Playback	
Search Mode	Regular, alarm, manual, intelligent
Playback Mode	Common playabck, sync playback, dayparting, intelligent fast playback, intellugent retrieval
Function	Play, Playback backward, Stop, Slow playback, reverse fast, fast forward, prev file, next file, repeat playback, full screen, Reverse fast, Fast playback, Repaet playback, Full screen, Video Clip
E-Zoom	Supported
Back up	
Backup Mode	Network (IE, App, VMS), USB hard Disk, USB Burnner
Backup Format	H.26X, AVI(only for H.264), MP4
Player Software	Player, Etc.
Alarm	
Alarm Mode	Motion detection, video blind, video loss, Alarm input, Alarm output, Intelligent Alarm
Intelligent Alarm	Perimeter alert, Items care, Video diagnosis
Human Detection	Supported
Alarm Schedule	Supported
Alarm Tringgering	Recording, Tour, Snapshot, PTZ activate, show message, write log, mobile reported, send email, FTP upload, show message, Buzzer, FTP, Email, Wite log, Mobile report
Abnormal / Others alarm	No Storage, Strorage device error, Storage no space, Net Disconnection, IP conflict
Network	
Netwok protocol	IPv4,IPv6, DHCP, HTTP, NTP, Email, DDNS, PPPoE, UPNP, FTP, Onvif, ARSP, RTSP, SMTP, DST
DDNS	hiview.org, CN99, Dyndns, Oray, NO-IP
Onvif	Support Onvif 2.4
USB Wi-Fi	Supported Wi-Fi (Extend via USB)
4G	Supported
Cloud	Support cloud service, P2P, alarm information push (www.hiviewxview.com)
Mobile monitoring	Support iOS&Android (hiviewxview)
Push Notify	Supported



Feature

- 4Ch. XVI 5-in-1, H.264/H.265
- Resolution 5MP, 4MP, 3MP, 2MP, 720P, 960H, D1
- HDD x1 (Max. 10Tb.), BNCx4, HDMIx1, VGAX1
- Audio in x1, Audio out x1, RJ45x1, USBx3
- HDMI output max. 4K
- Backup Network (IE, App, VMS), USB hard Disk, USB Burner
- Backup Format H.26X, AVI(only for H.264), MP4
- DDNS hiview.org, CN99, DynDNS, Oray, NO-IP
- Onvif Support Onvif 2.4
- USB Wi-Fi Supported Wi-Fi (Extend via USB)
- 4G Supported / Cloud Support
- Power supply DC12V/2000mA.

Specification

3/3

Model	HA-85504
IP Filter	Supported (Black list/White list)
Network status	Support
PTZ Function & OSD Control	
COC	Support XVI (XVI control, Image enhance, upgrade, sensor config)
Functions	
Start Up Wizard	Supported
User Interface	Account management, IE, App, VMS
Account Management	Supported
Auto Logout	Supported (0-60Min.)
Log	Support log export
SDK	Supported
Import&Export config	Supported
System Upgrade	Support USB, Network, OTA
Auto Maintenance	Supported (Auto reboot)
System Restore	Supported
Hardware Interface	
BNC input	x4CH. (BNC)
HDD	x1 (Max. 10TB)
HDMI output	HDMI x1 HDMI / VGA simultaneous video output
VGA output	VGA x1 HDMI/VGA simultaneous video output
Audio I/O	Input 1 RCA/ Output 1 RCA
RJ45	x1 (10/100M Mbps) self-adaption
USB 2.0	x3
Power input	DC12V
Others	
Power supply	DC12V / 2000mA.
Power consumption	<15W (Without HDD)
Working environment	0C to +55C
Working Humidity	10% to 90%, Atm:86kpa—106kpa
Dimension	168x80mm.
Weight	720g.

H.265+

Compression Code



ดาวน์โหลด แอปพลิเคชัน

