

HA-524B20E

AHD CAMERA SERIES

4-in-1 (AHD/TVI/CVI/CVBS)





AHD CAMERA SERIES

4-in-1 (AHD/TVI/CVI/CVBS)















Feature

- Sony 1/2.7" CMOS progressive scan
- 4-in-1 (AHD/TVI/CVI/CVBS)
- Frame rate"30fps@60Hz / 25fps@50Hz"
- "Color: 0.01 lux@F1.2, AGC ON) 0 lux with IR B/W: 0.001 lux@F1.2, AGC ON) 0 lux with IR"
- Lens size 3.6mm. / IR SMD 18 Pcs.
- IR distance 15-35M. / IP66

Function

- Function control OSD (COC control) COCSupport
- OSD language Support English, Etc. adjustable
- Grobal exposure / ATW/ MWB / DNR Support
- GAIN / D-WDR / AGC / BLC / FLC Support
- 2D-DNR / Brightness / Sharpness Support
- Image setting Support Contrast, Color gain

Specification

Model HA-524B20E

Solution Sony 1/2.7" CMOS progressive scan

Video system 4-in-1 (AHD / TVI / CVI / CVBS)

Video format PAL/NTSC

Video resolution 1920x1080P/720P

CVBS resolution 960H (960x576 Pixels)

Min. illumination "Color: 0.01 lux@F1.2, AGC ON) 0 lux with IR

B/W: 0.001 lux@F1.2, AGC ON) 0 lux with IR"

Electric shutter | Auto: 1/50s(1/60s) to 1/100,000s (PAL)

Frame rate "30fps@60Hz / 25fps@50Hz"

S/N ratio >58dB.

Ingress protection IP66

Lens

Lens size 3.6mm.

F/No. / Lens mount F1.2 / M12

Infrared

IR type IR SMD 18 Pcs.

IR distance 15-35M.

Day&Night Support color, B/W, Auto, Ext adjustable

ICR Siwtch Support IR filter (IR-CUT)

IR Smart Support

Hardware interface

Video output BNC female x1 (1Vp-p Composite Output(75 Ω /BNC)

Power input DC Jack x1

Cable OSD Cable

Electrical

Power supply DC12V(+-10%)

Power consumption Max.5W.

Others

Surge protection 4KV,

Working environment | -10°C to +50°C

Working humidity 10% to 90%

Dimension / Weight | 64mm*179mm / 370g.

