

HA-42516

Hybrid H.264 Cloud DVR 4000Series

5-in-1 (AHD/TVI/CVI/ANALOGUE/IP)



Characteristics

H.264 High profile compression format
5-in-1 System
New GUI N9000
Support 4 CH IPC Max. 3MP.
Support CMS (NVMS-1000)
Support Remote control via IE
Support HDMI Output 1080P
Support NAT (CLOUD QR CODE)
Support App (Superliveplus)
Support 2-Way Audio
Support CVBS Output as Main or SPOT
Support Instant Playback
Support E-Zoom
Support Snapshot
Support Smart Search Playback (Time-sliced Image)
Support System Info. Checking
Support Start up Wizard
Support Mobile Client Stream Self-adaption
Support View LOG&Export
Support Auto Maintenance
Support Backup&Recover System Config.
Support Local&Network Upgrade
Support Account and Authority management
Support Black and White List
Support Online User status checking
Support Hiview DDNS and Etc.
Support Telnet for Professional Debug
Support Storage Mode
Support S.M.R.T. information (HDD)
Support Recording Expire Date
Support Privacy Mask
Support channel adjust position live view
Support Dwell (Freely adjustable)

Packaging Include Accessories

1. DVR x1 Pc.
2. Switching Adaptor 12V/4A. x1 Pc.
3. Remote Control x1 Pc.
4. Battery AAA x2 Pcs.
5. Optical Mouse USB x1 Pc.
6. SATA Cable x 2Pcs.
7. Screw x4 Pcs. (For HDD)
8. Quick User Manual book x1 Pc.
9. CD Software x1 Pc.

Specification

System Compression
Main Chipset
AD Chipset
OS
GUI
Resolution
Video System
AD Chipset
Local Layout
Network Layout
Protocol
Web Client
Mobile Device

Interface

Video Input
Audio Input
Audio Output
HDMI Output
VGA Output
CVBS Output
Ethernet Port
Alarm Input
Alarm Output
USB 2.0
RS485
Power Input
HDD

IP Camera Input

IP Access Bandwidth
IP Resolution
Frame Rate

Recording

Main stream

Substream

Mode

Playback

Playback
Search Mode
Function

Alarm

Mode
Triggering

Backup

Local Backup
Network Backup
Power Input
Working Temperature
Dimensions

System Ver. Info.

MB Ver. TW2716TE-C(V12/NV9000) 1611181988
HW Ver. 20027-V1.2
Kernel Ver. GAAC-G857-GAAB
FW Ver. 1.0.4.0R2.B61213L.0.D002.U1(16A42T)

Standard H.264 High Profile

Hisilicon Hi3531A

Techpoint TP2833

Embedded Linux

N9000 16-bit True Color

1080P, 720P, WD1 Real Time

PAL/NTSC

Techpoint TP2833

Live view 1,4,6,8,9,13,16,20/Playback 1,4,9,16

Live view 1,4,8,9,10,16,25/Playback 1,4,9

TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, DST

Max 5 users online

iOS, Android (Superliveplus)

BNC x16

RCA x4

RCA x1

x1 (1920x1080, 1280x1024)

x1 (1920x1080, 1280x1024)

BNC x1 (Spot or Main)

LAN x1 (RJ45 10M/100Mbps)

x4

x1 (3A/250V AC, 3A/30V DC)

x2

x1 (Connect to PTZ or Keyboard)

x1

SATA x2 (Max. 6T)

IPC x4(24Mbps)

Max. 3.0MP. (2048x1536, 2304x1296, 1920x1080, 1280x720)

3.0MP@25fps

1080P, 960P, 720P@25fps(PAL)/30fps(NTSC)

1080P@12fps, Bitrate 512-1024kbps

1080 Lite/1208x720P/960x576(WD1)@25fps

1920x1080@12fps Bitrate 128-1024kbps

1280x720, 704x576, 352x288@25fps Bitrate 128-1024kbps

Manual, Timer, Motion, Sensor, Cycle record, Schedule

Local playback 1,4,9,16Ch

Time slice Image, Time, Event, Tag Search, Image Management

Play, Pause, FF(X32), FB(X1/32), Digital Zoom, Etc..

Manual, Sensor, Motion, Exception

Record, Snap, Preset, Email, Buzzer, Alarm out, Preset, Pop-up

U-disk, USB Mobile HDD (AVI/Private format)

Support (AVI format)

DC12V/2A, Power Consumption <8W. (without HDD)

-10°C~+50°C, 10%~90% Humidity

300x270x55(WxDxH)

Specification are subject to change without notice. (Last updated 20/1/2017)