



Road Barrier

Specification

สินค้าและผลิตภัณฑ์ไม้กั้นประตูเข้าออก

Model		HV-BR04	
Drive control	Microprocessor-Control		
Control	Desk-Top Console, Remote Controller, Induction Loop, Photo-Electric Barrier,		
Safety	Infrared sensors to be used to prevent barriers from closing on the vehicle.		
Casing			
Dimensions	288*361*1037mm (W*D*H)		
Material	Cold Rolled Carbon Structural Steel		
Paint	Brand: Akzonobel (Made In Netherlands) Automobile Grade Spray Coating		
Outdoor	Application		
Protection	All housing and internal parts to have rust & corrosion free metal or alloy of high strength with suitable epoxy coating as applicable.		
Material	Aluminium Alloy-octagonal-pole, powder coated, colour white with red stripes		
Length	Max 6m/5s		
Boom Support	Fixed		
Dimension			
Motor			
Type Of Motor	Worm And Gear Motor		
Power Supply	230v Ac±15%	Power Frequency	50/60hz
Rated Power	80W 220V AC	Rated Current	1.35a±10%
Environment Temperature	-20c~50c	Protection Class	IP55
Withstand Voltage Strength	1800v/5ma/1s No Breakdown	Working Noise	≤60db
Rated Speed	420 R/M±5%	Speed Reducing Ratio	1/50
Service Life	≥5million Times		
Time for up/down	5s	Arm	6m



HV-BR04