



5000 SERIES

IP CAMERA SUVEILANCE



3M PIXEL HD

IP Camera Series

3M
Pixel

**H.265X
H.264**
Compression

ONVIF
Support

PoE
Support

**DAY & Night
D&N**
Support

LED
Smart IR

BLC
Support



5000 SERIES

IP CAMERA SUVEILANCE



Specification

1/2



Feature

- 1/2.7" SC4239 CMOS sensor
- CPU Hisilicon Hi3516EV200
- Resolution 3MP / 2MP / 720
- H.265 / H.265X
- Fixed lens 3.2mm / M12
- IR SMD 18 pcs/IR Distance 10-30M
- Audio Input x1 (RCA, external)
- Metal bullet case, IP66
- Power supply 12VDC / PoE(af)

Model	HP-55D30PE
Image Sensor	1/2.7" SC4239 CMOS progressive scan
CPU Hisilicon	Hi3516EV100
Pixels	3MP/2MP
Min. Illumination	Color 0.1 lux@F1.2 / BW 0.01lux@F1.2
Shutter Speed	1/50(1/60s) to 1/10,000s
Slow Shutter Mode	Low, medium, high
Day / Night	EXT (IGR) / AUTO / Color / BW
White Balance	Supported
BLC / AGC	Supported
Image Brightness Adjust	Supported
Image Contrast Adjust	Supported
Image Sharpness Adjust	Supported
Image Saturation Adjust	Supported
DNR / DWDR	Supported
Defoging / Anti Flicker	Supported
Image Flip / Image Mirror	Supported
Regiaon Cover	Supported (Max. 4 ares)
Lens	
Mount Type	M12
Auto Iris	Auto Electric Iris
Focal Length	Fixed lens 3.2mm.
Focus Control	Manual
Infrared	
IR Type	SMD 18 Pcs
IR Distance	10-30M
IR-CUT	Support IR-CUT filter
IR Intensity	Smart IR (Auto)
IR-Swap	Supported
Video	
Video Format	PAL/NTSC
Video Encode	H.265 / H.265X
Smart Encode	Supported
Video Stream	Dual Stream
Image Resolution	Main: 3MP@25fps (PAL), 2MP@25fps (PAL), 720P@25fps (PAL) Sub: D1@25fps (PAL), CIF@25fps (PAL)
Bitrate Control	VBR / CBR
Privacy Masking	Supported





5000 SERIES

IP CAMERA SUVEILANCE



Specification

2/2



Feature

- 1/2.7" SC4239 CMOS sensor
- CPU Hisilicon Hi3516EV200
- Resolution 3MP / 2MP / 720
- H.265 / H.265X
- Fixed lens 3.2mm / M12
- IR SMD 18 pcs/IR Distance 10-30M
- Audio Input x1 (RCA, external)
- Metal bullet case, IP66
- Power supply 12VDC / PoE(af)

Model	HP-55D30PE
OSD	Supported
Audio	
Audio Encode	G.711A
Network	
Network Protocols	TCP/IPv4, DHCP, HTTP, DNS, DDNS, NTP, UPNP, ONVIF, FTP, SMTP, RTSP
DDNS Provider	Hiview DDNS, CN99, Dyn dns, Oray, NO-IP
User Interface	IE, App, VMS
Application Programming	ONVIF
Account Management	Supported
Alarm / Security / Maintain	
Motion Detection	Supported
Human Detection	Supported
Video Blind Alarm	Supported
IP Filtering	Supported
Image Storgae	Supported Email / FTP (Interval time setting)
Reboot Maintain	Supported
Import&Export Config.	Supported
Log Serach	Supported
Upgrading Software	Supported
Alarm Trigger	Send email, FTP, write log, record
Interfaces	
Ethernet	x1 (10/100M, RJ45 water-proof interface)
Audio Input	x1 (RCA)
Power Supply	x1 (DC jack female)
Environmental	
Operating Temperature	0C ~ +40C
StorageTemperature	-20C ~ +60C
Operating Humidity	90% RH
Protection Level	IP66
Surge Protection Level	6KV
Electrical	
Power	12V DC +- 10% /POE
POE Standard	IEEE 802.3af (15.40W)
Power Consumption	IR OFF: 1.7W / IR ON: 4.7W
Mechanical	
Case Matirial	Metal bullet
Weight	0.30Kg.
Dimensions	181x63x63mm.

