



DVR 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT

H.265

Compression Code



Xmeye



hiviewXview

ดาว์โหลด แอพพลิเคชัน

Available on the
App Store

GET IT ON
Google play

5M
Pixel Camera
Support

H.265+
Compression

HDMI
Interface

USB Port

Cloud(P2P)

CMS
Support

Mobile APP

Free DDNS



DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT



Feature

- Support 32ch 5M-N unreal-time encoding
- Support AHD, TVI, CVI,CVBS, IP video input
- HDMI/VGA simultaneous video output
- BIG 1U Case, 2 SATA(Up to 8TB)
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment
- Support the Onvif protocol
- Support GB28181 (Optional)
- Cloud services, P2P, alarm information push to phone
- Support remote access, support ARSP
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- Mobile phone remote monitoring (iOS, Android)
- Multi browser access (IE, Chrome, Firefox, Safari)
- Support for more than twenty languages
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform
- Support coaxial control

H.265
Compression Code

Specification

Model	HA-85532H2
processor	Hi3531D
Video	
Codec	H.265/H.264
preview	32ch 5M-N@12fps(6 in 1)/32ch 4M-N@15fps(6 in 1)/32ch 1080P@15fps(6 in 1)/32ch 1080N(6 in 1).default 5M-N
Encode	32ch 5M-N@6fps(6 in 1)/32ch 4M-N@8fps(6 in 1)/32ch 1080P@8fps(6 in 1)/32ch 1080N@15fps(6 in 1).default 5M-N
Decode	8ch 5M-N@6fps(6 in 1)/16ch 4M-N@8fps(6 in 1)/16ch 1080P@8fps(6 in 1)/16ch 1080N@15fps(6 in 1).default 5M-N
Multi-mode	Analog:32ch 5M-N/32ch 4M-N/32ch 1080N Digital to analog conversion : support Hybird:8*1080N(analog)+8*960P(network) IP: 32ch 1080P/16ch 3M/8ch 5M
Playback	16/8ch
Audio	
Compression	G.711a
Intercom	Support
Management	
Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA
Interface	
Video input	32*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:1080P)
VGA output	1*VGA (MAX:1080P)
Audio I/O	16/1
Alarm I/O	8/1
Ethernet port	1*10/100/1000Mbps Ethernet port, RJ45 port
PTZ control	1*RS485,1个RS232; Support for multiple PTZ protocol
USB Port	2*USB2.0 ports
HDD	2*SATA interface (Up to 8TB)
General	
Temperature	0C - + 55C
Humidity	10% -90% RH
Power supply	12V/4A
Consumption	<10W (Without HDD)
Weight	Around 3KG
Dimension	440mm(L)* 290mm(W)* 50mm(H)



ดาว์โหลด แอพพลิเคชัน

Available on the
App Store

GET IT ON
Google play