

**HP-30B30PEL-M**



## 3MPixel Smart LED Dual Light



Application  
**P6slite**



**3MPIXEL**   
WIFI Camera Series



## Feature

- \* Pixels 3.0 Mega Pixel
- \* Effective Pixels 2560\*1440P
- \* Compression H.264/H.265
- \* TV System PAL / NTSC
- \* Usable Illumination 0.001Lux
- \* Ethernet RJ-45 (10/100M)
- \* Protocol optional ONVIF2.4 / Hikvision
- \* Smart Phone iPhone, iPad, Android, Android Pad
- \* DWDR / WDR DWDR
- \* Recording Mode NVR/NAS/CMS/Web
- \* Audio G.711
- \* Focus Length F1.3 3.6mm
- \* Focus Control Fixed
- \* Infrared LED 3PCS Smart dual-chip LED
- \* Infrared Distance 35M
- \* IR Status Under 10 Lux By CDS
- \* Power Source DC12V±10%, 1000mA

## Specification

Model	HP-30B30PEL-M
Pixels	3.0 Mega Pixel
Image Sensor	GC2083
Main processor	FH8852V201
Effective Pixels	2560*1440P
TV System	PAL / NTSC
Main stream	2560*1440/2303*1296/1920*1080/1280*720
Sub-stream	800*448/704*576/640*360/352*228
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec NTSC 1/1-1/10000Sec
Usable Illumination	0.001Lux
S/N Ratio	52dB
Video Output	Network
<b>Network</b>	
Ethernet	RJ-45 (10/100M)
Protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, IP Search
Protocol optional	ONVIF2.4 / Hikvision
P2P	Support
POE	Support
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Smart Phone	iPhone, iPad, Android, Android Pad
Frames Per Second	25Fps
<b>Camera Features</b>	
Day / Night	when people come in Monitor Area, it is warm light full color at night ,when people leave , will be infrared B/W at night
Compression	H.264 / H.265
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK (Flicker Control)



Application  
**P6slite**



**3M** PIXEL **HD**  
WIFI Camera Series





## Feature

- \* Pixels 3.0 Mega Pixel
- \* Effective Pixels 2560\*1440P
- \* Compression H.264/H.265
- \* TV System PAL / NTSC
- \* Usable Illumination 0.001Lux
- \* Ethernet RJ-45 (10/100M)
- \* Protocol optional ONVIF2.4 / Hikvision
- \* Smart Phone iPhone, iPad, Android, Android Pad
- \* DWDR / WDR DWDR
- \* Recording Mode NVR/NAS/CMS/Web
- \* Audio G.711
- \* Focus Length F1.3 3.6mm
- \* Focus Control Fixed
- \* Infrared LED 3PCS Smart dual-chip LED
- \* Infrared Distance 35M
- \* IR Status Under 10 Lux By CDS
- \* Power Source DC12V±10%, 1000mA

## Specification

Model	HP-30B30PEL-M
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
DWDR / WDR	DWDR
Recording Mode	NVR / NAS / CMS / Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
Audio	G.711
<b>Lens</b>	
Focus Length	F1.3 3.6mm
Focus Control	Fixed
Lens Type	Fixed
<b>Night Vision</b>	
Infrared LED	3PCS Smart dual-chip LED
Infrared Distance	35M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
<b>General</b>	
Housing	Platic+Metal
Bracket	YES
IR Cut Filter	YES
Operation Temperature	-10 ~ +50 RH95% Max
Storage Temperature	-20 ~ +60 RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	187*60*72mm
Weight	0.4kg



Application  
**P6slite**

