



FHD IP CAMERA SERIES
Wireless/LED Light

2MP PIXEL
IP Camera Series



IP CAMERA 3000 SERIRES



P6SLite

Download on the
App Store

GET IT ON
Google Play



FHD IP CAMERA SERIES
Wireless/LED Light

Specification



Feature

- 1/2.9" High-resolution CMOS Sensor
- Resolution 2MP, 1920(H)*1080(V)
- Focus Length Board Lens 3.6mm/F2.0
- Infrared LED 4PCS Warmlight and 4pcs IR LED Meter: 25M
- Infrared Distance 25M
- IR Status Under 5 Lux By Auto
- Audio Two way Audio
- SD Card Slot Support MAX 128G
- Wifi Support Built-in WIFI
- Power Source DC12V±10%, 500mA

2MP PIXEL
IP Camera Series



Model	HP-30MPT202W
Image Sensor	1/2.9"High-resolution CMOS Sensor
Resolution	2MP
Effective Pixels	1920(H) * 1080(V)
TV System	PAL / NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥39dB
Scanning System	Progressive
Video Output	RJ45, WIFI
Reset Button	YES
PTZ	
Horizontal Rotation Range	0~355
Tilt Rotation Range	0~90
Speed	30 / SEC.
LENS Type	
Focus Length	Board Lens 3.6mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	3MP
Night Vision	
Infrared LED	4PCS Warmlight and 4pcs IR LED Meter: 25M
Infrared Distance	25M
IR Status	Under 5 Lux By Auto
IR Power On	CDS Auto Control
Camera	
Day/Night	Default night vision is black and white , when there are objects moving , the video will be converted to color
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR , White Balance, FLK (Flicker Control)
Corridor Pattern	Support
OSD	Support WEB and APP Control
Defog Mode	NO
BLC	Support
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR / NAS / VMS / Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands, Czech
Interface	
Audio	Two way Audio
Alarm	Support humanoid automatic tracking, two way Audio,Built-in loudspeaker warning,Speaker alarm can record its own sound;
SD Card Slot	Support MAX 128G
Wifi	
Wifi	Support Built-in WIFI
General	
Housing	Plastic IP66
Anti-cut Bracket	Anti-Cut 3-Axis
IR Cut Filter	YES
Operation Temperature	-20~ +60 RH95% Max
Storage Temperature	-20~ +60 RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	Size: 130x130)x 87mm
Weight	Weight 0.5g



P6SLite

