



# IP Camera HP-39BP20IR3



**DOME CAMERA IR PTZ**

**IP Camera Series**



## Features

- 2.0 MP FULL HD-IP
- 100M IR Distance
- All Cast Aluminium Material
- Powerful 20x/30x optical zoom / Support ONVIF
- Video Analysis Light-Adjustment Technology
- Auto Tracking
- IP 66 all-environments protection

## Specification

MODEL	HP-39BP20IR3
Image Sensor	1/2.8" Progressive Scan CMOS
Resolution	1080P(1920X1080)
Mini Illumination	0.05 Lux (Colour) (F1.6,AGC ON), 0.01 Lux (B/W) (F1.6,AGC ON)
Lens	f=4.3~135 mm
IRIS	F1.6~F22
Angle of View	59.8(wide) ~ 2.34(tele)
Min Object Distance	10mm~1500mm
Optical Zoom	30x
Electronic Shutter	1/25~1/30,000s
Day/Night	ICR (Auto/color/black)
Focus / AGC / BLC	Auto/Manual
White balance	Auto/Manual
SNR	>52dB
WDR	Support
Mirror Image	Level, Tilt, Centre
Noise Reduction	3D
NETWORK PARAMETER	
Solution	HISILICON 3516D
Video Coding	H.264/H.265
Dual-stream	Support
Image Resolution	*Main stream:1920x1080,1080P,1280X960,960P,1280X720,720P Sub stream:704x576 / D1 352X288 CIF"
Audio Coding	G.711ulaw
ONVIF Protocol	Support
NETWORK PROTOCAOL	
Port	TCP/IP,HTTP,DHCP,DNS,DDNS,RTSP,RTSP,PPPoE,NTP,UPnP,SNMP,SMTPTFP 1 channel audio input, 1 channel audio output, 1 channel alarm input, 1 channel alarm output, 1channel network port, 1channel analog output, 1channel power supply input
DOME PARAMETER	
IR Distance	100m
Pan Range	360°
Tilt Range	-10°~90° auto flip
Manual Speed	Horizontal: 0.01°/s - 350°/s,Vertical: 0.01°/s - 120°/s
Preset Speed	Pan: 350°/s, Tilt: 120°/s
Preset	256
Auto Cruising	8 groups (32 Preset/group)
Auto Scan	8 groups (setup left and right boundary)
Pattern Scanning	4 groups
Bracket	Wall mount
OSD Menu	English/Chinese
Timing function	Support
Alarm	1input/1output
Power Supply	DC12V+-10%
Power consumption	≤50W
Working Temp	-35°C+60°C
Working Humidity	<95%, no condensing
Protection Level	IP66, the secondary lightning protection, 3000V anti-surge design
Weight	6.5kg

