

hi-view[®]

HP-9632



Features

- Solution 1/28" SONY IMX124+HI3516D
- Resolution 3.0MP.
- Optical zoom 20X F=5.5-110mm./ F1.6-F3.5
- Support Auto focus
- Support SD Card Max. 128GB.
- Alarm input x1 / Alarm output x1
- Network RJ45 x1 (10/100Mbps)
- Mic input x1 / Speaker output x1
- Support 2-way-audio
- Support Menu OSD (Preset 95)
- Support App SuperlivePlus, NVMS-1000, NVMS-5000
- Support Brewers IE11 (Live view, Search. Config)
- Power supply AV24V. /300mA.
- Protection Level IP66
- Weight 3.5Kg.

Specification (1)

Solution	1/28" SONY IMX124+HI3516D
Resolution	3.0MP.
Optical zoom	20X F=5.5-110mm./ F1.6-F3.5
Support	Auto focus
Min. Illumination	0 Lux
Support	IR Array 5Pcs. / IR Smart
IR Distance	100M.
Video compression	H.264 / H.265
Main Stream	2048x1536, 1920x1080, 1280x720 @25fps, CBR/VBR, Bitrate 512-8192. H.264/H.265.
Sub Stream	704x576, 352x288 @25fps, CBR/VBR, Bitrate 128-2048. H.264/H.265./JPEG
Third Stream	704x576, 352x288, 480x240 @25fps, CBR/VBR, Bitrate 128-2048. H.264/H.265./JPEG
Stream snapshot	1@248x1536, 2@704x576, 3@352x288
Support	PAL/NTSC 50Hz/60Hz
S/N Ratio Max	48dB.
Support SD Card Max.	128GB.
Alarm input	x1
Alarm output	x1
Network RJ45	x1 (10/100Mbps)
Mic input	x1
Speaker output	x1
Support	2-way-audio
Support	Menu OSD (Preset 95)
Support	App SuperlivePlus, NVMS-1000, NVMS-5000
Support	Brewers IE11 (Live view, Search. Config)
Support	Camera temp. Checking
Onvif version	2.3
Support IR	on/off adjustable (Via IE)
Support Day&Night	(Auto, Day, Night, Timing)
Support IR Sensitivity adjustable	(Low, Mid, High, Custom)
Pan Range	360
Pam Speed	240/s., Manual control speed 0.5-90/s
Tile Range	0-93
Tile Speed Preset speed	160/s., Manual control speed 0.5-90/s
Preset	255, Cruise 8, Track 4, Scan 2, Home position



hi-view[®]

HP-9632



Features

- Solution 1/28" SONY IMX124+HI3516D
- Resolution 3.0MP.
- Optical zoom 20X F=5.5-110mm./ F1.6-F3.5
- Support Auto focus
- Support SD Card Max. 128GB.
- Alarm input x1 / Alarm output x1
- Network RJ45 x1 (10/100Mbps)
- Mic input x1 / Speaker output x1
- Support 2-way-audio
- Support Menu OSD (Preset 95)
- Support App SuperlivePlus, NVMS-1000, NVMS-5000
- Support Brewers IE11 (Live view, Search, Config)
- Power supply AV24V. /300mA.
- Protection Level IP66
- Weight 3.5Kg.

Specification (2)

Support	Smart 3D zoom
Support	Focus limit (30Cm. 1M, 1.5M, 2M, 3M, 5M, 10M)
Support	Camera initial
Support	Auto PTZ flip
Support	Preset, Cruise, Group, Trace, Task, Alarm, Home position
Support	Scan
Support	Motion Alarm (Area and sensitivity adjustable, Motion Schedule)
Support	Motion Alarm Triggering (Alarm out, Snap, Email, FTP)
Support	Alarm input x1 (NO/NC), (Alarm input schedule)
Support	Alarm output (Alarm holding time)
Support	Alarm server
Support	IP change notification
Support	online user
Support	BLC (Enable/Disable)
Support	3D DNR (Auto/Low/Middle/High)
Support	Defog (Level 1-4)
Support	color adjustable (Color level, Brightness, Sharpness)
Support	White balance (Auto, Indoor, Outdoor, Manual)
Support	AE Mode (Auto, Bright, Shutter, Iris)
Support	AGC (Level 0-15)
Support	Mirror (Disable, Mirror, Rota, Flip)
Support	User management
Support	Block and allow lists (IP filtering, MAC filtering)
Support	Config import/Export setting)
Support	Online upgrade
Support	LOG (Search, Export)
Support	DDNS (88ip, dns2P, meibu, dyndns, no-ip, dvrtydns, mintdns, and 123ddns)
Support	Protocol NTP, TCP IPv4, PPPoE, DDNS, SNMP, RTSP, UPnP, Email, FTP
Power supply	AV24V. /300mA.
Power consumption	15W. (Max 30W. IR ON)
Working Environment	Temp. -20C~+60C, Humidity less than 95%
Protection Level	IP66
Lighting protection	TVS6KV, surge protection
Weight / Dimension	3.5Kg. / ϕ 209x317