

HV-P0910



คุณสมบัติหลัก

- Power supply output 9Ch.
- Power input AC110V~220V
- Power output DC12V/10A.
- Support LED indicator status for each output when problem occurs only affect the individual output, other outputs still working;
- Support short circuit protection with PTC fuse (Restoring circuit)
- Support over current protection
- Application for security systems, CCTV, TZ, IR Illuminator, Video processor, Access Control Etc.
- CE, FCC, RoHS

รายละเอียดสินค้า

| | |
|---------------------------|--|
| Input Voltage | AC 100~240V, 50-60Hz |
| Input Frequency Range | 50Hz/60Hz |
| Output Voltage | DC11.8V-15.9V |
| Output Voltage Adjustment | Support |
| Total Output Current | 10A. |
| Total Output Channel | 9CH |
| Output Power | 120 Watt. |
| Fuse Type | "Polymer PTC Resetable fuse (JK60 200) (Max. voltage 60Vdc, Max. 2 ampere) สามารถต้านทานทางได้สูงสุด 60 โวลต์, กระแส 2แอมป์" |
| Fuse Rating | 2A |
| Ripple & Noise | <=150mv |
| Efficiency | >=80% |
| Operating Temperature | .-20°C+60°C, 20%~90%RH |
| Storage Temperature | .-40°C~+85°C, 10%~95%RH |
| Product Net Weight | 1.64kg |
| Product Dimension | 201.5x238.5x61.5mm. |
| Material | Metal |
| Package Dimension | 250x6x215mm. |