

PTV / PTZ DOME
Mini



RoHS
CE

HV-mPTZ



HV-mPTZ

Features:

- 1/4" SONY Super HAD CCD ICR Camera
- High resolution 480 TV lines , 0.03 Lux (ICR ON)
- 10x optical (3.78-37.8mm) and 10x digital zoom to give a total of 100X Zoom
- OSD on screen display
- AGC, ALC, AES, 48 zone BLC setting, AWB, Preset Mask, or manual control 48 motion detection zones, Image froze
- 360 Degree Rotation, 32 Preset Positions
- Pan Speed Up to 30°/S; Tilt Speed Up To 30°/S
- 6 Auto Cruising Track
- Dimensions: ø 127 mm x 187 mm(H)

Colour / Monochrome

SONY Super HAD Mini Dome

Specifications:

Model Number	HV-mPTZ
SYNC System	Internal Mode / External (AC-Lock) Mode +/- 1Hz
Scanning System	1:2 Interlace
Pick Up Device	1/4" SONY Super HAD CCD
Effective Pixels	NTSC:768(H) x 494(V) / PAL:752(H) x 582(V)
S/N	More than 46dB (r=1, AGC OFF, APC OFF, Y Out)
Horizontal Resolution	480 TV Lines
Lens	F1.6(W)~1.9(T) f=3.7(W)~37.8(T) mm
Zoom	10X Optical Zoom and 10X Digital Zoom
White Balance	ATW / AWB / FIX (Zero Colour Rolling)
ALC	Auto / FIX (OSD Control)
AGC	Auto Gain Control (+24dB Max.)
BLC Function	48 Zone BLC (OSD Control)
ICR Function	Yes
Illumination	0.03 Lux (ICR ON)
Video Signal Output	1.0 Vp-p / 75Ω
GAMMA Correction	0.45 / 1
Electronic Shutter	AES: 1/60(1/50) ~ 1/120,000 sec. / Manual: Steup in OSD
External Control	RS-485
Pan	Speed 0.5~30 °/s
Tilt	Speed 0.5~30 °/s
Preset	32 Preset Positions (Max)
Auto Cruise	6 Auto Cruising Tracks (Max)
Operation Temperature	-30°C~50°C
Operation Humidity	Within 85% RH
Power Source	DC12V +/- 1.0V, 6 W (max)