

IP CAMERA SERIES

8800 SERIES



HD IP CAMERA

IP CAMERA SERIES

8800 SERIES



Specification



Feature

- 2.07M. 1/2.9" CMOS sensor
- HD 1080P Resolution, Image clear, Delicate
- HD lens:3.6mm@F1.8
- H.265/H.265+/H.264/H.264+HighProfile
- Day/Night (Auto ICR)
- Auto electronic shutter time
- IR range: 25 LED 20m-30m
- Support DWDR, 3D DNR
- Protection IP67
- Support PoE

Model	Hmp-88B30PE
Image Sensor	1/2.9" Sony IMX323 CMOS sensor
Image Resolution	2048x1536 (3.14MP), 1920x1080P (2.07MP)
Shutter Time	1/50(1/60)s ~1/10,000s
Slow Shutter Mode	Support auto electronic shutter time
Min. Illumination	Color : 0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W : 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
Image setting	OSD setting, BLC, ATW, Defog, AGC, DWDR 3DNR, Anti flicker, Flip, Mirror, IR-swap
Lens	
Lens	Fixed HD lens 3.6mm./F1.8
Lens Mount	M12
Infrared	
Day&Night	IR-Cut filter with auto switch (Full color, B/W)
IR LED	25 Pcs.
IR Distance	20-30 Meters
Video	
Video Compression	H.265/H.265+/H.264/H.264+HighProfile, JPEG
Video Format	PAL/NTSC
Stream Type	Dual stream (main, sub)
Video Bite Rate	0.1Mbps~8Mbps
Bitrate Control	CBR/VBR
Main Stream Resolution	3M, 1080P, 720P, D1
Sub Stream Resolution	D1, CIF
Video Frame Rate	PAL: 3MP@15fps./1080P@25fps NTSC:13MP@15fps/1080P@30fps
Audio	
Audio Compression	G.711a
Audio Input	x1 (RCA)
Networking	
Network Protocol	TCP/IPv4, IPv6, HTTP, DHCP, DNS, DDNS PPPoE, SMTP, NTP, UPNP, FTP, RTSP
Hiview DDNS	Support free hiview DDNS
ONVIF	Onvif 2.4
Network Interfaces	IE, VMS, App
Cloud P2P	Support
Alarm	
Alarm Mode	Motion detection, video blind, Email, FTP
IP Filter	Support black list and white list
Mobile Reported	Support App push alarm
Maintenance	
Account Management	Support added max.60 users and permission setting
Auto-Reboot	Support
Log Search	Support log export
Import/Export	Support import/export config
Upgrading	Support via network upgrade
Hardware Interfaces	
RJ45	x1 (Speed 10/100Mbps Ethernet port)
Audio Input	x1 (RCA)
Electrical	
Power Supply	DC12V± 10%/POE
Power Consumption	Max. 5W
POE	Support class 0 (IEEE 802.3af, 15.4 Watt. 48V)
Others	
Working Temperature	-10 °C~+60 °C
Working Humidity	10%-90% RH
Ingress Protection	IP67
Weight	430g
Dimension	59x62.5x210mm.
Case Material	Metal bullet