



Wi-Fi CAMERA

4Mpixel WiFi Bullet IP Camera

HP-53B40WI



iCsee

App Free Download

Cloud IE: www.xmeye.net

4MPIXEL HD



Wi-Fi CAMERA

4Mpixel WIFI Bullet IP Camera



Feature

- * Image Sensor 4.0M 1/2.8" CMOS sensor
- * Pixels 2560(H) x 1440(V)
- * Min. Illumination Color: 0.01Lux @F1.2
B/W: 0.001 Lux @F1.2
- * Video Encoding Format H.265X
- * Main Stream 4MP@20fps Max. bitrate 10240Kb/s
- * Substream D1@20fps Max. Bit rate 2560 Kb/s
- * Fixed lens 3.6mm / F1.6
- * IR LED 2 Pcs and white light 2pcs / 20-30M.
- * Mobile Application iCsee (Android&iOS)
- * Wi-Fi 2.4Ghz / Cloud / ONVIF Support
- * Power DC12V / Ø5.5*2.1mm

3

Specification

Model	HP-53B40WI
Image Sensor	4.0M 1/2.8" Low illumination CMOS sensor
Pixels	2560(H) x 1440(V)
Min. Illumination	Color: 0.01Lux @F1.2 B/W: 0.001 Lux @F1.2
Shutter Speed	1/50 (1/60) - 1/10,000s
Video Encoding Format	H.265X
Video Coding Rate	32 Kbps~8Mbps
Audio Format	G.711
Stream	Dual steam
Main Stream	4MP @ 20fps Max. bit rate 10240Kb/s
Sub Stream	D1 @ 20fps Max. Bit rate 2560 Kb/s
Bitrate control	CBR / VBR
Signal System	PAL / NTSC
Image Control	BLC, ATW, AGC, DWDR, Defoging, Mirror, Flip, Anti Flicker, IR Swap
Lens	
Mount Type	Ø12
Auto Iris	Auto Electric Iris
Focal Length	Fixed lens 3.6mm/F1.6
Focus Mode	Manual focus
Angle of View	89°
Infrared	
IR LED	IR LED 2 Pcs and white light 2pcs
IR Distance	20-30M.
IR Intensive	Support IR Smart (Level adjustment)
IR CUT	Support IR CUT
Day&Night	Star IR, full color, Black & white,smart alert
Network	
Protocol	TCP/IPv4, NTP, DHCP, DNS, PPPoE, DAS, RTSP, DDNS
Mobile Application	iCsee (Android&iOS)
Connection mode	Wi-Fi 2.4Ghz
AP Mode	Support
Browsers	IE, VMS
Hiview.org	Support
Cloud	Support (https://xmeye.net)



Cloud IE: www.xmeye.net



Wi-Fi CAMERA

4Mpixel WIFI Bullet IP Camera



Feature

- * Image Sensor 4.0M 1/2.8" CMOS sensor
- * Pixels 2560(H) x 1440(V)
- * Min. Illumination Color: 0.01Lux @F1.2
B/W: 0.001 Lux @F1.2
- * Video Encoding Format H.265X
- * Main Stream 4MP@20fps Max. bitrate 10240Kb/s
- * Substream D1@20fps Max. Bit rate 2560 Kb/s
- * Fixed lens 3.6mm / F1.6
- * IR LED 2 Pcs and white light 2pcs / 20-30M.
- * Mobile Application iCsee (Android&iOS)
- * Wi-Fi 2.4Ghz / Cloud / ONVIF Support
- * Power DC12V / Ø5.5*2.1mm

3

Specification

Model	HP-53B40WI
ONVIF	YES
Network Upgrade	Support
User Management	Support
Auto Maintain	Support
Import & Export Config	Support
Recording & Playback	
Overwrite	Support
IE Playback	Support
Application Playback	Support
Record schedule	Regular, Detect, Alarm
Alarm & Triggering	
Alarm Type	Motion, Video Blind, IP Filter, Privacy Mask, Beep sound, humanoid detect
Motion Triggering	Mobile Reported, alarm sound, write log, buzzer, alarms lights
Electrical	
Power	DC 12 V / Ø5.5*2.1mm
Power Consumption	<8W Max.
Environmental	
StorageTemperature	-20°C ~+ 60°C
Operating Temperature	0°C ~+ 40°C
Working Humidity	90% RH (Non-Condensing)
Hardware Interface	
Wi-Fi Antenna	Support 2.4Ghz (built-in)
RJ45	x1 (100 Mbps)
TF-Card	x1 (Max. 128GB)
Mic Build-in	x1 Passive microphone
Speaker Build-in	Support
Reset Button	Support
LED Indicator Status	x1
Power Input	DC12V
Mechanical	
Case Material	Metal Case
Weight	400g
Dimension	183mm*71mm*60mm



Cloud IE: www.xmeye.net