

# IP CAMERA SERIES

## 8800 SERIES



**HD** IP CAMERA

# IP CAMERA SERIES

## 8800 SERIES



### Specification



### Feature

- 2.07M. 1/2.9" CMOS sensor
- HD 1080P Resolution, Image clear, Delicate
- HD lens:3.6mm@F1.8
- H.265/H.265+/H.264/H.264+HighProfile
- Day/Night (Auto ICR)
- Auto electronic shutter time
- IR range: 24 LED 20m-30m
- Support DWDR, 3D DNR
- Protection IP67
- Support PoE

Model	Hmp-88D30PE
Image Sensor	1/2.9" Sony IMX323 CMOS sensor
Image Resolution	2048x1536 (3.14MP), 1920x1080P (2.07MP)
Shutter Time	1/50(1/60)s ~1/10,000s
Slow Shutter Mode	Support auto electronic shutter time
Min. Illumination	Color : 0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W : 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
Image setting	OSD setting, BLC, ATW, Defog, AGC, DWDR 3DNR, Anti flicker, Flip, Mirror, IR-swap
<b>Lens</b>	
Lens	Fixed HD lens 3.6mm./F1.8
Lens Mount	M12
<b>Infrared</b>	
Day&Night	IR-Cut filter with auto switch (Full color, B/W)
IR LED	24 Pcs.
IR Distance	20-30 Meters
<b>Video</b>	
Video Compression	H.265/H.265+/H.264/H.264+HighProfile, JPEG
Video Format	PAL/NTSC
Stream Type	Dual stream (main, sub)
Video Bite Rate	0.1Mbps~8Mbps
Bitrate Control	CBR/VBR
Main Stream Resolution	3M, 1080P, 720P, D1
Sub Stream Resolution	D1, CIF
Video Frame Rate	PAL: 3MP@15fps./1080P@25fps NTSC:13MP@15fps/1080P@30fps
<b>Audio</b>	
Audio Compression	G.711a
Audio Input	x1 (RCA)
<b>Networking</b>	
Network Protocol	TCP/IPv4, IPv6, HTTP, DHCP, DNS, DDNS PPPoE, SMTP, NTP, UPNP, FTP, RTSP
Hiview DDNS	Support free hiview DDNS
ONVIF	Onvif 2.4
Network Interfaces	IE, VMS, App
Cloud P2P	Support
<b>Alarm</b>	
Alarm Mode	Motion detection, video blind, Email, FTP
IP Filter	Support black list and white list
Mobile Reported	Support App push alarm
<b>Maintenance</b>	
Account Management	Support added max.60 users and permission setting
Auto-Reboot	Support
Log Search	Support log export
Import/Export	Support import/export config
Upgrading	Support via network upgrade
<b>Hardware Interfaces</b>	
RJ45	x1 (Speed 10/100Mbps Ethernet port)
Audio Input	x1 (RCA)
<b>Electrical</b>	
Power Supply	DC12V±10%/POE
Power Consumption	Max. 3W
POE	Support class 0 (IEEE 802.3af, 15.4 Watt. 48V)
<b>Others</b>	
Working Temperature	-10 °C~+60 °C
Working Humidity	10%-90% RH
Ingress Protection	IP67
Weight	390g
Dimension	96x73mm.
Case Material	Metal dome