



## Feature

- Using CAT.5 network patch cords support power for the wireless AP and IP Camera
- Networking standard: IEEE802.3af/t
- Long distance transmission and power supply, maximum transmission distance is 130m
- Upload port automatic flip (Auto MDI/MDIX)
- Network performance: Store-and-forward
- Intelligent power distribution and secure power supply system
- Power circuit protection function can protect equipment
- Zero configuration feature power supply is automatically supplied to the adaptive equipment
- Professional thunder design, Overtemperature protection, short circuit protection, high reliability, high stability
- Nature cooling, small, compact, mute, all the design are convenient for you put
- Support: port no-load saving power

## Specification

Model	HG-CSW10 2P8
Network Interface	PoE(1-8) up-Link(7-8)/LAN1-2 1000Mbps Full Duplex; 100 or 1000Mbps Half Duplex
Transmission Rate	Network Interface: 10BASE-T or 1000BASE-TX RJ45 port of Ethernet Bandwidth:9.2 Gbps (no barriers)
Performance & Specification	Network Latency (10 to 1000Mbps): ≤20μs (use the 64 byte package size) MAC address table: 8K The Frame Filter & Transmission Rate 14800pps the most for 10M port, 1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX / IEEE802.3ab 1000BASE-TX IEEE 802.3x Flow Control IEEE 802.3af/at Power over Ethernet
PoE Core of Power Cable Power Support	Default: 1/2(+), 3/6(-); (Can Be Selected 4/5(+), 7/8(-)) Power input: AC 180~240V 120W Power input: PoE port 1-8 1/2 (+52V), 3/6 (GND)/DC 5525 5V1A
Physical Specifications	Size (L*W*H): 310mm*260mm*100mm
Working Environment	Operating Temperature: -10C ~ 55C (-14 ~ 131F) Storage Temperature: -40C ~ 70C (-104 ~ 158F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5% ~ 90% non-condensing
Electromagnetic Compatibility	CE mark FCC Part 15, Class B VCCI Class B EN 55022 (CISPR 22) C-Tick
Warranty	Whole machine: 1 Year
Package Content	AC Power Cable、Installation Manual Warrantny Card

