



3MP **PIXEL** **HD**
4G PT Dome camera



Feature



- * 4G PT Dome camera 4G
- * Resolution 3MP
- * Sensor 1/3" CMOS Sensor
- * Shutter Shutter adaptation
- * Lens 4mm
- * IR Distance IR 20-30m, spotlight 15m
- * Video Compression H.265 / H.264
- * Frame Rate Max 15fps
- * Interface Micro SD Card (max 256G)
- * Cloud Storage Support
- * Power Adapter DC 12V 1A

Specification

| Model | | HW-33MPT302-4G |
|-------------------------|---|----------------|
| Resolution | 3MP | |
| Sensor | 1/3" CMOS Sensor | |
| Shutter | Shutter adaptation | |
| Lens | 4mm | |
| Rotation Angle | Pan: 0~263 0.1~20/S Tilt :0~105 0.1~20/S | |
| Day-night | mode Infrared filter | |
| DNR | 3D digital noise reduction | |
| Dynamic Range | Digital WDR | |
| IR Distance | IR 20-30m, spotlight 15m (depends on environment) | |
| Compression Standard | | |
| Video Compression | H.265 / H.264 | |
| Video Compression | HD / SD | |
| Audio Coding Format | AAC / G711A | |
| Image | | |
| Resolution | Main stream: 2304 *1296 Sub stream: 640x360 | |
| Frame Rate | Max 15fps | |
| Image reversal | Support mirror and flip reversal | |
| Privacy Masking | Support | |
| Alarm Function | | |
| Intelligent Alarm | Motion detection | |
| Alarm Notification | Alarm notification push | |
| Storage | | |
| Interface | Micro SD Card (max 256G) | |
| Cloud Storage | Support | |
| Wireless Spec | | |
| Wireless Standard | 4G: LTE-TDD/LTE FDD; WIFI:802.11bgn | |
| Wireless Frequency Band | LTE-FDD: B1/B3/B5/B8 LTE-TDD: B40 WIFI: 2400MHz-2483.5MHz | |
| General Specs | | |
| Working Temperature | -20°C~50°C, Working Humidity: <95% | |
| Working Humidity | <95% <95% (no condensation) | |
| Power Adapter | DC 12V 1A | |