



# NVR 8900 SERIES

# 5MPiXEL HD

Network Video Recorder



- 5M Input Support
- H.265+ H.265 H.264 Compression
- HDMI Interface
- USB Port
- ONVIF Support
- CMS Support
- Free DDNS Support
- Cloud



Xmeye



hiviewXview



Download Application

## NETWORK VIDEO RECORDER

## ONVIF



## Feature

- \* 9ch 5M video input / H.265+ / H.265 / H.264
- \* VGA, HDMI video output
- \* Mini 1U Case, 1SATA(Up to 14TB)
- \* 1\*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port
- \* Automatic networking support, a key to add equipment
- \* Support the Onvif protocol / Support GB28181
- \* Cloud services, P2P, alarm information push to phone
- \* Support remote access, support ARSP
- \* Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL
- \* 3G, WIFI, IP search, Alarm center, etc
- \* Mobile phone remote monitoring (iOS, Android)
- \* Multi browser access (IE, Chrome, Firefox, Safari)
- \* Support for more than twenty languages
- \* Perfect protection circuit, unique triple watchdog function
- \* Support WEB, CMS, VMS, MYEYE Platform
- \* Support AI functions config like Face detection and human detect etc

## Specification

Model	HP-8909
System	Embedded Linux
<b>Video</b>	
Video input	9ch 5M
Playback	5M (1+1) /4M(2+1) / 3M(2+2) / 1080P(4+2)
Decode	H.265+ / H.265 / H.264
<b>Audio</b>	
Compression	G.711a
Intercom	Unsupport
<b>Management</b>	
Record mode	Manual > Alarm > Motiondetection > Timing
Inquire mode	Inquire by Time / Calendar / Event / Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA
<b>Interface</b>	
HDMI output	1*HDMI (MAX:2K)
VGA output	1*VGA (MAX:1080P)
Ethernet port	1*RJ45 1*10/100Mbps Ethernet port,
POE ports	N/A
Audio I/O	0/1 (3.5mm)
Alarm I/O	0/0
USB Port	2*USB2.0 ports
HDD	1*SATA interface (Up to 14TB)
<b>General</b>	
Temperature	0C- + 55C
Humidity	10% -90% RH
Power supply	12V/2A
Consumption	<10W (Without HDD)
Weight Around	1.0KG
Dimension	255(L)* 208mm(W)* 43mm(H)



Xmeye



hiviewXview



Download Application

# NETWORK VIDEO RECORDER