



NEW **STAR LIGHT**
กล้องสตาร์ไลท์ เปลี่ยนกลางคืนให้เป็นกลางวัน
 → 
คือกลางวัน กลางคืน
คือกลางคืน กลางวัน

HD **AHD CAMERA SERIES**
CCTV SURVEILLANCE **Star Light Camera**

Specification



Function

- Function control OSD (COC control)
 - OSD language Support English, Etc. adjustable
 - Global exposure / COC Support
 - D-WDR / AGC / Sens-Up / BLC Support
 - HSBC Support / Ultra-WDR Support (120dB)
 - ATW / AWB / 2D-DNR / 3D-DNR Support
 - Brightness / Defogging / Cam title Support
 - Freeze / Mirror Support
 - Neg. image / Motion detection Support
 - Privacy mask Support
 - Defect Support (Live DPC, White DPC, Black DPC)
 - Sharpness / LSC Support
 - Image setting Support
- (Black level, Gamma, Blue gain, Red gain)

Model	HA-924B20ST
Solution	1/2.8" Sony CMOS progressive scan Sensor
Video system	4-in-1 (AHD/TVI/CVI/CVBS)
Video format	PAL/NTSC
Video resolution	1920x1080P
Effective pixel	2.13MP.
CVBS resolution	960H CVBS output (1000TVL.)
CVBS Comet	Support
Min. illumination	Color: 0.001 lux@F1.2, AGC ON, B/W: 0 lux with IR ON
Electric shutter	Auto:1/50s to 1/100,000s (PAL), Auto: 1/60s to 1/100,000s (NTSC)
Frame rate	30fps@60Hz, 25fps@50Hz
S/N ratio	>52dB. (AGC OFF)
Ingress protection	IP66
Lens	
Lens size / F.No.	3.6mm. / F1.2
Lens mount	M12
Infrared	
IR type	IR LED 42 Pcs.
IR distance	20-30M.
Day&Night	Support color, B/W, Auto, Ext adjustable
ICR swithc	Support IR filter (IR-CUT)
IR smart	Support adjustable
Hardware interface	
Video output	BNC female x1
Power input	DC Jack x1
Cable	Switch Cabel
Electrical	
Power supply	DC12V(+/-10%)
Power consumption	IR OFF: <1W., IR ON: <4W.
Others	
Surge protection	4KV, Anto static 6KV(touch), 8KV(Gas)
Working environment	-20C to +50C
Working humidity	10% to 90%
Dimension / Weight	87x219.4mm. / 537g.