



**CAMERA 9700 SERIES**  
4Megapixel Network Camera

**H.265**  
Compression Code

**4MP** **PIXEL** **HD**  
Network Camera Series



# IP CAMERA

## 4MP Bullet Camera

H.265	WDR	AWB	Defog	HLC	BLC	Motion Detection	PoE	IP67	VCA	-20°~55°



# CAMERA 9700 SERIES

## 4Megapixel Network Camera

# IP CAMERA

## 4MP Bullet Camera



### Feature

- \* 4MP (2560 x 1440) H.265 coding
- \* Max.resolution: 2560 1440
- \* ICR auto switch, true day / night, ROI coding
- \* 3D DNR, digital WDR, HLC, BLC, defog
- \* 10~20m IR night view distance
- \* DC12V/PoE power supply
- \* P2P function optional
- \* IP 67 ingress protection
- \* Support three streams
- \* Support mobile surveillance by smart phones& tablet PCs with iOS and Android OS
- \* Intelligent analytics: object removal detection, abnormal video signal detection, line crossing detection and region intrusion detection

# H.265

Compression Code

# 4MPiXEL HD

Network Camera Series

### Specification

Model	HP-97B402PE
Image Sensor	1/2.7 "CMOS
Image Size	2560 x 1440
Electronic Shutter	1s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.011 lux @F1.2, AGC ON; 0 lux with IR 0.04 lux @ F2.2, AGC ON; 0 lux with IR
Lens	3.6 mm @F2.2, (fixed lens), horizontal field of view: 89°
Lens Mount	M12
Wide Dynamic Range	Digital WDR
BLC / HLC / Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0~360°; Tilt:0~80°; Rotation: 0~360°
<b>Image</b>	
Video Compression	H.265 / H.264
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
Main Stream	60Hz: 4MP(1~20fps)/3MP(1~30fps)/1080P(1~30fps); 50Hz: 4MP(1~20fps)/3MP(1~25fps)/1080P(1~25fps)
Sub Stream	60Hz: 720P(1~15fps)/D1 /CIF (1~30fps); 50Hz: 720P(1~12fps)/D1(1~25fps)/CIF (1~25fps);
Third Stream	60Hz: D1/CIF/480x240 (1~30fps); 50Hz: D1/CIF/480x240 (1~25fps)
Bit Rate	64 Kbps ~ 5 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
<b>Interfaces</b>	
Network	RJ45
<b>Functions</b>	
Remote Monitoring	Web browsing,CMS remote control
Online Connection	Support simultaneous monitoring for up to 4 users; Support multi-stream real time transmission
Network Protocol	UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion detection
Intelligent Analytics	Region intrusion detection, object removal detection, abnormal video detection and line crossing detection
General function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock
PoE	Yes
IR Distance	10 ~ 20m
Ingress Protection	IP67
<b>Others</b>	
Power Supply	DC12V/PoE
Power Consumption	<4W
Operating Environment	-20C ~ 55C (-4F~131F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	162.1 x 74.8 x 73.8
Weight (net)	Approx. 0.24KG
Installation	Ceiling mounting; Wall mountin
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) directive 94/62/EC and REACH(EC1907/2006)