

5MPiXEL

Network Video Recorder



Xmeye



hiviewXview



Download Application

NETWORK VIDEO RECORDER

H.265+ NVR 8 CH 4.0/5.0 MegaPixel



Feature

- Support Startup wizard.
- Support Quick set IP camera, search/add IPC via NVR menu.
- Support Hiview cloud P2P (www.hiviewxview.com)
- Support App "hiviewxview"
- Support OTA upgrade (Online upgrade)
- Support Hiview DDNS
- Support Tour function
- Support Record bitrate information table
- Support Log search and export file
- Support HDD information
- Support Import/Export Log, File config function
- Support Auto-reboot maintain system
- Support Output image adjustment
- Support Account management
- Support PTZ control

Specification

1/2

Model	HP-8908
CPU	Hisilicon Hi3336D
System	Embedded Linux
GUI Languages	Thai, English Etc. (More than 20)
VIDEO	
Decode	H.265+/H.264+
Video Input	4MPx8CH/5MPx4CH
Video Standard	PAL/NTSC
AUDIO	
Audio Compression	G.711a
Audio Intetcom	Support
RECORD	
Record Mode	Manual, Regura, Alarm, Motion, Timing
Record Period	Support 4 period mode
Serach Mode	Common playabck Intelligent fast playback
Storage Mode	HDD storage, Network storage
Backup Mode	Network, USB, SATA
Overwrite Mode	Support
Snapshot Mode	Support cycle capture, timing capture
CHANNEL TYPE	
Mode 1	4MP@8CH/ Playback x1, Priview x8
Mode 2	5MP@4CH/ Playback x1, Priview x4
NETWORK	
Network Protocol	IPv4, IPv6, DHCP, DNS, DDNS, UPNP PPPoE, FTP, SMTP, NTP, RTSP
Wi-Fi	Support (Extenal USB Wi-Fi 2.4Ghz)
ONVIF	Support
Cloud P2P	Support (www.hiviewxview.com)
Mobile Application	iOS&Android (hiviewxview)
OTA Upgrade	Support
Browsers Access	Support IE11
VMS/CMS	Support (Freeware)
Hiview DDNS	Support (Free)



Xmeye



hiviewXview



Download Application

NETWORK VIDEO RECORDER

H.265+ NVR 8 CH 4.0/5.0 MegaPixel



Feature

- Support Startup wizard.
- Support Quick set IP camera, search/add IPC via NVR menu.
- Support Hiview cloud P2P (www.hiviewxview.com)
- Support App "hiviewxview"
- Support OTA upgrade (Online upgrade)
- Support Hiview DDNS
- Support Tour function
- Support Record bitrate information table
- Support Log search and export file
- Support HDD information
- Support Import/Export Log, File config function
- Support Auto-reboot maintain system
- Support Output image adjustment
- Support Account management
- Support PTZ control

Specification

2/2

Model	HP-8908
Alarm Mode	Motion detection, video blind, video loss Abnormal
Intelligent Alarm	Support perimeter alert, items care video diagnosis
Alarm Tringering	Record, tour, show message, buzzer, send email, Write log, mobile reported PTZ activation, Post record
Alarm Period	Support
FTP Alarm	Support
IP Filter	Support (White list and black list)
Buzzer Alarm	Support
Mobile Reported	Support
Hardware Interface	
HDMI Output	x1 (1024x768, 1280x1024, 1440x900, 1920x1080)
VGA Output	x1
Audio Output	x1 (RCA)
Ethernet Port	x1 RJ45 (Speed 10/100Mbps)
USB 2.0	x2
HDD	x1 (Max.10TB.)
Alarm Buzzer	x1 (Built-in PCB)
General	
Working Temperature	0C~+55
Working Humidity	10%~90% RH
Power Supply	12V/2A
Power Consumption	<10W (Without HDD)
Weight	Around 1KG
Dimension (mm.)	255(L)x236(W)x44(H)



Xmeye



hiviewXview



Download Application

NETWORK VIDEO RECORDER