



# NVR 8800SERIES

## FULL HD SURVEILLANCE



## NETWORK VIDEO RECORDER

H.264



HDMI



USB



IP PTZ

FREE  
DDNS



IVS



Cloud

## Specification

1/2



## Feature

- H.264, H.264+, MJPEG/JPEG
- Audio Compression G.711A
- Video Standard PAL/NTSC
- Backup Mode Network, USB hard Disk, USB Burnner
- Backup Format H.264, AVI
- DDNS CN99, DynDNS, Oray, NP-IP, MYQ-SEE, Hiview
- Support cloud service, P2P, alarm information push
- OSD language Support Thai, English, Chinese Etc.
- Two-way-audio Supported
- HDD SATA 2.5 x1 (Max. 10TB)
- HDMI 1.3 x1 (Max. 1920x1080P)
- VGA x1 (Max. 1920x1080P)
- RJ45 x1 (10/100M Mbps) self-adaption
- USB 2.0 x3 / Power Input DC12V

Model	Hmp-8804NE
Video Compression	H.264, H.264+, MJPEG/JPEG
Audio Compression	G.711A
Video Standard	PAL/NTSC
View	
Local live view	1/4 Layout depend on channel type mode
Local playback	depend on channel type mode
Network live view	depend on channel type mode
Network playback	1Ch.
E-Zoom	Support live view & playback mode
Dwell	Support
Privacy mask	Support Max. 4 area
Channel Type	
Mode 1	1080Px4Ch./Local playbackx1
Mode 2	960Px8Ch./Local playbackx1
Mode 3	D1x8Ch./Local playbackx4
Video Streaming	
Stream Ttype	Support Dual stream
Bit Rate Control	CBR, VBR
Main Stream	Max. 1080P@25fps, Bit rate 8192 kb/s (Depend on mode)
Sub Stream	Max. D1@25fps, 2560 kb/s (Depend on mode)
Record Quality	Adjustable (VBR Mode)
Recording	
Storage Mode	HDD, Network
Record Length	1-120s
Record Mode	Timing, Manual, Motion, Alarm
Time Period/Expired	Support 4 period
Recording Status	Support
HDD Over Write	Support
HDD	
HDD Management	Read/Write, Read only, Redundant, Partition
HDD Info	Support view recording time, type&capacity, Record Time.
Search / Playback	
Search mode	Regular, Alarm, Manual
Function	Play, Playback backward, Stop, Slow playback, Reverse fast, Fast playback, Repeat playback, Full screen, Video Clip
Sync Playback	Support
E-Zoom	Support
Backup up	
Backup Mode	Network, USB hard Disk, USB Burnner
Backup Format	H.264, AVI
Alarm	
Alarm Mode	Video motion, Video blind, Video loss, Alarm input
Alarm Tringgering	Record channel, Tour, PTZ activate, Show message, FTP, White log, Email, Mobile reported
Abnormal Others Alarm	Storage device not exist, Storage spacelack alarm Storage device access failure



Xmeye



hiviewXview



# FULL HD SURVEILLANCE



## Specification

2/2



## Feature

- H.264, H.264+, MJPEG/JPEG
- Audio Compression G.711A
- Video Standard PAL/NTSC
- Backup Mode Network, USB hard Disk, USB Burnner
- Backup Format H.264, AVI
- DDNS CN99, Dyndns, Oray, NP-IP, MYQ-SEE, Hiview
- Support cloud service, P2P, alarm information push
- OSD language Support Thai, English, Chinese Etc.
- Two-way-audio Supported
- HDD SATA 2.5 x1 (Max. 10TB)
- HDMI 1.3 x1 (Max. 1920x1080P)
- VGA x1 (Max. 1920x1080P)
- RJ45 x1 (10/100M Mbps) self-adaption
- USB 2.0 x3 / Power Input DC12V

Model	Hmp-8804NE
Network	
Network Protocol	IPv4, IPv6, DHCP, NTP, Email, DDNS, PPPoE, UPNP, FTP, Onvif 2.4, ARSP, RTSP, DST
DDNS	CN99, Dyndns, Oray, NP-IP, MYQ-SEE, Hiview
Cloud	Support cloud service, P2P, alarm information push
Mobile Monitoring	Support iOS, Android
Block / Allow list	Support
Uses Online	Support (Trigger Disconnect)
Network Status	Support
User Interface	Account management, IE, App, VMS
TV-Wall	Support (Optional)
Software Function	
OSD language	Support Thai, English, Chinese Etc.
Start Up Wizard	Supported
Log	Support log export
SDK	Supported
Import & Export config	Supported
System upgade	Support USB, Network
Auto Maintenance	Supported
Two-way-audio	Supported
System status	Supported
Hardware interface	
HDD	SATA 2.5 x1 (Max. 10TB)
HDMI Output	HDMI 1.3 x1 (Max. 1920x1080P), HDMI/VGA simultaneous video output
VGA Output	VGA x1 (Max. 1920x1080P), HDMI/VGA simultaneous video output
RJ45	x1 (10/100M Mbps) self-adaption
USB 2.0	x3
Power Input	DC12V
Others	
Power supply	DC12V/2A
Power consumption	<10W (Without HDD)
Working environment	0°C to +55°C
Working Humidity	10% to 90% RH
Dimension	255(L)x236mm(W)x44mm(H)
Weight	886g.



Xmeye



hiviewXview



# FULL HD SURVEILLANCE