

# Surge protection device - S-PT-2XEX-24DC-1/2 - 2800041

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Surge protection for two floating signal circuits in screw-on module with IP67 protection for sensor heads, connection ½-inch 14 NPT. Tested in acc. with the protection types in Ex areas Ex d / Ex tD / Ex ia IIC / Ex iaD. Can be used inside of a fieldbus-system according to the FISCO concept.

## Your advantages

- ✓ Arresters in hexagonal pipe with various outer threads



## Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 411035
GTIN	4046356411035
Weight per Piece (excluding packing)	209.060 g
Custom tariff number	85363010
Country of origin	Germany
Note	Made to Order (non-returnable)

## Technical data

### Dimensions

Height	28 mm
Width	28 mm
Depth	79 mm

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C (non-Ex)
Altitude	≤ 2000 m (amsl (above mean sea level))
Degree of protection	IP67

### General

Housing material	Stainless steel
------------------	-----------------

# Surge protection device - S-PT-2XEX-24DC-1/2 - 2800041

## Technical data

### General

Color	silver
Standards for clearances and creepage distances	IEC 60664-1
	IEC 60079-11
Mounting type	1/2" NPT
Type	Screw-in module
Number of positions	4
Direction of action	Line-Line & Line-Earth Ground

### Protective circuit

IEC test classification	C1
	C2
	C3
	D1
Nominal voltage $U_N$	24 V DC
Maximum continuous voltage $U_C$	36 V DC
	25 V AC
Operating effective current $I_C$ at $U_C$	$\leq 5 \mu\text{A}$
Residual current $I_{PE}$	$\leq 2 \mu\text{A}$
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (line-line)	260 A
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (line-earth)	10 kA
Pulse discharge current $I_{imp}$ (10/350) $\mu\text{s}$	1 kA
Total discharge current $I_{total}$ (8/20) $\mu\text{s}$	20 kA
Total discharge current $I_{total}$ (10/350) $\mu\text{s}$	2 kA
Nominal pulse current $I_{an}$ (10/1000) $\mu\text{s}$ (line-line)	50 A
Output voltage limitation at 1 kV/ $\mu\text{s}$ (line-line) spike	$\leq 65 \text{ V}$
Output voltage limitation at 1 kV/ $\mu\text{s}$ (line-earth) spike	$\leq 1.1 \text{ kV}$
Output voltage limitation at 1 kV/ $\mu\text{s}$ (line-line) static	$\leq 50 \text{ V}$
Voltage protection level $U_p$ (line-line)	$\leq 50 \text{ V}$ (C3 - 10 A)
Voltage protection level $U_p$ (line-earth)	$\leq 1.1 \text{ kV}$ (C3 - 100 A)
	$\leq 1.1 \text{ kV}$ (C1 - 1 kV/500 A)
	$\leq 1.2 \text{ kV}$ (C2 - 10 kV / 5 kA)
Response time $t_A$ (line-line)	$\leq 1 \text{ ns}$
Response time $t_A$ (line-earth)	$\leq 100 \text{ ns}$
Input attenuation aE, sym.	typ. 0.1 dB (1 MHz / 50 $\Omega$ )
	typ. 0.1 dB (400 kHz / 150 $\Omega$ )
Cut-off frequency $f_g$ (3 dB), sym. in 50 Ohm system	typ. 5 MHz
Cut-off frequency $f_g$ (3 dB), sym. in 150 Ohm system	typ. 2 MHz
Capacity (line-line)	typ. 1.5 nF
Capacity (line-earth)	typ. 5 pF
Surge protection fault message	none

# Surge protection device - S-PT-2XEX-24DC-1/2 - 2800041

## Technical data

### Protective circuit

Impulse durability (line-line)	C3 - 25 A
Impulse durability (line-earth)	C1 - 1 kV / 500 A
	C2 - 10 kV / 5 kA
	C3 - 100 A
	D1 - 1 kA
Alternating current carrying capacity (line-earth)	10 A - 1 s

### Connection data

Connection method	Individual wires
-------------------	------------------

### Standards and Regulations

Standards/specifications	EN 61643-21 A2:2013
	EN 60079-0 2012
	EN 60079-1 2007
	EN 60079-11 2012
	EN 60079-31 2009
	IEC 60079-0 2011
	IEC 60079-1 2007
	IEC 60079-11 2011
	IEC 60079-31 2008

### General

Maximum inner capacitance $C_i$	1.65 nF
Max. internal inductance $L_i$	1 $\mu$ H
Max. input current $I_i$	500 mA (T4 / $\leq 75$ °C)
	500 mA (T5 / $\leq 75$ °C)
	500 mA (T6 / $\leq 60$ °C)
Max. input voltage $U_i$	36 V DC
max. input power $P_i$	3 W
Insulation voltage to ground	500 V AC
Ambient temperature (operation)	-40 °C ... 75 °C (T4)
	-40 °C ... 75 °C (T5)
	-40 °C ... 60 °C (T6)

### Conformity / approvals

ATEX	# II 1 G Ex ia IIC T4...T6
	# II 2 G Ex d IIC T4...T6
	# II 1 D Ex iaD 20 IP6x T85 °C...135 °C
	# II 2 D Ex tD A21 IP6x T85 °C...135 °C
IECEX	Ga Ex ia IIC T4...T6
	Ex d IIC T4...T6
	Ex iaD IP6x T85 °C...135 °C
	Ex tD A21 IP6x T85 °C...135 °C

# Surge protection device - S-PT-2XEX-24DC-1/2 - 2800041

## Technical data

### Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

---