



Power supply 30V DC 640 mA

TXA112

Architecture

Number of outputs	1
Bus system	EIB
Fixing mode	Din-Rail

Connectivity

Bus lines	max. 1
-----------	--------

Main electrical features

Frequency	50/60 Hz
-----------	----------

Voltage

Output voltage	28 - 32 V
Output voltage	30 V
Filtered output voltage	30V +/- 2V

Electric current

Output intensity	640 mA
Output current	max. 640 mA

Power

Total power loss under IN	15 W
---------------------------	------

Materials

RAL colour	RAL 7035 - Light grey
Colour	stone grey

Dimensions

Depth of installed product	64 mm
Height of installed product	90 mm
Length	64 mm
Width of installed product	72 mm

Connection

Conductor cross-section (flexible)	0,75 2,5 mm ²
Conductor cross-section (rigid)	0,75 2,5 mm ²
Connection cross-sect. rigid cable	0,75 / 2,5mm ²
Connection cross-sect. flexible conductor	0,75 / 2,5mm ²
Type of connection	quick connect

Equipment

Power failure bypass	yes
----------------------	-----

Use

- with labelling field

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5 45 °C
Storage temperature	-20 to 70 °C