



TXB304

Flush mounted input device 4 -fold

Architecture

Bus system	EIB
Fixing mode	flush-mounting

Functions

- ETS additional functions: value transmitter 1 and 2 bytes, 2-channel mode, level switch function

Compatibility

- extension unit for light scene push-button

Controls and indicators

- with programming button and red programming LED

Connectivity

- with 2 independent binary inputs for potential-free contacts
- with 2 freely parameterisable outputs for LED activation

Voltage

Operating voltage over bus	21 32 V DC
----------------------------	------------

Materials

Colour	stone grey
Material	plastic

Dimensions

Dimensions (LLxwxhh)	38 x 35 x 12 mm
----------------------	-----------------

Installation, mounting

- for flush-mounted and hollow-wall mounting

Connection

Conductor cross-section (flexible)	0,75 2,5 mm ²
Conductor cross-section (rigid)	0,75 2,5 mm ²

- with integral bus coupling unit
- with pre-assembled cable
- bus connection via connecting terminal

Cable

Cable length extendable to	max. 5 m
----------------------------	----------

Use

- with integral bus coupling unit

Safety

Protection index IP	IP30
Halogen free	no

Use conditions

Operating temperature	0 45 °C
Storage/transport temperature	-20 70 °C

Identification

Main design line	KNX
------------------	-----