


PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ground terminal, number of connections: 2, connection method: Push-in connection, cross section: 0.2 mm² - 6 mm², mounting type: NS 35/7,5, NS 35/15, color: green-yellow

Your advantages

- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- In addition to the testing option in the double function shaft, all terminal blocks provide an additional test pick-off
- The compact design and front connection enable wiring in a confined space
- Tested for railway applications

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 3211766 |
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales key | ***** |
| Product key | BE2221 |
| Catalog page | Page 99 (C-1-2019) |
| GTIN | 4046356482615 |
| Weight per piece (including packing) | 10.6 g |
| Weight per piece (excluding packing) | 9.833 g |
| Customs tariff number | 85369010 |
| Country of origin | CN |

PT 4-PE - Ground terminal



3211766

<https://www.phoenixcontact.com/sg/products/3211766>

Technical data

Product properties

| | |
|-----------------------|-----------------------|
| Product type | Ground terminal block |
| Area of application | Railway industry |
| | Machine building |
| | Plant engineering |
| | Process industry |
| Number of connections | 2 |
| Number of rows | 1 |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|---|--------|
| Rated surge voltage | 8 kV |
| Maximum power dissipation for nominal condition | 1.02 W |

Connection data

| | |
|---|--|
| Grounding foot | Yes |
| Number of connections per level | 2 |
| Nominal cross section | 4 mm ² |
| Note | Please observe the current carrying capacity of the DIN rails. |
| Stripping length | 10 mm ... 12 mm |
| Internal cylindrical gage | A4 |
| Connection in acc. with standard | IEC 60947-7-2 |
| Conductor cross section rigid | 0.2 mm ² ... 6 mm ² |
| Cross section AWG | 24 ... 10 (converted acc. to IEC) |
| Conductor cross section flexible | 0.2 mm ² ... 6 mm ² |
| Conductor cross section, flexible [AWG] | 24 ... 10 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.25 mm ² ... 4 mm ² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.25 mm ² ... 4 mm ² |
| Maximum load current | with 6 mm ² conductor cross section, rigid |

Connection cross sections directly pluggable

| | |
|---|--|
| Conductor cross section rigid | 0.5 mm ² ... 6 mm ² |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.75 mm ² ... 4 mm ² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.5 mm ² ... 4 mm ² |

Ex data

Rated data (ATEX/IECEx)

| | |
|-----------------------------|-----------------------|
| Identification | ⊕ II 2 G Ex eb IIC Gb |
| Operating temperature range | -60 °C ... 110 °C |

PT 4-PE - Ground terminal



3211766

<https://www.phoenixcontact.com/sg/products/3211766>

| | |
|--------------------------|-----------------------|
| Ex-certified accessories | 3030420 D-ST 4 |
| | 3030721 ATP-ST 4 |
| | 1204517 SZF 1-0,6X3,5 |
| | 3022276 CLIPFIX 35-5 |
| | 3022218 CLIPFIX 35 |
| output | (Permanent) |

Ex connection data General

| | |
|------------------------------|---|
| Nominal cross section | 4 mm ² |
| Rated cross section AWG | 12 |
| Connection capacity rigid | 0.2 mm ² ... 6 mm ² |
| Connection capacity AWG | 24 ... 10 |
| Connection capacity flexible | 0.2 mm ² ... 4 mm ² |
| Connection capacity AWG | 24 ... 12 |

Dimensions

| | |
|--------------------|---------|
| Width | 6.2 mm |
| End cover width | 2.2 mm |
| Height | 56 mm |
| Depth | 35.3 mm |
| Depth on NS 35/7,5 | 36.5 mm |
| Depth on NS 35/15 | 44 mm |

Material specifications

| | |
|---|--------------|
| Color | green-yellow |
| Flammability rating according to UL 94 | V0 |
| Insulating material group | I |
| Insulating material | PA |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354) | 28 MJ/kg |
| Surface flammability NFPA 130 (ASTM E 162) | passed |
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed |
| Smoke gas toxicity NFPA 130 (SMP 800C) | passed |

Mechanical properties

Mechanical data

| | |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

Environmental and real-life conditions

Oscillation/broadband noise

| | |
|------------------------|--|
| Specification | DIN EN 50155 (VDE 0115-200):2008-03 |
| Spectrum | Service life test category 2, bogie-mounted |
| Frequency | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level | 6.12 (m/s ²)/Hz |
| Acceleration | 3.12g |
| Test duration per axis | 5 h |
| Test directions | X-, Y- and Z-axis |
| Result | Test passed |

Shocks

| | |
|--------------------------------|-------------------------------------|
| Specification | DIN EN 50155 (VDE 0115-200):2008-03 |
| Pulse shape | Half-sine |
| Acceleration | 30g |
| Shock duration | 18 ms |
| Number of shocks per direction | 3 |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |
| Result | Test passed |

Ambient conditions

| | |
|--|--|
| Ambient temperature (operation) | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 90 % |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Standards and regulations

| | |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-2 |
|----------------------------------|---------------|

Mounting

| | |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
| | NS 35/15 |

PT 4-PE - Ground terminal


3211766

<https://www.phoenixcontact.com/sg/products/3211766>



Drawings

Circuit diagram



PT 4-PE - Ground terminal





3211766

<https://www.phoenixcontact.com/sg/products/3211766>


Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/3211766>


| | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  CSA Approval ID: 2030668 | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| | - | - | 24 - 10 | - |


| | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  IECEE CB Scheme Approval ID: DE1-65864 | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| | - | - | - | 0.2 - 4 |

| |
|--|
|  EAC Approval ID: RU C-DE.BL08.B.00644 |
|--|


| |
|--|
|  cULus Recognized Approval ID: E60425 |
|--|


| |
|---|
|  LR Approval ID: LR2371832TA |
|---|

| |
|---|
|  ClassNK NK Approval ID: 22ME0007 |
|---|

| |
|--|
|  RS Approval ID: 22.44.01.00083.250 |
|--|

| |
|---|
|  BV Approval ID: 39980/B0 BV |
|---|

| | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  VDE Zeichengenehmigung Approval ID: 40037246 | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| | - | - | - | 0.2 - 4 |

| |
|--|
|  PRS |
|--|

PT 4-PE - Ground terminal



3211766

<https://www.phoenixcontact.com/sg/products/3211766>

Approval ID: TE/2107/880590/21

ABS

Approval ID: 21-2192245-PDA

DNV

Approval ID: TAE000010T



cULus Recognized

Approval ID: E60425



cULus Recognized

Approval ID: E60425



cUL Recognized

Approval ID: E192998

| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
|--|-----------------------|-----------------------|-------------------|----------------------|
| | - | - | 24 - 10 | - |



IECEx

Approval ID: IECExPTB10.0046U

| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
|--------------------------|-----------------------|-----------------------|-------------------|----------------------|
| Only flexible conductors | - | - | - | 0.2 - 4 |
| Only rigid conductors | - | - | - | 0.2 - 6 |



UL Recognized

Approval ID: E192998

| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
|--|-----------------------|-----------------------|-------------------|----------------------|
| | - | - | 24 - 10 | - |



ATEX

Approval ID: PTB09ATEX1112U

| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
|--------------------------|-----------------------|-----------------------|-------------------|----------------------|
| Only flexible conductors | - | - | - | 0.2 - 4 |
| Only rigid conductors | - | - | - | 0.2 - 6 |

PT 4-PE - Ground terminal



3211766

<https://www.phoenixcontact.com/sg/products/3211766>



CCC

Approval ID: 2020322313000631



UKCA-EX

Approval ID: CSAE 22UKEX1100U

cULus Recognized

PT 4-PE - Ground terminal



3211766

<https://www.phoenixcontact.com/sg/products/3211766>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27141141 |
| ECLASS-13.0 | 27250103 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000901 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



Accessories

FBS 2-6 - Plug-in bridge

3030336

<https://www.phoenixcontact.com/sg/products/3030336>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

FBS 3-6 - Plug-in bridge

3030242

<https://www.phoenixcontact.com/sg/products/3030242>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBS 4-6 - Plug-in bridge

3030255

<https://www.phoenixcontact.com/sg/products/3030255>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red

FBS 5-6 - Plug-in bridge

3030349

<https://www.phoenixcontact.com/sg/products/3030349>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBS 6-6 - Plug-in bridge

1008238

<https://www.phoenixcontact.com/sg/products/1008238>



Plug-in bridge, One side not fully isolated, pitch: 6.2 mm, number of positions: 6, color: red

FBS 10-6 - Plug-in bridge

3030271

<https://www.phoenixcontact.com/sg/products/3030271>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBS 20-6 - Plug-in bridge

3030365

<https://www.phoenixcontact.com/sg/products/3030365>



Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: red

FBSR 2-6 - Plug-in bridge

3033715

<https://www.phoenixcontact.com/sg/products/3033715>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBSR 3-6 - Plug-in bridge

3001594

<https://www.phoenixcontact.com/sg/products/3001594>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red

FBSR 4-6 - Plug-in bridge

3001595

<https://www.phoenixcontact.com/sg/products/3001595>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBSR 5-6 - Plug-in bridge

3001596

<https://www.phoenixcontact.com/sg/products/3001596>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red

FBSR 10-6 - Plug-in bridge

3033716

<https://www.phoenixcontact.com/sg/products/3033716>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBSRH 2-6 - Short-circuit connector

3033812

<https://www.phoenixcontact.com/sg/products/3033812>



Short-circuit connector, pitch: 6.2 mm, number of positions: 2, color: red

FBS 2-6 BU - Plug-in bridge

3036932

<https://www.phoenixcontact.com/sg/products/3036932>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: blue

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBS 3-6 BU - Plug-in bridge

3036945

<https://www.phoenixcontact.com/sg/products/3036945>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: blue

FBS 4-6 BU - Plug-in bridge

3036958

<https://www.phoenixcontact.com/sg/products/3036958>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: blue

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBS 5-6 BU - Plug-in bridge

3036961

<https://www.phoenixcontact.com/sg/products/3036961>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: blue

FBS 10-6 BU - Plug-in bridge

3032198

<https://www.phoenixcontact.com/sg/products/3032198>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: blue

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



FBS 20-6 BU - Plug-in bridge

3032208

<https://www.phoenixcontact.com/sg/products/3032208>



Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: blue

FBS 50-6 BU - Plug-in bridge

3032211

<https://www.phoenixcontact.com/sg/products/3032211>



Plug-in bridge, pitch: 6.2 mm, number of positions: 50, color: blue

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



D-ST 4 - End cover

3030420

<https://www.phoenixcontact.com/sg/products/3030420>

End cover, depth: 29 mm, width: 2.2 mm, height: 55.9 mm, color: gray



ATP-ST 4 - Partition plate

3030721

<https://www.phoenixcontact.com/sg/products/3030721>

Partition plate, depth: 39 mm, width: 2 mm, height: 59.8 mm, color: gray



PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



GBS 5-25X12 - Group marker label for terminal marking

0810588

<https://www.phoenixcontact.com/sg/products/0810588>



Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

GBS-ZB/26X6 - Group marker label for terminal marking

0809298

<https://www.phoenixcontact.com/sg/products/0809298>



Group marking label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with ESL 26x6 mm or EST 25x6 mm, in the foot part with Zack marker strip, length: 29 mm

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



CARRIER-TM 300 - Marker carriers

0828282

<https://www.phoenixcontact.com/sg/products/0828282>



Marker adapter, 300 mm in length, for manual cutting, can be engaged in a flat marker groove, for ZB ..., UC-TM ... or UCT-TM ...

WS PT 4 - Warning label

1029563

<https://www.phoenixcontact.com/sg/products/1029563>



Warning label, 5-section, yellow/black, labeled: Lightning flash, mounting type: plug in, for terminal block width: 6.2 mm

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/sg/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/sg/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/sg/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/sg/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/sg/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/sg/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/sg/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/sg/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/sg/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/sg/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/sg/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/sg/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/sg/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/sg/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/sg/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/sg/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/sg/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/sg/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/sg/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

ZB 6:UNBEDRUCKT - Zack marker strip

1051003

<https://www.phoenixcontact.com/sg/products/1051003>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



ZB 6 CUS - Zack marker strip

0824992

<https://www.phoenixcontact.com/sg/products/0824992>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:FORTL.ZAHLEN - Zack marker strip

1051016

<https://www.phoenixcontact.com/sg/products/1051016>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PT 4-PE - Ground terminal

3211766


<https://www.phoenixcontact.com/sg/products/3211766>



ZB 6,QR:FORTL.ZAHLEN - Zack marker strip

1051029

<https://www.phoenixcontact.com/sg/products/1051029>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:GLEICHE ZAHLEN - Zack marker strip

1051032

<https://www.phoenixcontact.com/sg/products/1051032>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



ZB 6,LGS:L1-N,PE - Marker for terminal blocks

1051414

<https://www.phoenixcontact.com/sg/products/1051414>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:U-N - Marker for terminal blocks

1051430

<https://www.phoenixcontact.com/sg/products/1051430>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/sg/products/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UC-TM 6 CUS - Marker for terminal blocks

0824589

<https://www.phoenixcontact.com/sg/products/0824589>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



UCT-TM 6 - Marker for terminal blocks

0828736

<https://www.phoenixcontact.com/sg/products/0828736>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

UCT-TM 6 CUS - Marker for terminal blocks

0829602

<https://www.phoenixcontact.com/sg/products/0829602>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



ZBF 6:UNBEDRUCKT - Zack Marker strip, flat

0808710

<https://www.phoenixcontact.com/sg/products/0808710>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6 CUS - Zack Marker strip, flat

0825027

<https://www.phoenixcontact.com/sg/products/0825027>



Zack Marker strip, flat, Strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



UC-TMF 6 - Marker for terminal blocks

0818140

<https://www.phoenixcontact.com/sg/products/0818140>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 5.1 mm, Number of individual labels: 80

UC-TMF 6 CUS - Marker for terminal blocks

0824646

<https://www.phoenixcontact.com/sg/products/0824646>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 5.1 mm, Number of individual labels: 80

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



UCT-TMF 6 - Marker for terminal blocks

0828746

<https://www.phoenixcontact.com/sg/products/0828746>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.4 x 4.7 mm, Number of individual labels: 60

UCT-TMF 6 CUS - Marker for terminal blocks

0829665

<https://www.phoenixcontact.com/sg/products/0829665>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.4 x 4.7 mm, Number of individual labels: 60

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



ZBF 6,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808749

<https://www.phoenixcontact.com/sg/products/0808749>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0808765

<https://www.phoenixcontact.com/sg/products/0808765>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



ZBF 6,LGS:GERADE ZAHLEN - Zack Marker strip, flat

0810834

<https://www.phoenixcontact.com/sg/products/0810834>




Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive even numbers 2 ... 20, 22 ... 40, etc. up to 82 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6,LGS:UNGERADE ZAHLEN - Zack Marker strip, flat

0810876

<https://www.phoenixcontact.com/sg/products/0810876>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/sg/products/0201744>



Test plug, with solder connection up to 1 mm² conductor cross section, number of positions: 1, color: gray

MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/sg/products/0201663>

Insulating sleeve, color: white



PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/sg/products/0201676>

Insulating sleeve, color: red




MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/sg/products/0201689>

Insulating sleeve, color: blue



PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/sg/products/0201692>

Insulating sleeve, color: yellow



MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/sg/products/0201702>

Insulating sleeve, color: green



PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/sg/products/0201728>

Insulating sleeve, color: gray



MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/sg/products/0201731>

Insulating sleeve, color: black



PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



ISH 4/0,5 - Insulating sleeve

3002885

<https://www.phoenixcontact.com/sg/products/3002885>



Insulating sleeve, color: gray

ISH 4/1,0 - Insulating sleeve

3002898

<https://www.phoenixcontact.com/sg/products/3002898>



Insulating sleeve, color: black

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



PAI-4-FIX-5/6 BU - Test adapter

3035975

<https://www.phoenixcontact.com/sg/products/3035975>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 OG - Test adapter

3035974

<https://www.phoenixcontact.com/sg/products/3035974>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



PAI-4-FIX-5/6 YE - Test adapter

3035977

<https://www.phoenixcontact.com/sg/products/3035977>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 RD - Test adapter

3035976

<https://www.phoenixcontact.com/sg/products/3035976>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



PAI-4-FIX-5/6 GN - Test adapter

3035978

<https://www.phoenixcontact.com/sg/products/3035978>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 BK - Test adapter

3035980

<https://www.phoenixcontact.com/sg/products/3035980>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



PAI-4-FIX-5/6 GY - Test adapter

3035982

<https://www.phoenixcontact.com/sg/products/3035982>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 VT - Test adapter

3035979

<https://www.phoenixcontact.com/sg/products/3035979>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



PAI-4-FIX-5/6 BN - Test adapter

3035981

<https://www.phoenixcontact.com/sg/products/3035981>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 WH - Test adapter

3035983

<https://www.phoenixcontact.com/sg/products/3035983>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



PS-6 - Test plug

3030996

<https://www.phoenixcontact.com/sg/products/3030996>



Test plug, Modular test plug, number of positions: 1, color: red

PS-6/2,3MM RD - Test plug

3038736

<https://www.phoenixcontact.com/sg/products/3038736>



Test plug, number of positions: 1, color: red

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



TMT 6 R - Marker for terminal blocks

0816498

<https://www.phoenixcontact.com/sg/products/0816498>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK S1.1, perforated, mounting type: snapped, snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 6.35 x 6.15 mm, Number of individual labels: 16000

TMT 6 R CUS - Marker for terminal blocks

0824488

<https://www.phoenixcontact.com/sg/products/0824488>



Marker for terminal blocks, can be ordered: by line, white, labeled according to customer specifications, mounting type: snap into universal marker groove, snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 6.35 x 6.15 mm

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



TMT (EX9,5)R - Marker for terminal blocks

0828295

<https://www.phoenixcontact.com/sg/products/0828295>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snapped, snap into tall marker groove, for terminal block width: 30000 mm, lettering field size: 9.5 x 50000 mm, Number of individual labels: 1

US-TM 100 - Marker for terminal blocks

0829255

<https://www.phoenixcontact.com/sg/products/0829255>



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, lettering field size: 104 x 9.8 mm, Number of individual labels: 13

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



SZF 1-0,6X3,5 - Screwdriver

1204517

<https://www.phoenixcontact.com/sg/products/1204517>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

ST-BW - Actuation tool

1207608

<https://www.phoenixcontact.com/sg/products/1207608>



Actuation tool, for all 2.5 mm² - 4.0 mm² spring-cages

PT 4-PE - Ground terminal

3211766

<https://www.phoenixcontact.com/sg/products/3211766>



PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/sg/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.

105 Eunos Avenue 3, #04-00

Singapore 409836

+65 6228 4900

marketing@phoenixcontact.com.sg