



NUBOS-1000



Simple Solution for Home and Office Users




- Compact size
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function

This UPS provides comprehensive protection in a small package. Not only offering greater comprehensive power protection, it also provides pure voltage with built-in AVR stabilizer.



The UPS will continue providing clean and stable power to connected equipment while its embedded microprocessor controller guarantees high reliability, perfect for any home or small office application.



Line Interactive UPS with Stabilizer

Product from ISO 9001, ISO 14001 and ISO 45001 certified factory



Line Interactive UPS with Stabilizer

MODEL	NUBOS-1000		
CAPACITY	1000 VA / 500 W		
SYSTEM	UPS system	Line interactive UPS with stabilizer	
	Control system	Microprocessor control	
	Stabilizer function	Buck / Boost	
LOAD APPLICATION	The number of PC ⁽¹⁾	1 - 2 sets + printer ⁽²⁾	
INPUT	Voltage (single phase)	220 Vac ± 25%	
	Frequency	50 Hz ± 10%	
OUTPUT	Voltage battery mode	220 Vac ± 5%	
	Voltage AC mode	220 Vac ± 10%	
BATTERY	Type	Sealed lead acid (maintenance free)	
	Capacity	12 V 7.2 Ah	
	Backup time	10 - 30 min. (depending on connected load)	
	Continuous recharging time	6 - 8 hours (90% after full discharged)	
PROTECTION	Over voltage	Mains to UPS backup 220 Vac + 25%	
	Under voltage	Mains to UPS backup 220 Vac - 25%	
	Transfer time	4 - 8 msec typical	
	Overload (AC / DC mode)	yes	
	Output short circuit	yes	
	Surge energy dissipation	125 Joules / 2 msec x 3	
	Power dissipation	1,000,000 W within 100 microsec.	
	Acoustic noise	less than 40 dBA at 1 metre	
	OUTPUT OUTLET	Number of backup outlet	3
		Number of surge protection outlet (not backup)	1
FEATURES	AC / DC start	yes	
	Surge protection for telephone line (RJ11 port)	yes	
	Surge protection for laser printer	yes	
	Auto start function	yes	
	Off mode charging	yes	
	Communication interface	USB port with UPS monitoring and management software ⁽³⁾	
	INDICATOR	LED	AC mode (green), Battery mode (yellow), Fault (red)
AUDIBLE ALARM (BUZZER)	Battery mode	Audible beep every 10 seconds	
	Low battery	Audible beep every second	
	Overload	Audible beep every 0.5 seconds	
	Fault	Continuous audible beep	
ENVIRONMENT	Temperature	0 - 40°C	
	Relative humidity	0 - 90% (non-condensing)	
	Acoustic noise	less than 45 dBA at 1 metre	
CONFORMANCE	Safety	IEC/EN 62040-1, IEC/EN 60950-1	
	EMC	IEC/EN 62040-2, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8	
DIMENSIONS	W x H x D	101 x 142 x 298 mm	
WEIGHT	Approximate in kg.	4.5 kg	

(1) Computer with 19.5" LED monitor, (2) Bubble jet or Dot Matrix printer only, (3) Software compatible with Windows 98 / Me / 2000 / 2003 / XP / Vista / Windows 7 / Windows 11 / Linux. Continuous product development is our commitment. In that manner, the above specifications may be change without prior notice.

LEO POWER SUPPLY CO.,LTD.

27, 4th Floor, Soi Bangna-Trad 34, Bangna Tai, Bangna, Bangkok 10260
Phone 0-2746-9500 Fax 0-2746-8712 E-mail: marketing@lpsups.com