

HP-5616





NVR 5600 SERIES






















NVR 5600 SERIES





















- Support HDMI VGA HD output;
- Support ONVIF; access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.
- Support GB28181 protocol access to third-party platforms

Specification

Model

HP-5616

Hi3536E Main processor **Operating System Embedded Linux**

System resources Simultaneous multi-channel real-time recording, playback,

network operation, USB backup

Operator interface 16-bit true color graphic menu operation interface,

support mouse operation

Preview 1/4/8/9/16

Video

Interface

Video input (IP) 16*4K (Access bandwidth 72Mbps)

Video compression H.265AI / H.265+ (compatible H.265 / H.264)

Unsupport

Display quality Max:4K

4K/5M/4M/3M/1080P **Playback quality**

VR

Support (depend on camera) human shape / Face

G.711A Audio compression

Intercom unsupport

Record & playback

Recording mode Manual>Alarm>Dynamic Detection>Timing

Localpayback 4K (1*real-time) / 5M (1+1) / 4M (2+1)

3M (3+1) / 1080P (5+1)

Search mode Search by Time/Calendar/Event/Channel/Face

Record storage HDD, Network

Backup mode Network backup, USB hard disk, USB burner, SATA burner

Video output 1ch VGA, 1ch HDMI HD output

Audio I/O 0/1 (3.5MM audio output)

Alarm I/O

Network interface

External interface

1*RJ45 10M / 100M Adaptive Ethernet port

USB interface 2*USB2.0 ports(one USB extension interface is reserved)

HDD 1 SATA (Up to 8TB for each disk)

ESATA

Serial interface No

ONVIE Support 12V/2.5A Power supply

Power Consumption <10W (Without HDD) Work environment Temperature: 0C -55C Humidity: 10% -90%RH

Atm: 86kpa -106kp



App Store



