

3MP NVR KIT WIRELESS SURVEILLANCE SYSTEM



















3MP NVR KIT WIRELESS SURVEILLANCE SYSTEM













Features

- 3MP / 1080P / 960P / 720P Wireless Network Video Recorder
- Built-in WIFI module with high-performance and high stability
- Automatically Connection between **NVR and IPC**
- Support video preview / recording / playback backup
- Support the mixed use of wireless and wire, support different scene
- Support Android / IOS/PC remote

Specification

Model

HW-3304KIT30-H3

Video input 4ch 720P/960P/1080P/3MP

HDMI Output 1 ch. resolution: 1024x768.

1280x1024, 1366x768, 1440x900,

1920x1080, 2K, support audio output

VGA Output 1 ch, resolution: 1024x768,

1280x1024, 1366x768, 1440x900,

1920x1080

Resolution 720P/960P/1080P/3MP/5MP

Playback

Recording Manual, time, motion dection, alarm

Storage

6TB for each HDD Storage capacity

1 RJ45 10M/100M **Network interface**

2 WIFI connector

USB interface

≤ **5W**

Power consumption

Power

working temperature

Dimension (mm)

Audio interface

Working humidity

2 USB 2.0

3.5 mm headphone jack

DC12V

-10C -- +55C

258*210*42mm

10%--90%RH





3MP NVR KIT WIRELESS SURVEILLANCE SYSTEM











Features

- 3MP / 1080P / 960P / 720P Wireless Network Video Recorder
- Built-in WIFI module with high-performance and high stability
- Automatically Connection between **NVR and IPC**
- Support video preview / recording / playback backup
- Support the mixed use of wireless and wire, support different scene
- Support Android / IOS/PC remote

Specification

Model

Signal System

Resolution

Minimum illumination

Shutter

Lens

OSD

White Balance

Day & Night

3D-DNR

Mirror / Flip

smart stream

S/N

Interface

Anti-thunder Level

Working Temperature

Working Humidity

Working Temperature

Working Humidity

Power Input

Power consumption

Size

Weight

Level of Protection

HW-33B30-H3

1/3" Progressive Scan Sensor

PAL / NTSC

2304x1296 16:9 High Defination

Color: 0.01 Lux

B/W: 0.001 Lux

1/25s to 1/25,000s

4mm

Date Time & Title

Auto / Color / BW

Auto

On / Off

Dual-stream

2304x1296@15fps

640x360@15fps

> 39.1 Db

RJ45 / WIFI 802.11b/g/n

Standard IEC61000-4-5

-10°C to +50°C

30% to 80% RH

-20°C to +60°C

20% to 90% RH

DC12V-1A

< 6W

66*180mm

500a

IP66