



FULLY FOLDABLE CRANES > Rotation system on cylinders

Crane model	nr of extensions		Length of boom (m) and crane lifting capacity (kg)												
			3 m	4 m	5 m	6 m	7 m	8 m	9 m	10 m	11 m	12 m	13 m	14 m	
HLM 3	1S	m	3,5		5,17										
		Kg	1.000		680										
	2S	m	3,58		5,25	6,91									
		Kg	980		660	500									
HLM 6	1S	m	3,54		5,25										
		Kg	1.800		1.100										
	2S	m	3,63		5,3	6,97									
		Kg	1.700		1.150	850									
HLM 8	1S	m		4,20	5,90										
		Kg		2.100	1.500										
	2S	m		4,30	5,90		7,47								
		Kg		2.100	1.500		1.200								
	3S	m		4,37	5,99		7,64			9,30					
		Kg		1.950	1.400		1.100			850					
HLM 10	1S	m		4,64		6,54									
		Kg		2.300		1.650									
	2S	m		4,65		6,55		8,41							
		Kg		2.250		1.600		1.200							
	3S	m		4,81		6,65		8,52			10,30				
		Kg		2.150		1.500		1.150			930				
HLM 16	1S	m		4,92		6,92									
		Kg		3.400		2.400									
	2S	m		4,93		6,99				9,01					
		Kg		3.200		2.200				1.680					
	3S	m		4,99		6,99				9,00	10,99				
		Kg		3.150		2.150				1.600	1.200				
HLM 25	2S	m		4,68		6,64		8,62							
		Kg		5.200		3.600		2.800							
	3S	m		4,81		6,75		8,72			10,58				
		Kg		5.000		3.450		2.600			2.100				
	4S	m		4,94		6,88		8,85			10,71		12,63		
		Kg		4.850		3.350		2.450			1.800		1.450		
	5S	m			5,02	6,97		8,93			10,79		12,79		14,69
		Kg			4.700	3.200		2.400			1.800		1.400		1.150

