

DS-K1T671MF Face Recognition Terminal



- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens, built-in M1 card reading module
- Face recognition distance (without face mask): 0.3 m to 3 m, Duration < 0.2 s/User, Accuracy rate ≥ 99%
- Max.6000 faces, Max.6000 cards and Max. 5000 fingerprints
- Two-way audio with client software, indoor station, and main station
- Supports TCP/IP
- Configuration via the web client
- Supports ISAPI and ISUP5.0 protocol
- IP65





Specification

Linux						
Display						
7-inch						
LCD						
Capacitive touch screen						
Operation method Capacitive touch screen Video						
2 MP						
2						
Audio						
Noise suppression and echo cancellation						
Tone quality Noise suppression and echo cancellation Network						
10 M/100 M/1000 M self-adaptive						
Interface						
1						
1						
1						
1						
1						
1						
2						
1						
2-pin						
1						
2						
USB 2 Capacity						
6000						
6000						
5000						
50,000						
Event capacity 50,000 Authentication						
M1 card						
13.56MHz						
0 to 5 cm						
≥ 99%						
0.3 to 3 m (Without face mask)						
≤1s						
Support						
Support						
Support						
Support						
2-pin connecter						




Power supply	12 VDC/2 A			
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)			
Working humidity	10 to 90% (No condensing)			
Dimensions	290 mm × 116.5 mm × 33 mm (11.4" × 4.6" × 1.3")			
Protective level	IP65			
Installation	Surface			
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)			
Platform	Hik-ProConnect and HikCentral Professional			

Available Model

DS-K1T671MF

Dimension





Accessory

Optional

DS-KAB671-P1	DS-KAB671-S	DS-KAB671-S	DS-KAB671-B	DS-KAB671-B
	Protective Shield	Protective Shield	Stand Stick	Stand Stick
DS-K3H4411-120	DS-K3H4410-120			

Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com