

## DS-D60E-B Digital Signage Player



- Variable Materials Supports static and dynamic materials, including the application, pictures, audio, video, PDF, streaming media, webpage, live video, third-party data, etc.
- Flexible Program Schedule Supports free schedule and district display of multiple materials. Supports variable display modes: display by day, display by week, custom display, etc.
- Centralized Management Remotely control and manage one or more screens, such as timed startup/shutdown, timed brightness/volume, and screenshot previewing.
- Organization Feature 5-level organization is available for managing materials, programs, terminals, and users.
- Multilevel User Permission Supports creating custom users, and allocating permission for users according to user level.
- Multiple Security Safeguards 3-level check of materials, programs, and schedules to prevent mistake release.
   Screensaver to secure safe for broadcast contents.
   Encryption of data storage and transmission to avoid data tampering.
- Arbitrary Direction Remote Control The remote control, adopting wireless communication in 433 MHz, can control the information distribution box in arbitrary direction.



## Specification

Cabinet           Resolution         1920 × 1080@30 Hz, 1920 × 1080@50 Hz, 1920 × 1080@60 Hz, 1280 × 720@30 Hz, 1280 × 720@50 Hz, 1280 × 720@60 Hz, 3840 × 2160@30 Hz, 3840 × 2160@50 Hz           Built-in System           Operation System         Android 8.1.0           CPU         Cortex-A17, 4-core, main frequency 1.6 GHZ           Memory         2 GB           Storage         16 GB (EMMC)           Interface           Video & Audio Input         AUDIO IN × 1           Video & Audio Output         AUDIO OUT × 1, HDMI OUT × 1           Network Interface         LAN × 1, Wi-Fi           Data Transmission Interface         USB 2.0 × 2, Bluetooth 4.0           Power Supply         12 VAC, 2 A           Standby Consumption         2 VAC, 2 A           Standby Consumption         2 VAC, 2 A           Working Temperature         0 °C to 40 °C (32 °F to 104 °F)           General           Product Dimensions (W × H × 0)         145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")           Working humidity         0 °C to 40 °C (32 °F to 104 °F)           Package Dimensions (W × H × 0)         188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0") <th>• Specification</th> <th></th>	• Specification		
Resolution       , 1280 × 720@50 Hz, 1280 × 720@60 Hz, 3840 × 2160@30 Hz, 3840 × 2160@50 Hz, 3840 × 2160@60 Hz         Built-in System         Operation System       Android 8.1.0         CPU       Cortex-A17, 4-core, main frequency 1.6 GHZ         Memory       2 GB         Storage       16 GB (EMMC)         Interface         Video & Audio Input       AUDIO IN × 1         Video & Audio Output       AUDIO OUT × 1, HDMI OUT × 1         Network Interface       LAN × 1, Wi-Fi         Data Transmission Interface       USB 2.0 × 2 , Bluetooth 4.0         Power         Power Supply       12 VAC, 2 A         Standby Consumption       ≤ 1 W         Working Environment         Working Temperature       0 °C to 40 °C (32 °F to 104 °F)         General         Product Dimensions (W × H × D)       145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")         Working humidity       10 % to 90 %         Package Dimensions (W × H × D)       188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")         Net Weight       0.6 kg (1.3 lb.)         Gross Weight       0.65 kg (1.4 lb.)         Power Adaptor × 1, Remot	Cabinet		
Built-in System Operation System Android 8.1.0 CPU Cortex-A17, 4-core, main frequency 1.6 GHZ Memory 2 GB Storage 16 GB (EMMC) Interface Video & Audio Input AUDIO IN × 1 Video & Audio Output AUDIO OUT × 1, HDMI OUT × 1 Network Interface LAN × 1, Wi-Fi Data Transmission Interface USB 2.0 × 2, Bluetooth 4.0 Power Power Supply 12 VAC, 2 A Standby Consumption ≤ 1 W Working Environment Working Temperature 0 °C to 40 °C (32 °F to 104 °F) General Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3") Working humidity 10 % to 90 % Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0") Net Weight 0.65 kg (1.4 lb.) Packing List Power Adaptor × 1, Remote Control× 1 Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,		1920 × 1080@30 Hz, 1920 × 1080@50 Hz, 1920 × 1080@60 Hz, 1280 × 720@30 Hz	
Built-in System Operation System Android 8.1.0 CPU Cortex-A17, 4-core, main frequency 1.6 GHZ Memory 2 GB Storage 16 GB (EMMC) Interface Video & Audio Input AUDIO IN × 1 Video & Audio Output AUDIO OUT × 1, HDMI OUT × 1 Network Interface LAN × 1, Wi-Fi Data Transmission Interface USB 2.0 × 2, Bluetooth 4.0 Power Power Supply 12 VAC, 2 A Standby Consumption \$1 W Working Environment Working Temperature 0 °C to 40 °C (32 °F to 104 °F) General Product Dimensions (W × H × D) Var System	Resolution	, 1280 × 720@50 Hz, 1280 × 720@60 Hz, 3840 × 2160@30 Hz, 3840 × 2160@50	
Built-in System Operation System Android 8.1.0 CPU Cortex-A17, 4-core, main frequency 1.6 GHZ Memory 2 GB Storage 16 GB (EMMC) Interface Video & Audio Input AUDIO IN × 1 Video & Audio Output AUDIO OUT × 1, HDMI OUT × 1 Network Interface LAN × 1, Wi-Fi Data Transmission Interface USB 2.0 × 2, Bluetooth 4.0 Power Power Supply 12 VAC, 2 A Standby Consumption \$1 W Working Environment Working Temperature 0 °C to 40 °C (32 °F to 104 °F) General Product Dimensions (W × H × D) Var System		Hz 3840 × 2160@60 Hz	
Operation System         Android 8.1.0           CPU         Cortex-A17, 4-core, main frequency 1.6 GHZ           Memory         2 GB           Storage         16 GB (EMMC)           Interface         Video & Audio Input         AUDIO IN × 1           Video & Audio Output         AUDIO OUT × 1, HDMI OUT × 1           Network Interface         LAN × 1, Wi-Fi           Data Transmission Interface         USB 2.0 × 2, Bluetooth 4.0           Power         Power           Power Supply         12 VAC, 2 A           Standby Consumption         ≤ 1 W           Working Temperature         0 °C to 40 °C (32 °F to 104 °F)           General           Product Dimensions (W × H × D)         145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")           Working humidity         10 % to 90 %           Package Dimensions (W × H × D)         188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")           Net Weight         0.6 kg (1.3 lb.)           Gross Weight         0.6 kg (1.4 lb.)           Packing List         Power Adaptor × 1, Remote Control× 1           Default Parameters           Material         MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Duilt in Sustam	, , , , , , , , , , , , , , , , , , ,	
CPU         Cortex-A17, 4-core, main frequency 1.6 GHZ           Memory         2 GB           Storage         16 GB (EMMC)           Interface         Video & Audio Input         AUDIO IN × 1           Video & Audio Output         AUDIO OUT × 1, HDMI OUT × 1           Network Interface         LAN × 1, Wi-Fi           Data Transmission Interface         USB 2.0 × 2, Bluetooth 4.0           Power           Power Supply         12 VAC, 2 A           Standby Consumption         ≤ 1 W           Working Environment         Working Temperature         0 °C to 40 °C (32 °F to 104 °F)           General         Product Dimensions (W × H × D)         145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")           Working humidity         10 % to 90 %           Package Dimensions (W × H × D)         188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")           Net Weight         0.6 kg (1.3 lb.)           Gross Weight         0.65 kg (1.4 lb.)           Packing List         Power Adaptor × 1, Remote Control× 1           Default Parameters           Material         MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,		A 1 11040	
Memory         2 GB           Storage         16 GB (EMMC)           Interface           Video & Audio Input         AUDIO IN × 1           Video & Audio Output         AUDIO OUT × 1, HDMI OUT × 1           Network Interface         LAN × 1, Wi-Fi           Data Transmission Interface         USB 2.0 × 2, Bluetooth 4.0           Power           Power Supply         12 VAC, 2 A           Standby Consumption         ≤ 1 W           Working Environment         0 °C to 40 °C (32 °F to 104 °F)           General         Product Dimensions (W × H × D)         145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")           Working humidity         10 % to 90 %           Package Dimensions (W × H × D)         188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")           Net Weight         0.6 kg (1.3 lb.)           Gross Weight         0.6 s kg (1.4 lb.)           Packing List         Power Adaptor × 1, Remote Control× 1           Default Parameters         DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,			
Storage 16 GB (EMMC)  Interface  Video & Audio Input AUDIO IN × 1  Video & Audio Output AUDIO OUT × 1, HDMI OUT × 1  Network Interface LAN × 1, Wi-Fi  Data Transmission Interface USB 2.0 × 2, Bluetooth 4.0  Power  Power Supply 12 VAC, 2 A  Standby Consumption ≤ 1 W  Working Environment  Working Temperature 0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, Material MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,			
Interface         Video & Audio Input       AUDIO IN × 1         Video & Audio Output       AUDIO OUT × 1, HDMI OUT × 1         Network Interface       LAN × 1, Wi-Fi         Data Transmission Interface       USB 2.0 × 2, Bluetooth 4.0         Power         Power Supply       12 VAC, 2 A         Standby Consumption       ≤ 1 W         Working Environment         Working Temperature       0 °C to 40 °C (32 °F to 104 °F)         General         Product Dimensions (W × H × D)       145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")         Working humidity       10 % to 90 %         Package Dimensions (W × H × D)       188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")         Net Weight       0.6 kg (1.3 lb.)         Gross Weight       0.65 kg (1.4 lb.)         Packing List       Power Adaptor × 1, Remote Control× 1         Default Parameters         DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF,         Material       MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,			
Video & Audio Input  AUDIO IN × 1  Video & Audio Output  AUDIO OUT × 1, HDMI OUT × 1  Network Interface  LAN × 1, Wi-Fi  Data Transmission Interface  USB 2.0 × 2, Bluetooth 4.0  Power  Power Supply  12 VAC, 2 A  Standby Consumption  \$1 W  Working Environment  Working Temperature  0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D)  145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity  10 % to 90 %  Package Dimensions (W × H × D)  188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight  0.65 kg (1.4 lb.)  Packing List  Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Storage	16 GB (EMMC)	
Video & Audio Output AUDIO OUT × 1, HDMI OUT × 1   Network Interface LAN × 1, Wi-Fi   Data Transmission Interface USB 2.0 × 2, Bluetooth 4.0   Power   Power Supply 12 VAC, 2 A   Standby Consumption ≤ 1 W   Working Environment   Working Temperature 0 °C to 40 °C (32 °F to 104 °F)   General   Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")   Working humidity 10 % to 90 %   Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")   Net Weight 0.6 kg (1.3 lb.)   Gross Weight 0.65 kg (1.4 lb.)   Packing List Power Adaptor × 1, Remote Control× 1   Default Parameters   DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Interface		
Network Interface  LAN × 1, Wi-Fi  Data Transmission Interface  USB 2.0 × 2, Bluetooth 4.0  Power  Power Supply  12 VAC, 2 A  Standby Consumption  ≤ 1 W  Working Environment  Working Temperature  0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D)  145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity  10 % to 90 %  Package Dimensions (W × H × D)  188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight  0.6 kg (1.3 lb.)  Gross Weight  0.65 kg (1.4 lb.)  Packing List  Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Video & Audio Input	AUDIO IN × 1	
Data Transmission Interface  Power  Power Supply  12 VAC, 2 A  Standby Consumption  ≤1 W  Working Environment  Working Temperature  0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D)  145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity  10 % to 90 %  Package Dimensions (W × H × D)  188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight  0.66 kg (1.3 lb.)  Gross Weight  0.65 kg (1.4 lb.)  Packing List  Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Video & Audio Output	AUDIO OUT × 1, HDMI OUT × 1	
Power Supply 12 VAC, 2 A Standby Consumption ≤ 1 W  Working Environment  Working Temperature 0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, Material MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Network Interface	LAN × 1, Wi-Fi	
Power Supply 12 VAC, 2 A  Standby Consumption ≤ 1 W  Working Environment  Working Temperature 0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, M14erial MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Data Transmission Interface	USB 2.0 × 2 , Bluetooth 4.0	
Standby Consumption ≤ 1 W  Working Environment  Working Temperature 0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control × 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Power		
Working Environment  Working Temperature 0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control × 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Power Supply	12 VAC, 2 A	
Working Temperature 0 °C to 40 °C (32 °F to 104 °F)  General  Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control × 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Standby Consumption	≤1 W	
General  Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control × 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Working Environment		
Product Dimensions (W × H × D) 145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")  Working humidity 10 % to 90 %  Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control × 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Working Temperature	0 °C to 40 °C (32 °F to 104 °F)	
Working humidity  10 % to 90 %  Package Dimensions (W × H × D)  188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight  0.6 kg (1.3 lb.)  Gross Weight  0.65 kg (1.4 lb.)  Packing List  Power Adaptor × 1, Remote Control × 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	General		
Package Dimensions (W × H × D) 188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")  Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Product Dimensions (W $\times$ H $\times$ D)	145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")	
Net Weight 0.6 kg (1.3 lb.)  Gross Weight 0.65 kg (1.4 lb.)  Packing List Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, Meterial MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Working humidity	10 % to 90 %	
Gross Weight  0.65 kg (1.4 lb.)  Packing List  Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, Meterial  MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Package Dimensions (W × H × D)	188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")	
Packing List  Power Adaptor × 1, Remote Control× 1  Default Parameters  DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF,  Material  MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Net Weight	0.6 kg (1.3 lb.)	
DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, Material MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Gross Weight	0.65 kg (1.4 lb.)	
DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, Material MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Packing List	Power Adaptor × 1, Remote Control× 1	
Material MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	Default Parameters	Default Parameters	
		DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF,	
MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG	Material	MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF,	
		MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG	

## Available Model


DS-D60E-B

## Dimension
















Unit: mm





Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision\_Global





hikvisionhq