

# HS-25/25A Rocking Shaker

Shaker & Rocker

## Introduction

The rocking shaker is a desktop oscillator that can be used directly in the greenhouse or in the incubator. It is widely used in the fixation of various electrophoresis gels, Coomassie blue staining, oscillating shaking during decolorization, silver nitrate staining Fix, dye, develop, etc.

## Feature

1. Platform is made of stainless steel and natural rubber, which is acid & alkali resistant, non-deformation, easy-clean and spill-prevention.
2. Real-time display of speed and diminishing time.
3. The bearing is articulated rotating, secure and no wear, suitable for long time use.
4. Compact designed, save space.
5. Simple and beautiful appearance, humanization design.
6. Adopt stepper motor, low noise.

## Accessories



Flat platform with non-slip rubber mat



Double deck flat platform with non-slip rubber mat



HS-25A

## Parameter

| Model              | HS-25                         | HS-25A                        |
|--------------------|-------------------------------|-------------------------------|
| Speed Range        | 5-80rpm                       | 5-80rpm                       |
| Swing Cycloid      | 25mm (up and down) / 10°      | 25mm (up and down) / 10°      |
| Time Range         | 1min-99h59min                 | 1min-99h59min                 |
| Max. Load          | 5.0kgs (single-deck platform) | 5.0kgs (double-deck platform) |
| Platform Dimension | L.280 x W.228mm               | L.280 x W.228mm               |
| Voltage            | AC 100-230V, 50/60 Hz         | AC 100-230V, 50/60 Hz         |
| Power              | 50W                           | 50W                           |
| Fuse               | 250V, 1A, Φ5x20               | 250V, 1A, Φ5x20               |
| Dimension          | W.284 x D.264 x H.134mm       | W.284 x D.264 x H.248mm       |
| Net Weight         | 5.2kgs                        | 6.0kgs                        |



HS-25