




TDS Pocket Testers		TDSTestr 11+	TDSTestr 11
			
Range		0 to 200.0 ppm 0 to 2000 ppm 0 to 10.00 ppt	0 to 2000 ppm 0 to 10.00 ppt
Resolution		0.1 ppm 1 ppm 0.01 ppt	10 ppm 0.10 ppt
Accuracy		±1 % Full scale of each range	
Calibration Points		3 Manual	2 Manual
TDS Factor		0.40 to 1.00 (Selectable)	
Temperature	Range	0 to 50.0 °C or 32.0 to 122.0 °F	
	Resolution	0.1 °C / °F	
	Accuracy	0.5 °C / 0.9 °F	
	Calibration Window	±5.0 °C / 9.0 °F	
Meter Functions	ATC	Yes (0.0 to 50.0 °C or 32.0 to 122.0 °F)	
	Sensor Type	Cup	Dip
	Temp. Coefficient	2 % per °C	
	Normalization Temp.	25.0 °C	
	Non-Volatile Memory	Yes	
	Auto-Off	8.5 Mins after last key pressed	
	Operating Temp.	0.0 to 50.0 °C	
	LCD Display	Custom dual display 2.7 cm (H) x 2.1 cm (W)	
	Power	4 x 1.5 V "A76" Micro alkaline batteries	
	Battery Life	> 150 Hours	
Dimensions ; Weight	Tester	16.5 x 3.8 cm ; 90 g	
	Boxed	22 x 6 x 5 cm ; 170 g	

Salinity Pocket Tester		SaltTestr 11
		
Range		0 to 10.00 ppt
Resolution		0.10 ppt
Accuracy		±1 % Full scale of each range
Calibration Points		1 Point
Temperature	Range	0 to 50.0 °C or 32.0 to 122.0 °F
	Resolution	0.1 °C / °F
	Accuracy	0.5 °C / 0.9 °F
	Calibration Window	±5.0 °C / 9.0 °F
Meter Functions	ATC	Yes (0.0 to 50.0 °C or 32.0 to 122.0 °F)
	Sensor Type	Dip
	Temp. Coefficient	2 % per °C
	Normalization Temp.	25.0 °C
	Non-Volatile Memory	Yes
	Auto-Off	8.5 Mins after last key pressed
	Operating Temp.	0.0 to 50.0 °C
	LCD Display	Custom dual display 2.7 cm (H) x 2.1 cm (W)
	Power	4 x 1.5 V "A76" Micro alkaline batteries
	Battery Life	> 150 Hours
Dimensions ; Weight	Tester	16.5 x 3.8 cm ; 90 g
	Boxed	22 x 6 x 5 cm ; 170 g



<< Wastewater Treatment
>> Swimming Pools

<< Water Treatment
>> Aquariums & Fish Farms