



# DLH

## Overhead Stirrers

---

Digital overhead stirrer with 80 Ncm torque  
for medium-high viscosity application



# Robust, Safety and Convenient

DLH overhead stirrer guides the user with an extremely bright and easy to read display; all the most important parameters are available at a glance.

- Maximum torque of 80 Ncm
- Supports applications with a maximum viscosity of 50 000 mPa\*s
- Electronic speed regulation from 50 to 2000 rpm, up to 40 L
- SpeedServo™ ensures constant speed even when the viscosity changes
- Operating time can be set up to 999:59 minutes; automatic switch off
- Extremely bright and easy-to-read display
- Long life, robust motor
- Easy-chuck to change the shafts without tools
- Automatically stops if blocked – no burn-out or damage
- Overload, overcurrent and overtemperature protection
- Sealed to IP 40 standard



## INSTRUMENT - CODE

**DLH** **110-230 V / 50-60 Hz** **F201A0157**

## TECHNICAL DATA

CONSTRUCTION MATERIAL	Technopolymer and epoxy painted aluminum alloy
CHUCK RANGE	1 - 10 mm
VISUALIZATION OF SET SPEED	Display LCD
ELECTRONIC PROTECTION RATING CEI EN 60529	IP 40
ELECTRONIC SPEED REGULATION	From 50 to 2000 rpm
STIRRING VOLUME MAX (H2O)	Up to 40 L
MAX VISCOSITY	50000 (mPa*s)*
TORQUE MAX	80 Ncm
ALLOWED ROOM TEMPERATURE	From 0 to 40 °C
DIMENSION (WXHXD)	80x230x196 mm
POWER	190 W
WEIGHT	3.0 Kg



We reserve the right to make technical alterations  
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

### DESIGNED AND MANUFACTURED IN ITALY



**ITALY - HQ**  
Via Stazione 16  
20865 Usmate (MB) Italy  
Tel. +39 039 628811  
velpitalia@velp.com

**INDIA**  
velpindia@velp.com

**USA**  
155 Keyland Court, Bohemia  
NY 11716 - U.S.  
Tel. +1 631 573 6002  
velpusa@velp.com

**CHINA**  
Xinlong Rd Building 28, Lane 1333  
Shanghai city - China  
Tel. +86 180 1755 7329  
velpchina@velp.com