

# PORTABLE PRESSURE STEAM STERILIZER

Electric or LPG heated

YX-18LM/YX-24LM



## Characteristics:

- Fully stainless steel structure.
- Electric or LPG heated.
- Working pressure: 0.14~0.16MPa.
- Working temperature: 126°C
- Double scale indication pressure gauge.
- Easy to operate, safe and reliable.

## Specifications:

Model	YX-18LM	YX-24LM
Sterilizing volume	18L(280*260mm)	24L(280*390mm)
Working pressure	0.14 - 0.16 Mpa	
Working temperature	126°C	
Max. Safety pressure	0.165 Mpa	
Power	AC220V/50Hz / 2 KW	
Dimension	410×410×430 mm	410×410×550 mm
G.w /n. W	16/14 KG	17/15 KG

**PORTABLE PRESSURE STEAM STERILIZER****Electric or LPG heated**

YX-12LM

**Specifications:**

Model	YX-12LM
Sterilizing Volume	12L(240*200mm)
Working Pressure	0.14 - 0.16 Mpa
Working Temperature	126°C
Max. Safety Pressure	0.165 Mpa
Power / Consumption	AC220V/50Hz/ 2KW
Dimension	360×360×420 mm
G.W/N. W	12/11KG

**Characeristics:**

- Fully stainless steel structure.
- Electric or LPG heated.
- Double scale indication pressure gauge.
- Easy to operate,safe and reliable.