

Water Stills, Model W4L Favorit, Malaysia

Features

- Horizontal thick wall heat resistant glass boiler made from ISO 3585 borosilicate glass.
- Boiler fitted with 3 KW chromium plate heater from England.
- High efficiency coil condenser made from ISO 3585 borosilicate glass.
- Coil condenser capable of yielding low temperature, high output quality distillate of conductivity 3 to 4 $\mu\text{s}/\text{cm}$.
- Compact construction suitable for bench and wall mounting.
- Screwthread connectors enable easy fitting or removal of hose safely.
- Built-in constant level device with Vendura-Nova valve for drainage provides easy descaling without dismantling.
- Safety thermostat built into the heater assembly protects the Favorit water still in the event of water supply failure and automatically resets when the water supply is restored.



Water Stills, Model W4L

Specification

Model	W4L
Distillate Output	4 Litres Per Hour, Single Distilled
Electrical Power Requirement	220/240 Vac, 50/60 Hz Single Phase
Equipment Dimension (w x d x h)	46 x 15 x 44 cm
Packing Dimension (w x d x h)	65 x 26 x 48 cm
Gross Weight	7.2 kg

Ordering Information

Catalog No.	Description	Pack Qty
P21001	Basic Water Stills, Model W4L 4 Liters/Hour Distillate Output, Singled Distilled	1

Spare Parts

Catalog No.	Description	Pack Qty
P21602	White Triangular Rubber Gasket	1
P21501	Fiber Insert For Triangular Metal Flange	1
P21701	Metal Heater With Built-in Thermostat	1
P21711	Thermostat For W4L, WCM4L	1
P21802	Support Stand	1
P21806	Triangular Metal Flange	1
P21826	Hexagon Head Bolt	1
P21805	Strap For Boiler W4L	1
P21901	Boiler For W4L	1
P21911	Condenser For W4L	1