


AIR AMPLIFIERS

Blowoff, clean, cool and dry as well as vent and exhaust with no moving parts

WHAT ARE THEY - REASONS TO USE

Air Amplifiers or “Air Movers” are a simple, inexpensive device with virtually no maintenance that can convey fumes, smoke, light weight materials, and move a high volume of air for cooling, blowoff and drying applications. They use the “coanda effect” which entrains a large amount of surrounding air using only a small amount of compressed air. The effect is an amplification of up to 17 times the airflow or more (depending on the size) with reduced noise levels. Using only compressed air, the output flow and vacuum is easily controlled by adjusting or opening the air gap and/or inlet pressure. Either end of the amplifier may be ducted to address all kinds of applications from bringing in fresh air into an area to removing nasty fumes. Be wary of extremely high unrealistic or unsubstantiated amplification ratios claimed by some companies.



AIR AMPLIFIER FEATURES:

- ▶ No moving parts.
- ▶ Compact design, simple, lightweight and portable.
- ▶ Driven by air not electricity.
- ▶ Replaces fans used for blowoff, cleaning, drying, cooling and conveying.
- ▶ High airflow amplification.
- ▶ Instant on-off, no electricity or explosion hazard.

AIR AMPLIFIER BENEFITS:

- ▶ Longer life in difficult environments than competitive models.
- ▶ Lower compressed air consumption than ejectors and venturi.
- ▶ Maintenance free with output easily controlled, safe to use.

AIR AMPLIFIER ADVANTAGES OVER FANS:

- ▶ Compact design, simple, lightweight and portable.
- ▶ Driven by air, not electricity for safety.
- ▶ No moving parts hence safer and maintenance free.
- ▶ Each end can be ducted for light conveying applications.

SELECTION

The fixed unit being made of heavy duty zinc die cast is more ideal in rough environments where corrosion is not an issue. The aluminum Adjustable Air Amplifiers are light-weight and flexible because of being adjustable. Stainless steel adjustable units are meant for corrosive environments and for food/pharmaceutical applications.

TYPES OF AIR AMPLIFIERS



STANDARD “FIXED” AIR AMPLIFIER: made of zinc die cast system is solid and perform as well or better than many supposedly patented designs when used in similar applications. The gap can be adjusted by adding shims. Five sizes are available.



ADJUSTABLE AIR AMPLIFIER: made of anodized aluminum or stainless steel for high temperature or food applications. The customer can set the gap and lock it in place using a lock ring. Three sizes are available.

SPECIAL DESIGNS


Special designs are available to meet unique customer specifications. Specially treated stainless steel units have been made for a specific medical application and threaded adjustable versions have been made for a machine builder. Different materials can be provided as well as special sizes to fit any specific application.



Mounting and holding systems are available for the Air Amplifiers. Fully flexible positioning. See Accessories

STANDARD AIR AMPLIFIER - HOW IT WORKS:


A small amount of compressed air enters the annular chamber at point (A). That is then throttled through a small ring nozzle at high velocity and into the inside of the Amplifier over a “coanda” profile. The compressed air stream clings to the “coanda” profile as it enters the inside walls of the amplifier and thereby creating a vacuum that induces the outside air at point (B). Converting the pressure into amplified airflow. The amplified airflow leaves at the exit at point (C). Airflow is further amplified downstream at point (D). By entraining additional air from the surroundings at the exit.



AMPLIFIERS-RATIOS (APPROX.)

Model AM10: 6.5:1
Model AM20: 14:1
Model AM40: 15:1
Model AM75: 15:1
Model AM125: 16:1


MODEL NO.	A Inches (MM)	B Inches (MM)	C Inches (MM)	D Inches (MM)	E Inches (MM)	F Inches (MM)	G Inches (MM)	H Inches (MM)	I Inches (MM)	J Inches (MM)	K (NPT)
AM10	0.40"	1.30"	0.99"	1.89"	2.24"	0.19"	0.16"	0.59"	0.75"	1.59"	1/8"
	(10.16)	(33.1)	(25.2)	(48)	(57)	(4.8)	(4)	(15)	(19)	(40.4)	
AM20	0.81"	1.86"	1.50"	2.39"	3.03"	0.27"	0.20"	0.59"	1.27"	2.16"	1/4"
	(20.6)	(47.2)	(38)	(60.8)	(76.9)	(6.8)	(5)	(15)	(32.2)	(54.8)	
AM40	1.59"	3.15"	2.93"	3.54"	4.18"	0.29"	0.24"	0.79"	2.03"	2.84"	3/8"
	(40.4)	(80)	(74.5)	(90)	(106.1)	(7.4)	(6.2)	(20)	(51.6)	(72.2)	
AM75	2.98"	5.91"	4.96"	6.89"	8.46"	0.53"	0.51"	1.18"	3.98"	5.94"	1/2"
	(75.8)	(150)	(126)	(175)	(215)	(13.5)	(13)	(30)	(101)	(151)	
AM125	4.92"	10.24"	7.09"	-	-	-	-	0.79"	7.80"	16.54"	3/4"
	(125)	(260)	(180)	-	-	-	-	(20)	(198)	(420)	




AM10

AMPLIFICATION RATIO = 6.5:1 (SEE ADDENDUM-I)

Pressure vs. Air Consumption for Model AM 10 Standard Air Amplifier




Pressure vs. Air Flow At Outlet for Model AM 10 Standard Air Amplifier





AM10

Pressure vs. Velocity At Outlet for Model AM 10 Standard Air Amplifier




Pressure vs. Velocity 6" From Outlet for Model AM 10 Standard Air Amplifier




AM20

AMPLIFICATION RATIO = 14:1 (SEE ADDENDUM-I)

Pressure vs. Air Consumption for Model AM 20 Standard Air Amplifier




Pressure vs. Air Flow At Outlet for Model AM 20 Standard Air Amplifier





AM20

Pressure vs. Velocity At Outlet for Model AM 20 Standard Air Amplifier




Pressure vs. Velocity 12" From Outlet for Model AM 20 Standard Air Amplifier



AM40

AMPLIFICATION RATIO = 15:1 (SEE ADDENDUM-I)

Pressure vs. Air Consumption for Model AM 40 Standard Air Amplifier




Pressure vs. Air Flow At Outlet for Model AM 40 Standard Air Amplifier





AM40

Pressure vs. Velocity At Outlet for Model AM 40 Standard Air Amplifier




Pressure vs. Velocity 12" From Outlet for Model AM 40 Standard Air Amplifier




AM75

AMPLIFICATION RATIO = 15:1 (SEE ADDENDUM - I)

Pressure vs. Air Consumption for Model AM 75 Standard Air Amplifier




Pressure vs. Air Flow At Outlet for Model AM 75 Standard Air Amplifier





AM75

Pressure vs. Velocity At Outlet for Model AM 75 Standard Air Amplifier




Pressure vs. Velocity 12" From Outlet for Model AM 75 Standard Air Amplifier




AM125

AMPLIFICATION RATIO = 16:1 (SEE ADDENDUM - I)

Pressure vs. Air Consumption for Model AM 125 Standard Air Amplifier




Pressure vs. Air Flow At Outlet for Model AM 125 Standard Air Amplifier





AM125

Pressure vs. Velocity At Outlet for Model AM 125 Standard Air Amplifier




Pressure vs. Velocity 12" From Outlet for Model AM 125 Standard Air Amplifier




CAST ZINC FIXED STANDARD AIR AMPLIFIERS

PART NO.	DESCRIPTION
AM10	3/4" Zinc Alloy Amplifier
AM20	1-1/4" Zinc Alloy Amplifier
AM40	2" Zinc Alloy Amplifier
AM75	4" Zinc Alloy Amplifier
AM125	8" Zinc Alloy Amplifier
AM10-1	3/4" Amplifier plus Filter with Auto Drain
AM20-1	1-1/4" Amplifier plus Filter with Auto Drain
AM40-1	2" Amplifier plus Filter with Auto Drain
AM75-1	4" Amplifier plus Filter with Auto Drain
AM125-1	8" Amplifier plus Filter with Auto Drain
AM10-2	3/4" Amplifier plus Filter with Auto Drain plus Regulator with Gauge
AM20-2	1-1/4" Amplifier plus Filter with Auto Drain plus Regulator with Gauge
AM40-2	2" Amplifier plus Filter with Auto Drain plus Regulator with Gauge
AM75-2	4" Amplifier plus Filter with Auto Drain plus Regulator with Gauge
AM125-2	8" Amplifier plus Filter with Auto Drain plus Regulator with Gauge
SH10-2	Stainless Steel Shim, .002" for AM10
SH10-3	Stainless Steel Shim, .003" for AM10
SH20-2	Stainless Steel Shim, .002" for AM20
SH20-3	Stainless Steel Shim, .003" for AM20
SH40-2	Stainless Steel Shim, .002" for AM40
SH40-3	Stainless Steel Shim, .003" for AM40
SH75-2	Stainless Steel Shim, .002" for AM75
SH75-3	Stainless Steel Shim, .003" for AM75
SH125-3	Stainless Steel Shim, .003" for AM125

Using Model AM20 Air Amplifiers to cool castings, cooling time was reduced by 20%




Two Model AM40 Air Amplifiers vent fumes from a tank quickly & efficiently



ADJUSTABLE AIR AMPLIFIER - HOW IT WORKS:

A large volume of surrounding air is induced into the Amplifier at point (A) by the action of a small amount of compressed air which enters the annular chamber at point (B) that is then throttled through a small ring Nozzle at high velocity and into the inside of the Amplifier over a coanda profile. The compressed air stream clings to the coanda profile as it enters the inside walls of the Amplifier and thereby creating a vacuum that induces the outside air converting the pressure into amplified airflow. The amplified airflow leaves at the exit at point (C). Airflow is further amplified downstream at point (D) by entraining additional air from the surroundings at the exit.



ADJUSTABLE AIR AMPLIFIER SPECIFICATIONS:

Normally set to .002" (.05mm) gap if greater air force is required, the gap is adjustable. The first two sizes of adjustable air amplifiers come in two versions – unmarked regular versions and marked to gauge the gap setting from 0 to 1.5 mm.


ADJUSTABLE AIR AMPLIFIER RATIOS (APPROX.)

Models 40000 and 40000S: 10:1
Models 40001, 40001G and 40001S: 15:1
Models 40002, 40002G and 40002S: 16:1
Models 40003 and 40003S: 17:1

Model	A Inches (MM)	B Inches (MM)	C Inches (MM)	D Inches (MM)	E Inches (MM)	F INLET
40000 / 40000S	2.22" (57)	1.25" (32)	.75" (19)	1.5" (38)	1.5" (38)	1/8" NPT
40001 / 40001S	2.875" (73)	1.74" (44.2)	1.25" (31.75)	1.98" (50.3)	1.91" (48.4)	1/4" NPT
40002 / 40002S	3.25" (82.6)	2.75" (69.85)	2" (50.80)	2.98" (75.7)	2.19" (55.6)	3/8" NPT
40003 / 40003S	5.1" (130)	5.2" (132.6)	4" (101.6)	5.5" (139.7)	3.37" (85.5)	1/2" NPT

*BSP Threads or Adaptors can be supplied depending on country location.


ADJUSTABLE AIR AMPLIFIER




40000 and 40000S

AMPLIFICATION RATIO = 10:1 (SEE ADDENDUM - I)

Pressure vs. Air Consumption for Model 40000 and 40000S Adjustable Air Amplifier




Pressure vs. Air Flow At Outlet for Model 40000 and 40000S Adjustable Air Amplifier





40000 and 40000S

Pressure vs. Velocity At Outlet for Model 40000 and 40000S Adjustable Air Amplifier





Pressure vs. Velocity 12" From Outlet for Model 40000 and 40000S Adjustable Air Amplifier




40001, 40001G and 40001S

AMPLIFICATION RATIO = 15:1 (SEE ADDENDUM - I)





40001, 40001G and 40001S

Pressure vs. Velocity At Outlet for Model 40001, 40001G and 40001S Adjustable Air Amplifier




Pressure vs. Velocity 12" From Outlet for Model 40001, 40001G and 40001S Adjustable Air Amplifier




40002, 40002G & 40002S

AMPLIFICATION RATIO = 16:1 (SEE ADDENDUM - I)

Pressure vs. Air Consumption for Model 40002, 40002G & 40002S Adjustable Air Amplifier




Pressure vs. Air Flow At Outlet for Model 40002, 40002G & 40002S Adjustable Air Amplifier





40002, 40002G & 40002S

Pressure vs. Velocity At Outlet for Model 40002, 40002G & 40002S Adjustable Air Amplifier




Pressure vs. Velocity 12" From Outlet for 40002, 40002G & 40002S Adjustable Air Amplifier




40003 & 40003S

AMPLIFICATION RATIO = 17:1 (SEE ADDENDUM - I)

Pressure vs. Air Consumption for Model 40003 & 40003S Adjustable Air Amplifier




Pressure vs. Air Flow At Outlet for Model 40003 & 40003S Adjustable Air Amplifier








40003 & 40003S

Pressure vs. Velocity At Outlet for Model 40003 & 40003S Adjustable Air Amplifier





Pressure vs. Velocity 12" From Outlet for Model 40003 & 40003S Adjustable Air Amplifier







The Adjustable Air Amplifier can be adjusted to provide the blow-off force and/or vacuum required for any particular application. Made of anodized aluminum or stainless steel for corrosive and hightemperature applications the unit offers flexibility in applications.



Adjustable Air Amplifier mounting brackets allow for easy mounting. Available for the 1-1/4" and 2" sizes. Made in Stainless Steel.

The Gauged Adjustable Air Amplifier with marking to indicate the settings from 0 to 1.5 mm comes in anodized aluminum for applications where accurate gap control is required. As with the regular adjustable unit the gapis locked into place with a lockring.



ADJUSTABLE AIR AMPLIFIERS - ALUMINUM

PART NO.	DESCRIPTION
40000	3/4" Adjustable Aluminum Air Amplifier
40001	1-1/4" Adjustable Aluminum Air Amplifier
40002	2" Adjustable Aluminum Air Amplifier
40003	4" Adjustable Aluminum Air Amplifier
41001	1-1/4" Adjustable Aluminum Amplifier plus Filter with Auto Drain
41002	2" Adjustable Aluminum Amplifier plus Filter with Auto Drain
41003	4" Adjustable Aluminum Amplifier plus Filter with Auto drain
42001	1-1/4" Adjustable Aluminum Amplifier plus Filter with Auto Drain plus Regulator with Gauge
42002	2" Adjustable Aluminum Amplifier plus Filter with Auto Drain plus Regulator with Gauge
42003	4" Adjustable Aluminum Amplifier plus Filter with Auto Drain plus Regulator with Gauge

ADJUSTABLE AIR AMPLIFIERS - GAUGED SETTINGS

PART NO.	DESCRIPTION
40001G	1-1/4" Adjustable Aluminum Air Amplifier with Gauged Settings
40002G	2" Adjustable Aluminum Air Amplifier with Gauged Settings
41001G	1-1/4" Adjustable Aluminum Air Amplifier with Gauged Settings plus Filter with Auto Drain
41002G	2" Adjustable Aluminum Air Amplifier with Gauged Settings plus Filter with Auto Drain
42001G	1-1/4" Adj. Aluminum Air Amplifier with Gauged Settings plus Filter with Auto Drain plus Regulator with Gauge
42002G	2" Adj. Aluminum Air Amplifier with Gauged Settings plus Filter with Auto Drain plus Regulator with Gauge

ADJUSTABLE AIR AMPLIFIERS - STAINLESS STEEL

PART NO.	DESCRIPTION
40001S	1-1/4" Adjustable Stainless Steel Air Amplifier
40002S	2" Adjustable Stainless Steel Air Amplifier
40003S	4" Adjustable Stainless Steel Air Amplifier
41001S	1-1/4" Adjustable Stainless Steel Amplifier plus Filter with Auto Drain
41002S	2" Adjustable Stainless Steel Amplifier plus Filter with Auto Drain
41003S	4" Adjustable Stainless Steel Amplifier plus Filter with Auto Drain
42001S	1-1/4" Adjustable Stainless Steel Amplifier plus Filter with Auto Drain plus Regulator with Gauge
42002S	2" Adjustable Stainless Steel Amplifier plus Filter with Auto Drain plus Regulator with Gauge
42003S	4" Adjustable Aluminum Steel Amplifier plus Filter with Auto Drain plus Regulator with Gauge
40001 MTS	Mouning bracket for 40001, 40001G and 40001S
40002MTS	Mouning bracket for 40002, 40002G and 40002S

Spray Booth Dry Air Gun System

Blowoff, clean, cool and dry as well as vent and exhaust with no moving parts

SPRAY BOOTH DRY AIR GUN SYSTEM:

Similar to the Model: 48001 but fixed to a handle and supplied with a filter screen on the intake end, this unit is designed especially for cooling solvent and water based paint surfaces quickly and efficiently.


SPECIFICATIONS:

- ▶ Maximum inlet pressure: 10 bar (145 psig)
- ▶ Working pressure: 3-6 bar (43-87 psig)
- ▶ Air Consumption: 12.3 cfm (350l/min) at 60 psig
- ▶ Air Inlet thread 1/4" NPT

FIXED MOUNTING SYSTEM



ADJUSTABLE MOUNTING SYSTEM



SPRAY BOOTH DRY AIR GUN SYSTEM



MOUNTING SPECIFICATION

The Mounting Brackets come in two versions: Model 48002 Fixed System complete with a sturdy stand, vertical support bar, parallel support bar and two movable supports to hold the Dry Air Guns or any other blowoff product from an air knife or amplifier to jets and nozzles. The compressed air is fed in at the bottom of the support with hoses (supplied with the system) feeding the blowoff units. Model 48003 Adjustable System is the same as the above except for the adjustable parallel support bar for totally variable support adjustments to aim the blowoff units wherever they need to be. This simple design allows for tremendous portability and flexibility of use for many blowoff applications

PART NO.	DESCRIPTION
48001	Dry Air Gun Only
48002	Fixed Mounting System
48003	Flexible Mounting System
48004	Diffuser Spare Part
48005	Spare Sieve