

Small Machine, Tools & Equipment For Rental



NishioRentAll

Rentall.co.th

บริการเช่าเครื่องจักร รายวัน - รายเดือน - รายปี

Hand Guide Roller

Specifications

MAKE	TAIKYOKU	MIKASA	Kanjo Teko	
MODEL	TMR65KDS	MRH600DSA	H650K	
Dimensions	Operating weight (kg)	675	620	640
	Overall width (mm)	700	692	694
	Overall length (mm)	2,385	2,620	2,350
	Overall height (mm)	1,150	1,130	1,175
	Wheelbase (mm)	560	520	520
Drum size	Diameter (mm)	402	355	356
	Width (mm)	650	650	648
	Vibrating power	Centrifugal force (kg)	1,100	1,100
Traveling speed	Frequency (vpm)	3,300	3,300	55 Hz
	Gradability (°)	25	20	46
	Forward (km/h)	0~3.6	0~3	3.5
Engine	Rated output (ps/rpm)	5.4/2,500	6.0/2,500	5.3/4
Fuel tank capacity (ℓ)	4.8	5.2	4.8	
Water tank capacity (ℓ)	35	40	35	



MRH600DSA



MVC-90BG

Plate Compactor (Gasoline / Diesel)

Specifications

MAKE	MIKASA			Wacker
MODEL	MVC-60	MVC-90BG	MVC110D	DPS185H
Dimensions	Length (mm)	825	1,160	1,130
	Height (mm)	890	720	925
	Weight (kg)	60	81	125
Plate size	Length (mm)	510	560	670
	Width (mm)	350	500	520
Vibrating frequency (vpm)	5,600	5,800	5,800	90 Hz
Centrifugal force (kN)	10.0	15.2	21.6	18
Max. Traveling speed (m/min)	20-25	25	25	22
limited gradeability (°)	25	20	35	30
Power source	Gasoline		Diesel	Diesel

Reversible Compactor

Specifications

MAKE	MIKASA	
MODEL	MVH-306DS	
Dimensions	Length (mm)	1,570
	Height (mm)	970
	Weight (kg)	350
Plate size	Length (mm)	860
	Width (mm)	445
Vibrating frequency (vpm)	4,400	
Centrifugal force (kN)	45.0	
Max. Traveling speed (m/min)	0-23	
limited gradeability (°)	20	
Power source	Diesel	



MVH-306DS

Tamping Rammer (Gasoline / Diesel)

Specifications

MAKE	WACKER	MIKASA		
MODEL	DS70	MT72FW	MT-65HE	MT-76D
Dimensions	Length (mm)	725	730	740
	Width (mm)	370	415	370
	Height (mm)	1,000	1,045	1,070
	Weight (kg)	83	74	66
Plate size	Length (mm)	330	340	340
	Width (mm)	280	285	285
Jumping stroke (mm)	Up to 75	50-75	50~80	50~80
Impact force (kN)	16	13.7	16.5	17.5
Impact number per min.	700	642-679	640-695	650-700
Power source	Diesel	Gasoline	Gasoline	Diesel



MT-65HE

Protection Mat • Aluminium Ladder • New Carrier

Protection Mat

Specifications

Material	100% Polyethylene (Recycled)
Size	1220×2440 mm (4ft×8ft)
Weight	39 Kgs.
Thickness	12.8 mm
Load Capacity	60T (Based on track record)



Specifications New Carrier

Model	Load Center (Kg)	Length (mm)	Width (mm)	Height (mm)	Weight (Kg)
N-1200	1,200	1,200	800	335	50



Specifications Aluminium Ladder

Model	Height (mm)	Platform area (D×W)	Dimension		Load Center (Kg)	Weight (Kg)
			Width (W2)	Width (D2)		
DUK15SX	1,100 - 1,400	1,300×500	765×2,088	868×2,331	150	18
DUK18SX	1,440 - 1,850	1,600×500	850×2,590	958×2,842	150	24

Electric Tools

Bar Cutter (Portable & Stationary Type)

Specifications

MAKE	IKURA	TANAKA	COPKO
MODEL	IS-25SC	KC-32	SKC32
Cutting capacity (mmφ)	25	32	25
Input (kW)	1.05	1.55	2.2 / 380V
Dimensions (L×W×H) (mm)	—	650×510×950	920×660×800
Weight (kg)	15.7	420	400



Bar Bender / Bar Straighter (Portable & Stationary Type)

Specifications

MAKE	OGURA	TOYO	COPKO
MODEL	HBB-32	B-33	SKB32
R.Bar capacity (mm)	32	32	25
Input (kW)	0.7	2.2	2.2/380V
Dimensions (L×W×H) (mm)	590×290×210	965×950×750	1000×830×860
Weight (kg)	19	450	450



Core Drill Machine

Specifications

MODEL	SPN-8A2	TS1800
Max Bit Dia (inch/mm)	8/205	200
Rated Current (A)	9	17
Max. Output (W)	2,400	2,550
Power Source (V)	220/single	100/single
No-Load Speed (rpm/min)	680	700
Dimensions (L×W×H) (mm)	395×232×412	217×158×803
Weight (kg)	10.3	16.3



Baby Sander

MODEL	9500NB
Capacity Depressed center wheel (mm/inch)	100/4"
Power Input (W)	570
No-Load Speed (min/rpm)	12,000
Overall Length (mm)	253
Weight (kg)	1.5

* Blade is sales item.



Rotary Hammer Drill

Specifications

MAKE	BOSCH
MODEL	GBH5-40D
Rated power input (W)	1,100
Impact energy (J)	8.5
Impact rate at rated speed (bpm)	1,500 - 2,900
Rated speed (rpm)	170 - 340
Weight without cable (kg)	6.8



HM1201

Electric Hammer

Specifications

MAKE	MAKITA	
MODEL	HM1201	HM1306
Input (kW)	1.13	1.51
Blows Per Minute (rpm/min)	2,000	1,450
Overall Length (mm)	430	645
Weight (kg)	8.7	15



HM1306

* Chisel is sales item

Electric Hand Cutter

MODEL	K2300EL
Rated Voltage (V)	220
Rated Current (A)	15
Power (W)	1400
Cutter Disc (inch)	12
Dimensions (L×W×H) (mm)	630×205×215
Weight (kg)	9

* Blade is sales item.



Engine Hand Cutter

MAKE	MIKASA	Husqvarna
MODEL	MCH-300L	K650
Displacement (cc)	66.8	71
Fuel	gasoline 0.64ℓ 2cycle oil 0.37ℓ	gasoline : 2cycle oil 50 : 1
Cutter Disc (m/m)	305	305
Dimensions (L×W×H) (mm)	635×360×270	705×205×307
Weight (kg)	11	11

* Blade is sales item.



Concrete Cutter

MAKE	MIKASA				Wacker
MODEL	MCD-L14	MCD-214	MCD-216	MCD-218	BFS18
Max cutting depth (mm)	120	120	145	170	175
Cutter Disc (inch)	14	14	16	18	14-18
Water tank capacity (ℓ)	45	45	45	45	45
Weight (kg)	86	113	136	139	117
Dimensions (mm)	Length	1,650	1,958	1,958	1,045
	Width	527	540	540	540
	Height	930	965	981	981
Power Source (gasoline engine)	5.9kW 4cycle	5.9kW 4cycle	6.6kW 4cycle	8.1kW 4cycle	Diesel

* Blade is sales item.

และยังมีเครื่องจักรอื่นๆให้เช่าเพิ่มเติมอีกมากมาย

Light



Flood Light "Mini Tellastar"

Specifications

MAKE	NISHIO	
MODEL	NTC-46W-2	
Bulb Capacity (W x bulbs)	400 x 4	
Bulb Configuration	High vapor mercury bulb H-400	
Bulb Output (Lumens)	82,000	
Dimension (mm)	Length	1,055
	Width	860
	Height	2,065
Max. Height of tower (mm)	A	3,400
Weight (kg)	271	
Generator	Engine	DA3000SS
	Output Single Phase (kW)	3
Fuel tank capacity (ℓ)	Diesel 15	



Halogen Handy Light

Specifications

MODEL	HS-500S	HS-1000S
Weight (kg)	2.6	5.5
Powerinput (V)	100	100

Solar LED Signal Light

MAKE	Nishio-Asco
MODEL	SFL600
Dimension	600x646x100mm
Weight	7.0kg
Lamp	Polycarbonate
Battery	Extra high - lminance LED (Blue-Green/orange light)
Solar Panel	Nickel Hydrogen Battery
Solar Charge	High efficiency crystal cell
Charge by AC adapter (Option)	Charge Approx. 5hours
Period of use without sunshine	Charge Approx. 10hours
Type of signal light	Approx. 15 days In Super Eco mode
	Rotation mode
	Random Flashing mode
	Super Eco mode
Brightness control	Day - night brightness adjustment : Fully automatic
Over charge protection function	Yes
Over heat protection function	Yes : by Automatic power disconnection
Over Current protection function	Yes : by Automatic power disconnection

Mobile Flood Light (Electric Model)

MAKE	Nishio	
MODEL	SVN400W	
Bulb Capacity (W)	400W Metal Halide	
Weight (kg)	14.5	
Power Source (V)	220	
Max. Height (m)	2.3	
Min. Height (m)	1.7	
Cable Length (m)	7	



Wobble Light

Specifications

MODEL	WL400MH
Height (mm)	935
Weight (kg)	17
Power input (W)	400
Bulb capacity	400W Metal Halide
Bulb height (mm)	760
Power source (V)	200
Rated current (A)	5



Fan



Industrial Fan

Model	Size	Motor	Air Flow (cfm)
F1A	24"	300W	3,000
IF-24	24"	1/2Hp 220V	7,500



Duct Hole

Ducting Capacity

Blade Dia	Length (m)
300 φ	5
600 φ	10



Portable Ventilator

Diameter (mm)	300	600	
Power rating (W)	380	1,500	2,200
Voltage (V)	220 - 240	220 - 240	415
Weight (kg)	16.0	68	60

Air Jet Fan

Specifications

Model	Mounting Slot Diameter	Bolt Circle Diameter	Inlet	Max PSI	Outside Diameter	Net Weight
TX-JF24	1"	24" API	1" NPT	110 PSI	24 - 1/2" x 12"	132 lbs

Air Mover

Specifications

Model	Length	Diameter of Base	Diameter top of Horn	NPT Size	Bolt Circle Diameter	Base Slot Diameter	Net Weight
TX-6AM-P	44.25"	11.25"	12.5"	1"	10.5"	0.4	132 lbs



Swing Gate

Specifications

Model	Size
TX-SG24	24"

Cleaning Equipment



Floor Polisher

Specifications

MAKE	CHAMPION	
MODEL	RPM320	
Size	18"	
Power (hp)	1	
Speed/min (rpm)	500	

* Brush & Pad are sales item.



Brush Cutter

Specifications

MAKE	HONDA	
MODEL	UMK-422U	
Dimensions [L x W x H] (mm)	1,890 x 585 x 390	
Displacement (cc)	22.2	
Fuel tank (ℓ)	0.45	
Blade (mm)	230	
Total weight (kg)	6.6	



Industrial Sweeper

Specifications

MAKE	Hako	
MODEL	HAKO-Profi-Flipper	
Working Width w side brush (mm)	670	
Working Width w/o side brush (mm)	480	
Working w side brush (mm)	790	
Length with side brush	1,330 or 1,510	
Height with handle	900 or 1,060	
Height with handle dismantled	900 or 1,060	
Weight (kg)	24	

Vacuum Cleaner

Specifications

MAKE	MAKITA	K'ARCHER	POWER JET
MODEL	407	NT65/2Eco Me	PANDA 629
TYPE	Wet & Dry		Wet & Dry
Input (w)	1,050	2,750	2,400
Dimensions [L x W x H] (mm)	422 x 487 x 699	740 x 560 x 890	550 x 600 x 980
Tank capacity (ℓ)	30	65	78
Total weight (kg)	11		24

* Filter is sales item.

Sweeper

Specifications

MAKE	HAKO	
MODEL	JONAS900 V/E	845
Max. cleaning width (mm)	1,200	430
Sweeping speed (km/h)	6	4
Cleaning capacity (m ² /h)	7,200	2,000
Dust tank capacity (L)	30 x 2	42
Water tank capacity (L)	-	42
Engine rated output (kW[ps])	4.9/6.5	1.54/1.15
Dimensions	Overall length	500
	Overall length (driving)	1,500
	Overall width	1,000
	Overall height	1,330
Turning radius (mm)		
Operating weight (kg)	350	216



Pump



Water Pump 220V Single Phase

Specifications

Discharge bore (inch/mm)	Total head (m)	Capacity (m ³ /min)	Motor output (kW)	Dry weight (kg)	MODEL
220V 2-5/8	8	0.1	0.4	10	HS24S

Water Pump 380V 3 Phase

Specifications

Discharge bore (inch/mm)	Total head (m)	Capacity (m ³ /min)	Motor output (kW)	Dry weight (kg)	MODEL
2/50	15	0.25	1.5	29	KT21.5
3/75	10	0.6	2.2	34	KT232.2
4/100	10	1.0	3.7	62	KT243.7
6/150	15	1.6	7.5	107	KT267.5
4/100	15	1	5.5	86	KT245.5
6/150	15	2	11	158	KRS2D6
8/200	15	4	15	235	KRS815
8/200	10	4.0	11	174	KRS2-SS

Water Pump (High Head) 380V 3 Phase

Specifications

Discharge bore (inch/mm)	Total head (m)	Capacity (m ³ /min)	Motor output (kW)	Dry weight (kg)	MODEL
3/75	20	0.5	3.7	55	KT233.7
6/150	20	1.7	11	130	KT2611
4/100	35	1	11	130	KT2411

* Sunny hose & hose clip are sales item.

Engine Water Pump • Engine Flexible Pump

Specifications (Engine Water Pump)

MAKE	MODEL	Discharge bore (inch [mm])	Total head (m)	Capacity (m ³ /min)	Fuel tank Capacity (ℓ)	Fuel	Weight (kg)
HONDA	WB30XT	80/3	28	1.1	3.6	Petrol	29

* Sunny hose & hose clip are sales item.

Specifications (Flexible Pump)

MAKE	MODEL	Discharge bore (inch [mm])	Total head (m)	Capacity (m ³ /min)	Fuel tank Capacity (ℓ)	Fuel	Weight (kg)
MIKASA	WP-SLB	78/3	23	1.2	3.6	Petrol	54.2

* Sunny hose will be a sales item.



Residual Dewatering Pump

Specifications

Discharge bore (in/mm)	MODEL	Motor output (kW)	Phase	Total head (m)	Capacity (m ³ /min)	Dry weight (kg)	Voltage (V)
1/25	LSC-1.4S	0.4	Single	11	0.06	12	100

* Sunny hose will be a sales item.