

# Heavy Construction Machine For Rental

**NISHIO**

บริการเช่าเครื่องจักร รายวัน - รายเดือน - รายปี

## EXCAVATOR

Bucket Capacity 0.5 ~ 0.8m<sup>3</sup>



PC-200



ZX-200

### Specifications

M A K E		KOMATSU	KOMATSU	HITACHI
M O D E L		PC130-8	PC200	ZX200
Bucket capacity (m <sup>3</sup> )		0.5	0.8	0.8
Dimensions	Operating weight (kg)	12,700	19,100	19,400
	Overall length (mm)	A 7,590	9,425	9,620
	Overall height (mm)	B 2,855	3,000	2,950
	Overall width (mm)	C 2,490	2,970	2,800
	Track gauge (mm)	D 1,990	2,200	2,200
	Length of track on ground (mm)	E 2,880	3,270	3,370
	Track shoe width (mm)	F 500	800	600
	Ground clearance (mm)	G 400	440	450
Performance	Bucket capacity (m <sup>3</sup> )	0.5	0.8	0.8
	Bucket width (mm)	H 859	1,150	1,140
	Max. Digging depth (mm)	I 5,520	6,620	5,980
	Max. vertical wall digging depth (mm)	J 4,950	5,980	5,140
	Ground level max. reach (mm)	K 8,290	9,700	9,250
	Max. digging height (mm)	L 8,650	9,305	9,170
	Max. dumping height (mm)	M 6,210	6,475	6,390
	Boom swing angle / offset Boom	N-O	-	-
	Min. turn radius (m)	11.0	3.6	3.53
	Gradability (°)	35	35	35
Traveling speed (km/h)	L2.9/H5.5	5.5	5.5	
Engine	Rated output (ps/rpm)	93/2,200	134/2,000	147/2,100
Fuel tank capacity (ℓ)		Diesel 247	Diesel 340	Diesel 360


## Wheel Excavator Backhoe Loader

Wheel Excavator



SK100W

Dimension



### Specifications

M A K E		VOLVO	KOBELCO
M O D E L		EW145B	SK100W
Bucket capacity (m <sup>3</sup> )		0.58	0.45
Dimensions	Operating weight (kg)	13,100	11,110
	Overall length (mm)	A 7,479	6,835
	Overall height (mm)	B 3,058	3,550
	Overall width (mm)	C 2,496	2,486
	Tread (mm)	D 1,914	1,895
	Wheel base (mm)	E 2,800	2,600
	Ground clearance (mm)	G 350	265
	Performance	Bucket capacity (m <sup>3</sup> )	0.58
Bucket width (mm)		H 1,010	850
Max. Digging depth (mm)		I 4,396	4,260
Max. vertical wall digging depth (mm)		J 4,116	3,510
Ground level max. reach (mm)		K 7,544	7,080
Max. digging height (mm)		L 4,116	8,790
Max. dumping height (mm)		M 5,943	6,370
Boom swing angle / offset Boom		174	-
Min. turn radius (m)		6.9	6.4
Gradability (°)		-	31
Traveling speed (km/h)	37/10/3.6	36/9	
Engine	Rated output (ps/rpm)	150/110	128/2150
Fuel tank capacity (ℓ)		Diesel 260	Diesel 750

## Wheel Excavator Backhoe Loader

Backhole Loader



### Specifications

M A K E		KOMATSU	JCB
M O D E L		WB935R-5	3CX
Bucket capacity (m <sup>3</sup> )		0.08	0.22
Max. Loader capacity (m <sup>3</sup> )		1.03	1
Operating weight (kg)		7,460	8,425
Dimensions	Max height (m)	A 4.29	3.61
	Cab roof height (m)	B 2.75	1.36
	Max dumping height (m)	C 2.72	4.370
	Max digging height (m)	D 5.80	5.390
	Max digging depth (m)	E 5.02	3.410
	Overall length (m)	G 5.89	5.62
	Overall width (with bucket) (m)	H 2.32	12.13
	Ground clearance (m)	0.43	0.33
	Engine power (hp/rpm)		99.2/2,200
Fuel tank capacity (ℓ)		150	160

Motor Grader



GD655

### Specifications

M A K E		CAT	KOMATSU	MITSUBISHI
M O D E L		140H	GD655-5	MG430
Dimensions	Weight (kg)	21,261	18,120	13,285
	Overall length (mm)	A 10,097	10,575	8,595
	Overall width (mm)	B 2,464	2,600	2,420
	Overall height (mm)	C 3,103	3,200	3,070
	Wheel base (mm)	E 2,443	2,600	6,250
	Tread (mm)	F 2,077	2,165	2,000
	Distance between centre of tandem wheels (mm)	G 344	390	785
	Blade	Blade length (mm)	J 3,658	4,320
	Blade height (mm)	K 610	615	530
Min. turning radius (m)		7.5	7.3	6.9
Speed : forward (km/h)		44	44.3	6/44.1
Speed : reverse (km/h)		34.7	40.3	6/44.9
Engine	Fly wheel horse power (ps/rpm)	205/153	221/165	157
	Piston displacement (cc)	10.3	6.69	7.540
Fuel tank capacity (ℓ)		397	416	270

และยังมีเครื่องจักรอื่นๆให้เช่าอีกมากมาย

NishioRentAll

Rentall.co.th

