

Equipment Machine For Rental



บริการเช่าเครื่องจักร รายวัน - รายเดือน - รายปี



Generator (37kVA ~ 340kVA)



DCA45



DCA60



DCA150

Specifications

M O D E L		DCA25	DCA-45SPI	DCA-45ESI	DCA-60SPI	DCA-60ESI	DCA-90SPH	DCA100	SDG100
Alternator	Frequency	Hz	50/60		50				50/60
	Output rating	kVA	22	37	37	50	50	75	100
		kw		29.6	29.6	40	40	60	110
No. of phase			3-Phase, 4-Wire						
Rated voltage		V	Single Voltage System Line 190~215(220) or 380~430(440)						
Power factor			0.8(Lagging)						
Voltage regulation		%	Within±0.5	Within±1.5	Within±1.0	Within±1.5	Within±1.0	Within±1.5	Within±0.5
Excitation			Brushless, Rotating Exciter(With A.V.R.)						
Engine	Output rating	PS/rpm	32.2/1,800	46.5	46.5	64	66	95	124/1,800
		kW/min-1	23.7/1,800	34.2	34.2	47.07	48.5	69.87	91.3/1,800
	Fuel consumption	ℓ/h	4.2	6.5	6.5	9.4	8.8	12.3	20.7
	Fuel tank capacity	ℓ	70	100	100	125	125	185	225
Unit	Dimensions (LxWxH)	mm	1,540x680x900	2,000x880x1,250	2,000x880x1,250	2,420x880x1,250	2,050x880x1,250	2,900x1,050x1,400	2,750x1,050x1,350
	Dry weight	kg	564	1,180	1,180	1,400	1,240	1,975	1,730

M O D E L		DCA-125SPK	DCA-125ESM	DCA-150SPK	DCA-150ESH	SDG150	DCA-180SPK3	SDG220	DCA-220SPK	DCA400SPM	
Alternator	Frequency	Hz	50				50/60	50	50/60	50	
	Output rating	kVA	100	100	125	125	150	150	220	200	340
		kw	80	80	100	100	120	120	160	272	
No. of phase			3-Phase, 4-Wire								
Rated voltage		V	DUAL Voltage System Line 190~215(220) or 380~430(440)								
Power factor			0.8(Lagging)								
Voltage regulation		%	Within ± 0.5	Within ± 1.0	Within ± 1.5	Within ± 1.0	Within ± 0.5		Within ± 1.5	Within ± 1.5	
Excitation			Brushless, Rotating Exciter(With A.V.R.)								
Engine	Output rating	PS/rpm	133	145	153	153	153/1,800	185	270/1,800	242	400
		kW/min-1	97.8	107	113	113	112/1,800	136	199/1,800	178	294
	Fuel consumption	ℓ/h	15.5	16.5	19.5	19.3	17.4	22.4	26.2	29.4	51.4
	Fuel tank capacity	ℓ	250	250	250	250	250	300	390	380	490
Unit	Dimensions (LxWxH)	mm	3,000x1,080x1,500	3,280x1,080x1,500	3,350x1,200x1,500	3,200x1,180x1,500	2,990x1,180x1,480	3,300x1,200x1,500	3,700x1,300x1,670	3,650x1,300x1,750	4,300x1,400x2,100
	Dry weight	kg	2,120	2,290	2,740	2,360	2,430	2,900	3,630	3,670	4,700

Welding Machine Portable Generator



DLW300ES

Specifications

M A K E	Denyo		SHINDAIWA	
M O D E L	DLW300ES	DAW500S	DGW310	DGW510
Current range (A)	30-280	40-500	260/280	480/230
Engine rated output (ps)	17.5	34.5	11.7/3,000	29.0/3,600
Applicable electrode (mm)	2.0-6.0	2.0-8.0		
Weight (kg)	384	435	377	613
Dimensions (mm)	Length (mm)	1,410	1,260	1,410
	Height (mm)	680	800	760
	Width (mm)	760	870	566
Duty cycle	200A-100%	400A-100%	100	60
	300A-40%	500A-40%		80
Fuel tank capacity (ℓ)	Diesel 36	Diesel 45	37	63

Engine Welding Machine

Portable Generator



Specifications

M A K E	YUH	Makita
M O D E L	SH2900DX	G-2900LX
AC Output [Cont] (KVA)	2.5	2.1
AC Output [Max] (KVA)	3	2.4
Frequency (Hz)	50	50
Voltage (V) / Phase	220 / single	220 / single
Fuel	Petrol	Petrol
Fuel Tank Capacity (ℓ)	17	16.6
Fuel Consumption (ℓ/h)	1.0	1.4
Dimensions (mm)	Length	605
	Width	422
	Height	474
Weight (kg)	42	44kg

※ AVR ALTERNATOR (G-2900LX)

MOD-300



Arc Welding Machine

Specifications

M A K E	Palang	
M O D E L	MOD-300	MOD-500
Power source (V)	220	220
Input (kW/kVA)	13/24.5	23.5/44
Duty cycle (%)	40	60
Current range (A)	45-300	80-500
Dimensions [LxWxH] (cm)	41x63x74	49x72x79
Weight (kg)	120	192

Arc/Tig Welding Machine

Specifications

M O D E L	PTM-200	PTM-300
Power source (V)	380	380
Input (kW/kVA)	8.3/15.3	13/24.5
Duty cycle (%)	40	40
Current range (A)	AC	40-200
	DC	35-170
Dimensions [LxWxH] (cm)	47x73x63.5	49.5x80x73
Weight (kg)	104	137

และยังมีเครื่องจักรอื่นๆให้เช่าอีกมากมาย



NishioRentAll



Rentall.co.th

Air Compressor (Engine Type)

PDS125(s) PDS175(s) PDS390(s) PDS655(s)

Specifications

M A K E		AIRMAN						
M O D E L		PDS125(S)	PDS130(S)	PDS175(S)	PDS185	PDS390(S)	PDS655(S)	PDS750
Compressor		Rotary Twin Screw, Single-Stage, Oil-Cooled						
Type		Rotary Twin Screw, Single-Stage, Oil-Cooled						
Free air delivery	m ³ /min	3.5	3.7	5.0	5	11.0	18.5	21.2
Rated operating pressure	kg/cm ²	7	7.1	7.1	7	7.1	7.1	7.1
Air tank capacity	m ³	0.035	0.030	0.030	0.02	0.098	0.189	0.189
Engine								
No. of Air cock	mm(inch)×PCS	20A(3/4") × 2		20A(3/4") × 3	3/4" × 2	20A(3/4") × 4 50A(2") × 1	20A(3/4") × 2 50A(2")×1 10A(4")×1	3/4" × 3
Type		4cycle, water cooled direct-injection		4cycle, water cooled swirl chamber type		4cycle, water cooled direct-injection w/turbo charger	4cycle, water cooled direct-injection	4cycle, water cooled direct-injection w/turbo charger
No. of Cylinder		3		4	4	4	6	6
Total displacement	cc	1,422	1,662	2,179	2189	4,329	7,961	7,961
Rated output	ps(kW)/rpm	35.5(26.1)/3,450	38/3,000	51.5(37.9)/3,000	49.5(36.4)/3,000	110(80.9)/2,400	160(118)/2,500	196(144.5)/2,100
Fuel tank capacity	l	66	70	90	90	180	270	310
Lubrication oil capacity	l	8	6.0	8.5	7.4	13	23	23
Dimensions								
Length	mm	2,440	1,700	2,740	2,960	3,865	3,650	3,650
Width	mm	1,350	1,510	1,455	1,650	1,525	1,685	1,685
Height	mm	1,480	1,360	1,330	1,430	1,760	2,070	2,070
Weight	kg	860	960	1,000	960	1,915	3,190	3,335
Tyre size		5.00-10 6PR×2W		145R12 6PR×2W	175R13 8PR×2W	6.50-14 8PR×2W	6.50-14 8PR×4W	6.5-14 8PR×4W



PDS175S



PDS655S

Explosion Proof Light Balloon Light

Explosion Proof Light

Specifications

Model	Light Source			Power source			Weight
	Type	Volts	Watt	Out put	Air pressure	Consumption	
A-TL44	Halogen filled filament buldb	24V	250W	6000 lm/9000 lm	72 - 116 psi	18 - 20 cubic ft/min	12 lb
A-TL45	Halogen filled filament buldb	24V	250W	6000 lm/9000 lm	72 - 116 psi	18 - 20 cubic ft/min	15.5 lb



Balloon Light (Electric)

Specifications

Model	NMT910MZ
Bulb	Metal Halide
Watts (w)	1,000
Diameter (mm)	930
Running Height (mm)	3,400
Power Supply (V)	200-240
Ballast	Electromagnatique
Packaging	Transport Box



Balloon Light (Engine)

Specifications

Model	NMT910M
Bulb	Metal Halide
Watts (w)	1,000
Diameter (mm)	930
Length (mm)	1,055
Width (mm)	860
Height (mm)	3,400
Fuel Tank Capacity (L)	15
Fuel	Diesel
Weight (kg)	205



NISHIO RENT ALL (THAILAND) CO.,LTD.

- 02-326-0970 ลาดกระบัง
- 05-201-0336 เชียงใหม่

- 03-802-4624 ระยอง
- 02-665-7065 Event