




680W-720W

18BB Bifacial Double-Glass

KEY FEATURES



High Efficiency

Leading module efficiency in industry, the highest efficiency up to 23.82%



Excellent Appearance and Performance

Bifacial solar cell, symmetrical design, low risk of micro-crack



High Reliability

Passed 3*IEC standard test, 15 years materials warranty, 30 years output linear power warranty



Excellent Rear Side Power Generation

Bifaciality is up to 80%, up to 30% more energy yield than conventional modules



Better low irradiance performance

Higher power output even under low irradiance environments like on cloudy or foggy days



Extensive Application Scenes

More extensive application scenes, such as snow field, vertical installation, high humidity, strong wind and desert

Maximum Power Output

720W

Maximum Module Efficiency

23.23%

Power Output Tolerance

0-+3%

Product and Quality Certifications

IEC 61215, IEC 61730


ISO 9001: Quality Management System

ISO 14001: Environment Management System

ISO 45001: Occupational Health and Safety Management System

IEC 62716, IEC 61701: Ammonia, Salt mist corrosion test



IEC TS 62804-1, IEC 60068-2-68: PID test, Dust and Sand test




Leading Product and Power Warranty

-1.00%1st-Year Degradation -0.40%Annual Degradation 15Materials and Workmanship Warranty 30Linear Power Warranty

ENGINEERING DRAWING (mm)





A Long Frame



B Short Frame

CHARACTERISTIC CURVES (700W)



ELECTRICAL PARAMETERS (Test Condition is Based on the Front Side)

Module Type	N680H132G12D		N690H132G12D		N700H132G12D		N710H132G12D		N720H132G12D	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Nominal Max. Power(Pmax/W)	680	519	690	527	700	535	710	543	720	552
Open Circuit Voltage(Voc/V)	47.40	44.90	47.80	45.30	48.20	45.70	48.60	46.10	49.00	46.50
Short Circuit Current(Isc/A)	18.18	14.65	18.26	14.71	18.34	14.77	18.42	14.83	18.50	14.89
Maximum Power Voltage(Vmp/V)	39.60	37.10	40.00	37.50	40.40	37.90	40.80	38.30	41.20	38.70
Maximum Power Current(Imp/A)	17.20	13.98	17.27	14.05	17.34	14.12	17.41	14.19	17.48	14.26
Efficiency(%)	21.89%		22.21%		22.53%		22.85%		23.23%	

STC: Irradiance = 1000 W/m², Cell Temperature = 25°C, AM = 1.5, Average efficiency reduction of 4.5% at 200W/m².

NOCT: Irradiance = 800 W/m², Ambient Temperature = 20°C, AM = 1.5, Wind Speed = 1 m/s.

MECHANICAL PARAMETERS

Cell Type	210*105mm, 132HC		Connector	MC4 Original/Compatible	
Module Size&Weight	2384×1303×33mm, 38.8Kg		Junction Box	IP68, 3 Bypass Diodes	
Glass	2.0mm AR Coated Heat Strengthened Glass		Frame	Anodized Aluminium Alloy(Silver)	
Backsheet	2.0mm Ultra-Clear Float Glass		Cable	4mm ² , Cable Length 300mm(customized)	

TEMPERATURE COEFFICIENTS

Nominal Operating Cell Temperature	43°C(±2°C)	Temperature Coefficient of Voc	-0.250%/°C
Temperature Coefficient of Pmax	-0.310%/°C	Temperature Coefficient of Isc	+0.040%/°C

BACKSIDE POWER GAIN 10% FOR REFERENCE

Module Frontside Power(W)	680	690	700	710	720
Nominal Max. Power(Pmax/W)	748	759	770	781	792
Open Circuit Voltage(Voc/V)	47.4	47.8	48.2	48.6	49.0
Short Circuit Current(Isc/A)	19.95	20.04	20.13	20.22	20.31
Max. Power Voltage(Vmp/V)	39.6	40.0	40.4	40.8	41.2
Max. Power Current(Imp/A)	18.89	18.98	19.06	19.14	19.22

OPERATING PARAMETERS

Max. System Voltage	DC1500V
Power Tolerance	0 - +3%
Operating Temperature	-40°C - +85°C
Max. Fuse Rated Current	35A
Front Static Load	Snow 5400Pa, Wind 2400Pa
Packaging Data	33PCS/Pallet; 594PCS/40HQ